General Services Administration
FEDERAL ACQUISITION SERVICE

AUTHORIZED FEDERAL SUPPLY SCHEDULEPRICELIST

Multiple Award Schedule (MAS)
Code E – Industrial Products and Services &
Code G – Miscellaneous
PSC 4630

Eddy Pump Corporation
15405 Olde Highway 80
El Cajon, CA 92021
619-345-5446
Info@eddypump.com

www.eddypump.com

Contract Administrator:
Rebecca Weinrib
619-258-7020
rw@eddypump.com

Business Size: Small

Contract #47QSWA20D000G
Contract Period: November 1, 2019 through October 31, 2024

Pricelist Updated through Modification PO-0004 - Effective May 4, 2020

For more information on ordering from Federal Supply Schedules click on:
http://www.gsa.gov/portal/category/100611

CUSTOMER INFORMATION:

1a. Table of awarded special item numbers:

- **SIN 325998W: Water Treatment Products and Systems**
- **SIN OLM: Order-Level Materials (OLM)**

1b. Lowest priced Models per SIN:

SIN 325998W: Part Number – ES2000 $23,425.69
SIN OLM: Not Applicable

2. Maximum Order*: **Per SIN 325998W: $300,000**
Per SIN OLM: None

*Ordering activities may request a price reduction at any time before placing an order, establishing a BPA, or in conjunction with the annual BPA review. However, the ordering activity shall seek a price reduction when the order or BPA exceeds the simplified acquisition threshold. Schedule contractors are not required to pass on to all schedule users a price reduction extended only to an individual ordering activity for a specific order or BPA.

3. Minimum order: **$0.00**

4. Geographic coverage: **Domestic, 48 states, Washington, DC, and to a CONUS port or consolidation point for orders received from overseas activities.**

5. Point of production: **El Cajon, California USA**

6. Discount from list price: **Net Price - the prices shown are GSA net, the discounts have been deducted and the GSA IFF has been added**

7. Quantity discounts:

6 – 10 Units = 10% Discount
11 to 25 Units = 15% Discount
25+ Units = 20% Discount

8. Prompt payment terms: **Net 30**

9a. The Government purchase cards must be accepted at or below the micro-purchase threshold.

9b. Government Purchase Cards are accepted above the micro-purchase threshold. Contact contractor for limit.

10. Foreign items: **Not Applicable**

11a. Time of delivery:

10 to 14 Weeks – Contact Eddy Pump for additional information.

11b. Expedited Delivery: **Contact Eddy Pump for additional information.**

11c. Overnight and 2-Day Delivery: **Not applicable.**

11d. Urgent Requirements: **Not applicable.**

12. F.O.B point: **Origin**

13a. Ordering Address:

15405 Olde Highway 80
El Cajon, CA 92021

13b. ORDERING PROCEDURES: **For supplies and services, the ordering procedures, information on Blanket Purchase Agreements (BPA's) are found in FAR 8.405-3**

14. Payment Address:

15405 Olde Highway 80
El Cajon, CA 92021

15. Warranty provision: **Standard Warranty – 1 Year Limited Warranty**

16. Export packing charges: **Not Applicable**

17. Contractor **will accept** Government purchase cards above the micro-purchase level.

18. Terms and Conditions applicable to maintenance and repair: **Maintenance and Repair costs are available open market from Eddy Pump.**

19. Terms and conditions for installation: **Not Applicable**

20a. Terms and conditions of repair parts indicating date of parts price lists and any discounts from list prices (if applicable): **Not Applicable**

20b. Terms and conditions for any other services: **Not Applicable**

21. List of service and distribution points:

15405 Olde Highway 80
El Cajon, CA 92021

22. List of participating dealers (if applicable): **Not Applicable**

23. Preventive maintenance (if applicable): **Contact Eddy Pump**

24a. Environmental attributes, e.g., recycled content, energy efficiency, and/or reduced pollutants: **Not Applicable**

24b. Section 508 Compliance for Electronic and Information Technology (EIT): **Not Applicable.**

25. Data Universal Number System (DUNS) number. **153432349**

26. Notification regarding registration in System for Award Management (SAM):

Eddy Pump Corporation is registered with SAM and the registration is active.

Eddy Pump Corporation – Schedule Pricing

SIN 325998W: Water Treatment Products and Systems

SIN	Part #	Product Name	Unit of Issue	Product Description	GSA Price
485	SMSPD2000	2-Inch Skid Mounted Diesel Solids Pump	Each	2-Inch Skid Mounted Self-Priming Diesel Solids Pump - EDDY Slurry & Sludge Pumps are designed for high solids industrial pump applications. Our slurry pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult pumping applications. The 2" EDDY Pump's open rotor design with high tolerances allow pumping of up to 1.75" solids without issues. Operating Levels: 50-390 Gallons Per Minute (GPM) at TDH of up to 90 feet. 1800 RPM motor speed. Percentage of solids up to 40-70%. Standard Materials for wet ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Dredging, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash, Coal Ash, Wastewater. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Design. This is a self-priming pump designed to prime automatically by being submerged in the fluid to be pumped, there is no need for manual priming.	$37,481.11
485	SMSPD3000	3-Inch Skid Mounted Diesel Solids Pump	Each	3-Inch Skid Mounted Self-Priming Diesel Solids Pump - EDDY Slurry & Sludge Pumps are designed for high solids industrial pump applications. Our slurry pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult pumping applications. The 3" EDDY Pump's open rotor design with high tolerances allow pumping of up to 3" solids without issues. Operating Levels: 100-780 Gallons Per Minute (GPM) at TDH of up to 130 feet. 1800 RPM motor speed. Percentage of solids up to 40-70%. Standard Materials for wet ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Dredging, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash, Coal Ash, Wastewater. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Design. This is a self-priming pump designed to prime automatically by being submerged in the fluid to be pumped, there is no need for manual priming.	$46,851.39

485	**SMSPE2000**	**2-Inch Skid Mounted Electric Solids Pump**	**Each**	2-inch Skid Mounted Self-Priming Electric Driven Non-Clog High Solids Pump - EDDY Slurry & Sludge Pumps are for high solids industrial pump applications. Our slurry pump technology outperforms all centrifugal, vortex and positive displacement pumps in the most difficult pumping applications. The 2" EDDY Pump's open rotor design with high tolerances allow pumping of up to 1.75" solids without issues. Operating Levels: 50-390 Gallons Per Minute (GPM) at TDH up to 90 feet. 1800 RPM motor speed. Percentage of solids up to 40-70%. Standard Materials: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Dredging, Chemical, Sand & Agg, Oil & Gas, Paper & Pulp, Fly Ash, Coal Ash, Wastewater. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Design. This is a self-priming pump designed to prime automatically by being submerged in the fluid to be pumped, there is no need for manual priming.	**$32,795.97**
485	**SMSPE3000**	**3-Inch Skid Mounted Electric Solids Pump**	**Each**	3-inch Skid Mounted Self-Priming Electric Driven Non-Clog High Solids Pump - EDDY Slurry & Sludge Pumps are for high solids industrial pump applications. Our slurry pump technology outperforms all centrifugal, vortex and positive displacement pumps in the most difficult pumping applications. The 3" EDDY Pump's open rotor design with high tolerances allow pumping of up to 3" solids without issues. Operating Levels: 100-780 Gallons Per Minute (GPM) at TDH of up to 130 feet. 1800 RPM motor speed. Percentage of solids up to 40-70%. Standard Materials: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Dredging, Chemical, Sand & Agg, Oil & Gas, Paper & Pulp, Fly Ash, Coal Ash, Wastewater. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Design. This is a self-priming pump designed to prime automatically by being submerged in the fluid to be pumped, there is no need for manual priming.	**$42,166.25**

485	**TMSPD2000**	**2-Inch Trailer Mounted Diesel Solids Pump**	**Each**	2-inch Trailer Mounted Self-Priming Diesel Solids Pump - EDDY Slurry & Sludge Pumps are designed for high solids industrial pump applications. Our slurry pump technology outperforms all centrifugal, vortex and positive displacement pumps in the most difficult pumping applications. The 2" EDDY Pump's open rotor design with high tolerances allow pumping of up to 1.75" solids without issues. Operating Levels: 50-390 Gallons Per Minute (GPM) at TDH of up to 90 feet. 1800 RPM motor speed. Percentage of solids up to 40-70%. Standard Materials: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Dredging, Chemical, Sand & Agg, Oil & Gas, Paper & Pulp, Fly Ash, Coal Ash, Wastewater. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Design. This is a self-priming pump designed to prime automatically by being submerged in the fluid to be pumped, there is no need for manual priming.	**$42,166.25**
485	**TMSPD3000**	**3-Inch Trailer Mounted Diesel Solids Pump**	**Each**	3-inch Trailer Mounted Self-Priming Diesel Driven Non-Clog High Solids Pump - Eddy non-clog pumps are designed for high solids industrial pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in the most difficult pumping applications. The 3" EDDY Pump's open rotor design with high tolerances allow pumping of up to 3" solids without issues. Operating Levels: 50-390 Gallons Per Minute (GPM) at TDH of up to 130 feet. 1800 RPM motor Percentage of solids up to 40-70%. Standard Materials for wet ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Dredging, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash, Coal Ash, Wastewater. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Design. This is a self-priming pump designed to prime automatically by being submerged in the fluid to be pumped, there is no need for manual priming.	**$51,536.52**

485	**TMSPE2000**	**2-Inch Trailer Mounted Electric Solids Pump**	**Each**	2-inch Trailer Mounted Self-Priming Electric Driven Non-Clog High Solids Pump - Eddy slurry pumps are designed for high solids industrial pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in the most difficult pumping applications. The 2" EDDY Pump's open rotor design with high tolerances allow pumping of up to 1.75" solids without issues. Operating Levels: 50-390 Gallons Per Minute (GPM) at TDH of up to 90 feet. 1800 RPM motor Percentage of solids up to 40-70%. Standard Materials for wet ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Dredging, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash, Coal Ash, Wastewater. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Design. This is a self-priming pump designed to prime automatically by being submerged in the fluid to be pumped, there is no need for manual priming.	**$37,481.11**

485	**TMSPE3000**	**3-Inch Trailer Mounted Electric Solids Pump**	**Each**	3-inch Trailer Mounted Self-Priming Electric Driven Non-Clog High Solids Pump - Eddy slurry pumps are designed for high solids industrial pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in the most difficult pumping applications. The 3" EDDY Pump's open rotor design with high tolerances allow pumping of up to 3" solids without issues. Operating Levels: 100-780 Gallons Per Minute (GPM) at TDH of up to 130 feet. 1800 RPM motor Percentage of solids up to 40-70%. Standard Materials for wet ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Dredging, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash, Coal Ash, Wastewater. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Design. This is a self-priming pump designed to prime automatically by being submerged in the fluid to be pumped, there is no need for manual priming.	**$46,851.39**
485	**ES2000**	**2-Inch Electric Submersible Solids Sump Pump**	**Each**	2-inch Electric Driven Submersible Non-Clog High Solids Sump Pump - Slurry pumps that are completely submerged in the liquid are called submersible pumps. By being submerged in the fluid to be pumped, there is no need for priming. Operating Levels: 50-390 Gallons Per Minute (GPM) at TDH up to 90 feet. Ability to transport up to 40-70% Solids. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand & Agg, Oil and Gas, Paper and Pulp, Manufacturing, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. The 2-inch EDDY Pump's open rotor design with high tolerances allow pumping of up to 1.75-inch solids without issues. This means more uptime, less clogs, less maintenance, and lower cost of ownership.	**$23,425.69**

485	**ES3000**	**3-Inch Electric Submersible Solids Sump Pump**	**Each**	3-inch Electric Driven Submersible Non-Clog High Solids Sump Pump - Slurry pumps that are completely submerged in the liquid are called submersible pumps. By being submerged in the fluid to be pumped, there is no need for priming. Operating Levels: 100-780 Gallons Per Minute (GPM) at TDH up to 130 feet. Ability to transport up to 40-70% Solids. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand & Agg, Oil and Gas, Paper and Pulp, Manufacturing, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. The 3-inch EDDY Pump's open rotor design with high tolerances allow pumping of up to 3-inch solids without issues. This means more uptime, less clogs, less maintenance, and lower cost of ownership.	**$28,110.83**
485	**HS2000**	**2-Inch Hydraulic Submersible Solids Sump Pump**	**Each**	2-inch Hydraulic Driven Submersible Non-Clog High Solids Sump Pump - Slurry Pumps that are completely submerged in the liquid are called submersible pumps. By being submerged in the fluid to be pumped, there is no need for priming. Operating Levels: 50-390 Gallons Per Minute (GPM) at TDH up to 90 feet. Ability to transport up to 40-70% Solids. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand & Agg, Oil and Gas, Paper and Pulp, Manufacturing, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. The 2-inch EDDY Pump's open rotor design with high tolerances allow pumping of up to 1.75-inch solids without issues. This means more uptime, less clogs, less maintenance, and lower cost of ownership.	**$28,110.83**

485	**HS3000**	**3-Inch Hydraulic Submersible Solids Sump Pump**	**Each**	3-inch Hydraulic Driven Submersible Non-Clog High Solids Sump Pump - Slurry pumps that are completely submerged in the liquid are called submersible pumps. By being submerged in the fluid to be pumped, there is no need for priming. Operating Levels: 100-780 Gallons Per Minute (GPM) at TDH up to 130 feet. Ability to transport up to 40-70% Solids. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand & Agg, Oil and Gas, Paper and Pulp, Manufacturing, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. The 3-inch EDDY Pump's open rotor design with high tolerances allow pumping of up to 3-inch solids without issues. This means more uptime, less clogs, less maintenance, and lower cost of ownership.	**$32,795.97**
485	**ESUB4000**	**4-inch Electric Remote-Operated Submersible Dredge (Subdredge)**	**Each**	4-inch Electric Driven Remote-Operated Submersible Non-Clog Dredge. Operating Levels: Minimum Flow is 250 Gallons Per Minute (GPM). Maximum Flow is 2,100 Gallons Per Minute (GPM). Head Range up to 160 feet. Solids handling up to 3-inches. 1800 RPM Motor Speed. Percentage of solids up to 40-70%. Cubic Yard Material Per Hour is 55-475. Controls: Handheld wireless controller with live redundant controller and ruggedized laptop. Application specific software for easy operation. Applications: Subsea Dredging, Below Structures and Ships, Liner Safe Dredging (Clay, Poly, Concrete, etc.), Tailings Ponds, Concrete Canals, and Spent Material Basins. Features and Benefits: Safety, Ideal for Hazardous Areas. Subdredge supports Cutterhead, Non-Clog, and Self-Cleaning Head Configurations. Transport 40-70% Solids. Rubber Tracks Prevent Liner Damage.	**$562,216.62**

485	**ESUB6000**	**6-inch Electric Remote-Operated Submersible Dredge (Subdredge)**	**Each**	6-inch Electric Driven Remote-Operated Submersible Non-Clog Dredge. Operating Levels: Minimum Flow is 450 Gallons Per Minute (GPM). Maximum Flow is 2500 Gallons Per Minute (GPM). Head Range up to 200 feet. Solids handling up to 5 inches. 1800 RPM Motor Speed. Percentage of solids up to 40-70%. Cubic Yard Material Per Hour is 55-475. Controls: Handheld wireless controller with live redundant controller and ruggedized laptop. Application specific software for easy operation. Applications: Subsea Dredging, Below Structures and Ships, Liner Safe Dredging (Clay, Poly, Concrete, etc.), Tailings Ponds, Concrete Canals, and Spent Material Basins. Features and Benefits: Safety, Ideal for Hazardous Areas. Subdredge supports Cutterhead, Non-Clog, and Self-Cleaning Head Configurations. Transport 40-70% Solids. Rubber Tracks Prevent Liner Damage.	**$702,770.78**
485	**ESUB8000**	**8-inch Electric Remote-Operated Submersible Dredge (Subdredge)**	**Each**	8-inch Electric Driven Remote-Operated Submersible Non-Clog Dredge. Operating Levels: Minimum Flow is 1400 Gallons Per Minute (GPM). Maximum Flow is 3600 Gallons Per Minute (GPM). Head Range up to 230 feet. Solids handling up to 7 inches. 1200 RPM Motor Speed. Percentage of solids up to 40-70%. Cubic Yard Material Per Hour is 55-475. Controls: Handheld wireless controller with live redundant controller and ruggedized laptop. Application specific software for easy operation. Applications: Subsea Dredging, Below Structures and Ships, Liner Safe Dredging (Clay, Poly, Concrete, etc.), Tailings Ponds, Concrete Canals, and Spent Material Basins. Features and Benefits: Safety, Ideal for Hazardous Areas. Subdredge supports Cutterhead, Non-Clog, and Self-Cleaning Head Configurations. Transport 40-70% Solids. Rubber Tracks Prevent Liner Damage.	**$937,027.71**

485	**ESUB10000**	**10-inch Electric Remote-Operated Submersible Dredge (Subdredge)**	**Each**	10-inch Electric Driven Remote-Operated Submersible Non-Clog Dredge. Operating Levels: Minimum Flow is 1600 Gallons Per Minute (GPM). Maximum Flow is 5000 Gallons Per Minute (GPM). Head Range up to 200 feet. Solids handling up to 9 inches. 1200 RPM Motor Speed. Percentage of solids up to 40-70%. Cubic Yard Material Per Hour is 55-475. Controls: Handheld wireless controller with live redundant controller and ruggedized laptop. Application specific software for easy operation. Applications: Subsea Dredging, Below Structures and Ships, Liner Safe Dredging (Clay, Poly, Concrete, etc.), Tailings Ponds, Concrete Canals, and Spent Material Basins. Features and Benefits: Safety, Ideal for Hazardous Areas. Subdredge supports Cutterhead, Non-Clog, and Self-Cleaning Head Configurations. Transport 40-70% Solids. Rubber Tracks Prevent Liner Damage.	**$1,030,730.48**
485	**ESUB12000**	**12-inch Electric Remote-Operated Submersible Dredge (Subdredge)**	**Each**	12-inch Electric Driven Remote-Operated Submersible Non-Clog Dredge. Operating Levels: Minimum Flow is 2600 Gallons Per Minute (GPM). Maximum Flow is 7300 Gallons Per Minute (GPM). Head Range up to 180 feet. Solids handling up to 11 inches. 900 RPM Motor Speed. Percentage of solids up to 40-70%. Cubic Yard Material Per Hour is 55-475. Controls: Handheld wireless controller with live redundant controller and ruggedized laptop. Application specific software for easy operation. Applications: Subsea Dredging, Below Structures and Ships, Liner Safe Dredging (Clay, Poly, Concrete, etc.), Tailings Ponds, Concrete Canals, and Spent Material Basins. Features and Benefits: Safety, Ideal for Hazardous Areas. Subdredge supports Cutterhead, Non-Clog, and Self-Cleaning Head Configurations. Transport 40-70% Solids. Rubber Tracks Prevent Liner Damage.	**$1,405,541.56**

485	**HSUB4000**	**4-inch Hydraulic Remote-Operated Submersible Dredge (Subdredge)**	**Each**	4-inch Hydraulic Driven Remote-Operated Submersible Non-Clog Dredge. Operating Levels: Minimum Flow is 250 Gallons Per Minute (GPM). Maximum Flow is 2,100 Gallons Per Minute (GPM). Head Range up to 160 feet. Solids handling up to 3 inches. 1800 RPM Motor Speed. Percentage of solids up to 40-70%. Cubic Yard Material Per Hour is 55-475. Controls: Handheld wireless controller with live redundant controller and ruggedized laptop. Application specific software for easy operation. Applications: Subsea Dredging, Below Structures and Ships, Liner Safe Dredging (Clay, Poly, Concrete, etc.), Tailings Ponds, Concrete Canals, and Spent Material Basins. Features and Benefits: Safety, Ideal for Hazardous Areas. Subdredge supports Cutterhead, Non-Clog, and Self-Cleaning Head Configurations. Transport 40-70% Solids. Rubber Tracks Prevent Liner Damage.	**$562,216.62**
485	**HSUB6000**	**6-inch Hydraulic Remote-Operated Submersible Dredge (Subdredge)**	**Each**	6-inch Hydraulic Driven Remote-Operated Submersible Non-Clog Dredge. Operating Levels: Minimum Flow is 800 Gallons Per Minute (GPM). Maximum Flow is 2500 Gallons Per Minute (GPM). Head Range up to 200 feet. Solids handling up to 5 inches. 1800 RPM Motor Speed. Percentage of solids up to 40-70%. Cubic Yard Material Per Hour is 55-475. Controls: Handheld wireless controller with live redundant controller and ruggedized laptop. Application specific software for easy operation. Applications: Subsea Dredging, Below Structures and Ships, Liner Safe Dredging (Clay, Poly, Concrete, etc.), Tailings Ponds, Concrete Canals, and Spent Material Basins. Features and Benefits: Safety, Ideal for Hazardous Areas. Subdredge supports Cutterhead, Non-Clog, and Self-Cleaning Head Configurations. Transport 40-70% Solids. Rubber Tracks Prevent Liner Damage.	**$702,770.78**

485	**HSUB8000**	**8-inch Hydraulic Remote-Operated Submersible Dredge (Subdredge)**	**Each**	8-inch Hydraulic Driven Remote-Operated Submersible Non-Clog Dredge. Operating Levels: Minimum Flow is 1400 Gallons Per Minute (GPM). Maximum Flow is 3600 Gallons Per Minute (GPM). Head Range up to 230 feet. Solids handling up to 7 inches. 1200 RPM Motor Speed. Percentage of solids up to 40-70%. Cubic Yard Material Per Hour is 55-475. Controls: Handheld wireless controller with live redundant controller and ruggedized laptop. Application specific software for easy operation. Applications: Subsea Dredging, Below Structures and Ships, Liner Safe Dredging (Clay, Poly, Concrete, etc.), Tailings Ponds, Concrete Canals, and Spent Material Basins. Features and Benefits: Safety, Ideal for Hazardous Areas. Subdredge supports Cutterhead, Non-Clog, and Self-Cleaning Head Configurations. Transport 40-70% Solids. Rubber Tracks Prevent Liner Damage.	**$819,899.24**
485	**HSUB10000**	**10-inch Hydraulic Remote-Operated Submersible Dredge (Subdredge)**	**Each**	10-inch Hydraulic Driven Remote-Operated Submersible Non-Clog Dredge. Operating Levels: Minimum Flow is 1600 Gallons Per Minute (GPM). Maximum Flow is 5000 Gallons Per Minute (GPM). Head Range up to 240 feet. Solids handling up to 9 inches. 1200 RPM Motor Speed. Percentage of solids up to 40-70%. Cubic Yard Material Per Hour is 55-475. Controls: Handheld wireless controller with live redundant controller and ruggedized laptop. Application specific software for easy operation. Applications: Subsea Dredging, Below Structures and Ships, Liner Safe Dredging (Clay, Poly, Concrete, etc.), Tailings Ponds, Concrete Canals, and Spent Material Basins. Features and Benefits: Safety, Ideal for Hazardous Areas. Subdredge supports Cutterhead, Non-Clog, and Self-Cleaning Head Configurations. Transport 40-70% Solids. Rubber Tracks Prevent Liner Damage.	**$866,750.63**

485	**HSUB12000**	**12-inch Hydraulic Remote-Operated Submersible Dredge (Subdredge)**	**Each**	12-inch Hydraulic Driven Remote-Operated Submersible Non-Clog Dredge. Operating Levels: Minimum Flow is 2600 Gallons Per Minute (GPM). Maximum Flow is 7300 Gallons Per Minute (GPM). Head Range up to 180 feet. Solids handling up to 11 inches. 900 RPM Motor Speed. Percentage of solids up to 40-70%. Cubic Yard Material Per Hour is 55-475. Controls: Handheld wireless controller with live redundant controller and ruggedized laptop. Application specific software for easy operation. Applications: Subsea Dredging, Below Structures and Ships, Liner Safe Dredging (Clay, Poly, Concrete, etc.), Tailings Ponds, Concrete Canals, and Spent Material Basins. Features and Benefits: Safety, Ideal for Hazardous Areas. Subdredge supports Cutterhead, Non-Clog, and Self-Cleaning Head Configurations. Transport 40-70% Solids. Rubber Tracks Prevent Liner Damage.	**$1,218,136.02**
485	**ESUMP2000**	**2-inch Electric Sump Pump with Internal Chopper**	**Each**	2-inch Electric Driven Non-Clog Sump Pump with Internal Chopper Blade. Designed for high solids industrial slurry pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult applications. Operating Levels: 50-390 Gallons Per Minute (GPM), TDH up to 90 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design: Transport 40-70% Solids. 1800 RPM max motor speed. The 2-inch EDDY Pump has the ability to pump objects of up to 1.75-inches in diameter.	**$25,299.75**

485	**ESUMP3000**	**3-inch Electric Sump Pump with Internal Chopper**	**Each**	3-inch Electric Driven Non-Clog Sump Pump with Internal Chopper Blade. Designed for high solids industrial slurry pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult applications. Operating Levels: 100-780 Gallons Per Minute (GPM), TDH up to 130 feet. Pump solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design: Transport 40-70% Solids. 1800 RPM max motor speed. The 3-inch EDDY Pump has the ability to pump objects of up to 3-inches in diameter.	**$29,984.89**
485	**ESUMP4000**	**4-inch Electric Sump Pump with Internal Chopper**	**Each**	4-inch Electric Driven Non-Clog Sump Pump with Internal Chopper Blade. Designed for high solids industrial slurry pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult applications. Operating Levels: 250-2100 Gallons Per Minute (GPM), TDH up to 160 feet. Pump solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design: Transport 40-70% Solids. 1800 RPM max motor speed. The 4-inch EDDY Pump has the ability to pump objects of up to 4-inches in diameter.	**$43,103.27**

485	**ESUMP6000**	**6-inch Electric Sump Pump with Internal Chopper**	**Each**	6-inch Electric Driven Non-Clog Sump Pump with Internal Chopper Blade. Designed for high solids industrial slurry pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult applications. Operating Levels: 450-2500 Gallons Per Minute (GPM), TDH up to 200 feet. Pump solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design: Transport 40-70% Solids. 1800 RPM max motor speed. The 6-inch EDDY Pump has the ability to pump objects of up to 6-inches in diameter.	**$56,221.66**
485	**ESUMP8000**	**8-inch Electric Sump Pump with Internal Chopper**	**Each**	8-inch Electric Driven Non-Clog Sump Pump with Internal Chopper Blade. Designed for high solids industrial slurry pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult applications. Operating Levels: 1400-3600 Gallons Per Minute (GPM), TDH up to 230 feet. Pump solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design: Transport 40-70% Solids. 1200 RPM max motor speed. The 8-inch EDDY Pump has the ability to pump objects of up to 8-inches in diameter.	**$74,962.22**

485	**ESUMP1000**	**10-inch Electric Sump Pump with Internal Chopper**	**Each**	10-inch Electric Driven Non-Clog Sump Pump with Internal Chopper Blade. Designed for high solids industrial slurry pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult applications. Operating Levels: 1600-5000 Gallons Per Minute (GPM), TDH up to 240 feet. Pump solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design: Transport 40-70% Solids. 1200 RPM max motor speed. The 10-inch EDDY Pump has the ability to pump objects of up to 10-inches in diameter.	**$79,647.36**
485	**ESUMP12000**	**12-inch Electric Sump Pump with Internal Chopper**	**Each**	12-inch Electric Driven Non-Clog Sump Pump with Internal Chopper Blade. Designed for high solids industrial slurry pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult applications. Operating Levels: 2600-7300 Gallons Per Minute (GPM), TDH up to 180 feet. Pump solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design: Transport 40-70% Solids. 900 RPM max motor speed. The 12-inch EDDY Pump has the ability to pump objects of up to 12-inches in diameter.	**$103,073.05**

485	**HSUMP2000**	**2-inch Hydraulic Sump Pump with Internal Chopper**	**Each**	2-inch Hydraulic Driven Non-Clog Sump Pump with Internal Chopper Blade. Designed for high solids industrial slurry pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult applications. Operating Levels: 100-500 Gallons Per Minute (GPM), TDH up to 90 feet. Pump solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design: Transport 40-70% Solids. 1800 RPM max motor speed. The 2-inch EDDY Pump has the ability to pump objects of up to 1.75-inches in diameter.	**$29,984.89**
485	**HSUMP3000**	**3-inch Hydraulic Sump Pump with Internal Chopper**	**Each**	3-inch Hydraulic Driven Non-Clog Sump Pump with Internal Chopper Blade. Designed for high solids industrial slurry pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult applications. Operating Levels: 2600-7300 Gallons Per Minute (GPM), TDH up to 180 feet. Pump solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design: Transport 40-70% Solids. 1800 RPM max motor speed. The 3-inch EDDY Pump has the ability to pump objects of up to 3-inches in diameter.	**$34,670.03**

485	**HSUMP4000**	**4-inch Hydraulic Sump Pump with Internal Chopper**	**Each**	4-inch Hydraulic Driven Non-Clog Sump Pump with Internal Chopper Blade. Designed for high solids industrial slurry pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult applications. Operating Levels: 250-2100 Gallons Per Minute (GPM), TDH up to 130 feet. Pump solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design: Transport 40-70% Solids. 1800 RPM max motor speed. The 4-inch EDDY Pump has the ability to pump objects of up to 4-inches in diameter.	**$52,473.55**
485	**HSUMP6000**	**6-inch Hydraulic Sump Pump with Internal Chopper**	**Each**	6-inch Hydraulic Driven Non-Clog Sump Pump with Internal Chopper Blade. Designed for high solids industrial slurry pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult applications. Operating Levels: 450-2500 Gallons Per Minute (GPM), TDH up to 200 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design: Transport 40-70% Solids. 1800 RPM max motor speed. The 6-inch EDDY Pump has the ability to pump objects of up to 6-inches in diameter.	**$63,717.88**

485	**HSUMP8000**	**8-inch Hydraulic Sump Pump with Internal Chopper**	**Each**	8-inch Hydraulic Driven Non-Clog Sump Pump with Internal Chopper Blade. Designed for high solids industrial slurry pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult applications. Operating Levels: 1400-3600 Gallons Per Minute (GPM), TDH up to 160 feet. Pump solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design: Transport 40-70% Solids. 1200 RPM max motor speed. The 8-inch EDDY Pump has the ability to pump objects of up to 8-inches in diameter.	**$84,332.49**
485	**HSUMP10000**	**10-inch Hydraulic Sump Pump with Internal Chopper**	**Each**	10-inch Hydraulic Driven Non-Clog Sump Pump with Internal Chopper Blade. Designed for high solids industrial slurry pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult applications. Operating Levels: 1600-5000 Gallons Per Minute (GPM), TDH up to 200 feet. Pump solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design: Transport 40-70% Solids. 1200 RPM max motor speed. The 10-inch EDDY Pump has the ability to pump objects of up to 10-inches in diameter.	**$89,017.63**

485	**HSUMP12000**	**12-inch Hydraulic Sump Pump with Internal Chopper**	**Each**	12-inch Hydraulic Driven Non-Clog Sump Pump with Internal Chopper Blade. Designed for high solids industrial slurry pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult applications. Operating Levels: 2600-7300 Gallons Per Minute (GPM), TDH up to 180 feet. Pump solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design: Transport 40-70% Solids. 900 RPM max motor speed. The 12-inch EDDY Pump has the ability to pump objects of up to 12-inches in diameter.	**$117,128.46**
485	**EXSUMP2000**	**2-inch Extended Shaft Electric Sump Pump Submersible with Dry Motor**	**Each**	2-inch Extended Shaft Electric Driven Sump Pump. Submersible Non-Clog Pump with Dry Motor and Internal Chopper Blade. Designed for high solids industrial pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult pumping applications. Operating Levels: 50-390 Gallons Per Minute (GPM) at TDH up to 90 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%,Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump objects of up to 1.75-inches in diameter.	**$28,110.83**

485	**EXSUMP3000**	**3-inch Extended Shaft Electric Sump Pump Submersible with Dry Motor**	**Each**	3-inch Extended Shaft Electric Driven Sump Pump. Submersible Non-Clog Pump with Dry Motor and Internal Chopper Blade. Designed for high solids industrial pumping applications. Our patented pump technology outperforms all centrifugal, vortex and displacement pumps in a variety of the most difficult pumping applications. Operating Levels: 100-780 Gallons Per Minute (GPM) at TDH up to 130 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%,Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump objects of up to 3-inches in diameter.	**$32,795.97**
485	**EXSUMP4000**	**4-inch Extended Shaft Electric Sump Pump Submersible with Dry Motor**	**Each**	4-inch Extended Shaft Electric Driven Sump Pump. Submersible Non-Clog Pump with Dry Motor and Internal Chopper Blade. Designed for high solids industrial pumping applications. Our patented pump technology outperforms all centrifugal, vortex and displacement pumps in a variety of the most difficult pumping applications. Operating Levels: 250-2100 Gallons Per Minute (GPM) at TDH up to 160 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%,Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump objects of up to 4-inches in diameter.	**$46,851.39**

485	**EXSUMP6000**	**6-inch Extended Shaft Electric Sump Pump Submersible with Dry Motor**	**Each**	6-inch Extended Shaft Electric Driven Sump Pump. Submersible Non-Clog Pump with Dry Motor and Internal Chopper Blade. Designed for high solids industrial pumping applications. Our patented pump technology outperforms all centrifugal, vortex and displacement pumps in a variety of the most difficult pumping applications. Operating Levels: 450-2000 Gallons Per Minute (GPM) at TDH up to 200 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%,Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump objects of up to 6-inches in diameter.	**$60,906.80**
485	**EXSUMP8000**	**8-inch Extended Shaft Electric Sump Pump Submersible with Dry Motor**	**Each**	8-inch Extended Shaft Electric Driven Sump Pump. Submersible Non-Clog Pump with Dry Motor and Internal Chopper Blade. Designed for high solids industrial pumping applications. Our patented pump technology outperforms all centrifugal, vortex and displacement pumps in a variety of the most difficult pumping applications. Operating Levels: 1400-3600 Gallons Per Minute (GPM) at TDH up to 230 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%,Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump objects of up to 8-inches in diameter.	**$79,647.36**

485	**EXSUMP10000**	**10-inch Extended Shaft Electric Sump Pump Submersible with Dry Motor**	**Each**	10-inch Extended Shaft Electric Driven Sump Pump. Submersible Non-Clog Pump with Dry Motor and Internal Chopper Blade. Designed for high solids industrial pumping applications. Our patented pump technology outperforms all centrifugal, vortex and displacement pumps in a variety of the most difficult pumping applications. Operating Levels: 1600-5000 Gallons Per Minute (GPM) at TDH up to 240 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%,Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump objects of up to 10-inches in diameter.	**$84,332.49**
485	**EXSUMP12000**	**12-inch Extended Shaft Electric Sump Pump Submersible with Dry Motor**	**Each**	12-inch Extended Shaft Electric Driven Sump Pump. Submersible Non-Clog Pump with Dry Motor and Internal Chopper Blade. Designed for high solids industrial pumping applications. Our patented pump technology outperforms all centrifugal, vortex and displacement pumps in a variety of the most difficult pumping applications. Operating Levels: 2600-7300 Gallons Per Minute (GPM) at TDH up to 180 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%,Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump objects of up to 10-inches in diameter.	**$121,813.60**

485	**EHPU20**	**20 Horsepower Electric Hydraulic Power Unit**	**Each**	20 Horsepower Electric Hydraulic Power Unit - The HPU powers the EDDY Excavator Dredge Pump Attachment and other dredging equipment. This can ensure super power to the cutterhead in situations where aggressive cutterhead employed. There is enough power for the hydraulic motor and the cutterhead.	**$16,397.98**
485	**EHPU30**	**30 Horsepower Electric Hydraulic Power Unit**	**Each**	30 Horsepower Electric Hydraulic Power Unit - The HPU powers the EDDY Excavator Dredge Pump Attachment and other dredging equipment. This can ensure super power to the cutterhead in situations where aggressive cutterhead employed. There is enough power for the hydraulic motor and the cutterhead.	**$18,740.55**
485	**EHPU40**	**40 Horsepower Electric Hydraulic Power Unit**	**Each**	40 Horsepower Electric Hydraulic Power Unit - The HPU powers the EDDY Excavator Dredge Pump Attachment and other dredging equipment. This can ensure super power to the cutterhead in situations where aggressive cutterhead employed. There is enough power for the hydraulic motor and the cutterhead.	**$28,110.83**
485	**EHPU50**	**50 Horsepower Electric Hydraulic Power Unit**	**Each**	50 Horsepower Electric Hydraulic Power Unit - The HPU powers the EDDY Excavator Dredge Pump Attachment and other dredging equipment. This can ensure super power to the cutterhead in situations where aggressive cutterhead employed. There is enough power for the hydraulic motor and the cutterhead.	**$37,481.11**
485	**EHPU75**	**75 Horsepower Electric Hydraulic Power Unit**	**Each**	75 Horsepower Electric Hydraulic Power Unit - The HPU powers the EDDY Excavator Dredge Pump Attachment and other dredging equipment. This can ensure super power to the cutterhead in situations where aggressive cutterhead employed. There is enough power for the hydraulic motor and the cutterhead.	**$46,851.39**

485	**DHPU20**	**20 Horsepower Diesel Driven Hydraulic Power Unit**	**Each**	20 Horsepower Diesel Driven Hydraulic Power Unit - The HPU powers the EDDY Excavator Dredge Pump Attachment and other dredging equipment. This can ensure super power to the cutterhead in situations where aggressive cutterhead use is being employed. There is enough power for the hydraulic motor and the cutterhead.	**$28,110.83**
485	**DHPU30**	**30 Horsepower Diesel Driven Hydraulic Power Unit**	**Each**	30 Horsepower Diesel Driven Hydraulic Power Unit - The HPU powers the EDDY Excavator Dredge Pump Attachment and other dredging equipment. This can ensure super power to the cutterhead in situations where aggressive cutterhead use is being employed. There is enough power for the hydraulic motor and the cutterhead.	**$37,481.11**
485	**DHPU40**	**40 Horsepower Diesel Driven Hydraulic Power Unit**	**Each**	40 Horsepower Diesel Driven Hydraulic Power Unit - The HPU powers the EDDY Excavator Dredge Pump Attachment and other dredging equipment. This can ensure super power to the cutterhead in situations where aggressive cutterhead use is being employed. There is enough power for the hydraulic motor and the cutterhead.	**$46,851.39**
485	**DHPU50**	**50 Horsepower Diesel Driven Hydraulic Power Unit**	**Each**	50 Horsepower Diesel Driven Hydraulic Power Unit - The HPU powers the EDDY Excavator Dredge Pump Attachment and other dredging equipment. This can ensure super power to the cutterhead in situations where aggressive cutterhead use is being employed. There is enough power for the hydraulic motor and the cutterhead.	**$56,221.66**
485	**DHPU75**	**75 Horsepower Diesel Driven Hydraulic Power Unit**	**Each**	75 Horsepower Diesel Driven Hydraulic Power Unit - The HPU powers the EDDY Excavator Dredge Pump Attachment and other dredging equipment. This can ensure super power to the cutterhead in situations where aggressive cutterhead use is being employed. There is enough power for the hydraulic motor and the cutterhead.	**$70,277.08**

485	**SPT4000**	**Diesel Trailer Mounted 4-inch Pump**	**Each**	4-inch Self-Priming Trailer Mounted Diesel Pump - With a self-priming unit, the pump and power unit are not submerged. The suction hose goes into the slurry and the unit acts like a super-sized wet dry vacuum. Designed for high solids industrial pumping applications. Operating Levels: 250-2100 Gallons Per Minute (GPM) at TDH up to 160 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Ability to pump objects of up to 4-inches in diameter. 1800 RPM max motor speed.	**$187,405.54**
485	**SPT6000**	**Diesel Trailer Mounted 6-inch Pump**	**Each**	6-inch Self-Priming Trailer Mounted Diesel Pump - With a self-priming unit, the pump and power unit are not submerged. The suction hose goes into the slurry and the unit acts like a super-sized wet dry vacuum. Designed for high solids industrial pumping applications. Operating Levels: 450-2500 Gallons Per Minute (GPM) at TDH up to 200 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Ability to pump objects of up to 6-inches in diameter. 1800 RPM max motor speed.	**$257,682.62**

485	**SPT8000**	**Diesel Trailer Mounted 8-inch Pump**	**Each**	8-inch Self-Priming Trailer Mounted Diesel Pump - With a self-priming unit, the pump and power unit are not submerged. The suction hose goes into the slurry and the unit acts like a super-sized wet dry vacuum. Designed for high solids industrial pumping applications. Operating Levels: 1400-3600 Gallons Per Minute (GPM) at TDH up to 230 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Ability to pump objects of up to 8-inches in diameter. 1200 RPM max motor speed.	**$304,534.01**
485	**SPT10000**	**Diesel Trailer Mounted 10-inch Pump**	**Each**	10-inch Self-Priming Trailer Mounted Diesel Pump - With a self-priming unit, the pump and power unit are not submerged. The suction hose goes into the slurry and the unit acts like a super-sized wet dry vacuum. Designed for high solids industrial pumping applications. Operating Levels: 1600-5000 Gallons Per Minute (GPM) at TDH up to 240 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solid. Ability to pump objects of up to 10-inches in diameter. 1200 RPM max motor speed.	**$327,959.70**

485	**SPT12000**	**Diesel Trailer Mounted 12-inch Pump**	**Each**	12-inch Self-Priming Trailer Mounted Diesel Pump - With a self-priming unit, the pump and power unit are not submerged. The suction hose goes into the slurry and the unit acts like a super-sized wet dry vacuum. Designed for high solids industrial pumping applications. Operating Levels: 2600-7300 Gallons Per Minute (GPM) at TDH up to 180 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Ability to pump objects of up to 12-inches in diameter. 900 RPM max motor speed.	**$398,236.78**
485	**SPTE4000**	**Electric Trailer Mounted 4-inch Pump**	**Each**	4-inch Self-Priming Trailer Mounted Electric Pump - With a self-priming unit, the pump and power unit are not submerged. The suction hose goes into the slurry and the unit acts like a super-sized wet dry vacuum. Designed for high solids industrial pumping applications. Operating Levels: 250-2100 Gallons Per Minute (GPM) at TDH up to 160 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Ability to pump objects of up to 4-inches in diameter. 1800 RPM max motor speed.	**$140,554.16**

485	**SPTE6000**	**Electric Trailer Mounted 6-inch Pump**	**Each**	6-inch Self-Priming Trailer Mounted Electric Pump - With a self-priming unit, the pump and power unit are not submerged. The suction hose goes into the slurry and the unit acts like a super-sized wet dry vacuum. Designed for high solids industrial pumping applications. Operating Levels: 450-2500 Gallons Per Minute (GPM) at TDH up to 200 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Ability to pump objects of up to 6-inches in diameter. 1800 RPM max motor speed.	**$210,831.23**
485	**SPTE8000**	**Electric Trailer Mounted 8-inch Pump**	**Each**	8-inch Self-Priming Trailer Mounted Electric Pump - With a self-priming unit, the pump and power unit are not submerged. The suction hose goes into the slurry and the unit acts like a super-sized wet dry vacuum. Designed for high solids industrial pumping applications. Operating Levels: 1400-3600 Gallons Per Minute (GPM) at TDH up to 230 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Ability to pump objects of up to 8-inches in diameter. 1200 RPM max motor speed.	**$267,052.90**

485	**SPTE10000**	**Electric Trailer Mounted 10-inch Pump**	**Each**	10-inch Self-Priming Trailer Mounted Electric Pump - With a self-priming unit, the pump and power unit are not submerged. The suction hose goes into the slurry and the unit acts like a super-sized wet dry vacuum. Designed for high solids industrial pumping applications. Operating Levels: 1600-5000 Gallons Per Minute (GPM) at TDH up to 240 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Ability to pump objects of up to 10-inches in diameter. 1200 RPM max motor speed.	**$281,108.31**
485	**SPTE12000**	**Electric Trailer Mounted 12-inch Pump**	**Each**	12-inch Self-Priming Trailer Mounted Electric Pump - With a self-priming unit, the pump and power unit are not submerged. The suction hose goes into the slurry and the unit acts like a super-sized wet dry vacuum. Designed for high solids industrial pumping applications. Operating Levels: 2600-7300 Gallons Per Minute (GPM) at TDH up to 180 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Ability to pump objects of up to 12-inches in diameter. 900 RPM max motor speed.	**$327,959.70**

485	**SP4000**	**Skid Mounted 4-inch Pump**	**Each**	4-inch Self-Priming Skid Mounted Diesel Pump - With a self-priming unit, the pump and power unit are not submerged. The suction hose goes into the slurry and the unit acts like a super-sized wet dry vacuum. Designed for high solids industrial pumping applications. Operating Levels: 250-2100 Gallons Per Minute (GPM) at TDH up to 160 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solid. Ability to pump objects of up to 4-inches in diameter. 1800 RPM max motor speed.	**$70,277.08**
485	**SP6000**	**Skid Mounted 6-inch Pump**	**Each**	6-inch Self-Priming Skid Mounted Diesel Pump - With a self-priming unit, the pump and power unit are not submerged. The suction hose goes into the slurry and the unit acts like a super-sized wet dry vacuum. Designed for high solids industrial pumping applications. Operating Levels: 450-2500 Gallons Per Minute (GPM) at TDH up to 200 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solid. Ability to pump objects of up to 6-inches in diameter. 1800 RPM max motor speed.	**$98,387.91**

485	**SP8000**	**Skid Mounted 8-inch Pump**	**Each**	8-inch Self-Priming Skid Mounted Diesel Pump - With a self-priming unit, the pump and power unit are not submerged. The suction hose goes into the slurry and the unit acts like a super-sized wet dry vacuum. Designed for high solids industrial pumping applications. Operating Levels: 1400-3600 Gallons Per Minute (GPM) at TDH up to 230 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solid. Ability to pump objects of up to 8-inches in diameter. 1200 RPM max motor speed.	**$166,790.93**
485	**SP10000**	**Skid Mounted 10-inch Pump**	**Each**	10-inch Self-Priming Skid Mounted Diesel Pump - With a self-priming unit, the pump and power unit are not submerged. The suction hose goes into the slurry and the unit acts like a super-sized wet dry vacuum. Designed for high solids industrial pumping applications. Operating Levels: 1600-5000 Gallons Per Minute (GPM) at TDH up to 240 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solid. Ability to pump objects of up to 10-inches in diameter. 1200 RPM max motor speed.	**$210,831.23**

485	**SP12000**	**Skid Mounted 12-inch Pump**	**Each**	12-inch Self-Priming Skid Mounted Diesel Pump - With a self-priming unit, the pump and power unit are not submerged. The suction hose goes into the slurry and the unit acts like a super-sized wet dry vacuum. Designed for high solids industrial pumping applications. Operating Levels: 2600-7300 Gallons Per Minute (GPM) at TDH up to 180 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solid. Ability to pump objects of up to 12-inches in diameter. 900 RPM max motor speed.	**$271,738.04**
485	**SPE4000**	**Skid Mounted Electric 4-inch Pump**	**Each**	4-inch Self-Priming Skid Mounted Electric Pump - With a self-priming unit, the pump and power unit are not submerged. The suction hose goes into the slurry and the unit acts like a super-sized wet dry vacuum. Designed for high solids industrial pumping applications. Operating Levels: 250-2100 Gallons Per Minute (GPM) at TDH up to 160 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solid. Ability to pump objects of up to 4-inches in diameter. 1800 RPM max motor speed.	**$70,277.08**

485	**SPE6000**	**Skid Mounted Electric 6-inch Pump**	**Each**	6-inch Self-Priming Skid Mounted Electric Pump - With a self-priming unit, the pump and power unit are not submerged. The suction hose goes into the slurry and the unit acts like a super-sized wet dry vacuum. Designed for high solids industrial pumping applications. Operating Levels: 450-2500 Gallons Per Minute (GPM) at TDH up to 200 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Ability to pump objects of up to 6-inches in diameter. 1800 RPM max motor speed.	**$93,702.77**
485	**SPE8000**	**Skid Mounted Electric 8-inch Pump**	**Each**	8-inch Self-Priming Skid Mounted Electric Pump - With a self-priming unit, the pump and power unit are not submerged. The suction hose goes into the slurry and the unit acts like a super-sized wet dry vacuum. Designed for high solids industrial pumping applications. Operating Levels: 1400-3600 Gallons Per Minute (GPM) at TDH up to 230 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Ability to pump objects of up to 8-inches in diameter. 1200 RPM max motor speed.	**$143,365.24**

485	**SPE10000**	**Skid Mounted Electric 10-inch Pump**	**Each**	10-inch Self-Priming Skid Mounted Electric Pump - With a self-priming unit, the pump and power unit are not submerged. The suction hose goes into the slurry and the unit acts like a super-sized wet dry vacuum. Designed for high solids industrial pumping applications. Operating Levels: 1600-5000 Gallons Per Minute (GPM) at TDH up to 240 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Ability to pump objects of up to 10-inches in diameter. 1200 RPM max motor speed.	**$161,168.77**
485	**SPE12000**	**Skid Mounted Electric 12-inch Pump**	**Each**	12-inch Self-Priming Skid Mounted Electric Pump - With a self-priming unit, the pump and power unit are not submerged. The suction hose goes into the slurry and the unit acts like a super-sized wet dry vacuum. Designed for high solids industrial pumping applications. Operating Levels: 2600-7300 Gallons Per Minute (GPM) at TDH up to 180 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Ability to pump objects of up to 12-inches in diameter. 900 RPM max motor speed.	**$254,871.54**

485	**EXH4000**	**4-inch Hydraulic Excavator Pump Attachment**	**Each**	4-inch Hydraulic Excavator Pump Attachment - Ideal for pumping slurry from barges, rail cars, pits, lined ponds or other bodies used for material storage. By attaching the EDDY Pump to a standard boom or long boom excavator you can get reach of up to 75-ft and handle the most difficult applications. Designed for high solids dredging applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in the most difficult pumping applications. Operating Levels: 250-1200 Gallons Per Minute (GPM) at TDH up to 200ft. Ability to pump solids up to 3-inches in diameter. Can be powered by an HPU or excavator auxiliary power.	**$84,332.49**
485	**EXH6000**	**6-inch Hydraulic Excavator Pump Attachment**	**Each**	6-inch Hydraulic Excavator Pump Attachment - Ideal for pumping slurry from barges, rail cars, pits, lined ponds or other bodies used for material storage. By attaching the EDDY Pump to a standard boom or long boom excavator you can get reach of up to of up to 75-ft and handle the most difficult applications. Designed for high solids dredging applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in the most difficult pumping applications. Operating Levels: 450-2000 Gallons Per Minute (GPM) at TDH up to 200ft. Ability to pump solids up to 5-inches in diameter. Can be powered by an HPU (recommended) or excavator auxiliary power.	**$103,073.05**
485	**EXH8000**	**8-inch Hydraulic Excavator Pump Attachment**	**Each**	8-inch Hydraulic Excavator Pump Attachment - Ideal for pumping slurry from barges, rail cars, pits, lined ponds or other bodies used for material storage. By attaching the EDDY Pump to a standard boom or of up to 75-ft and handle the most difficult applications. Designed for high solids dredging applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in the most difficult pumping applications. Operating Levels: 800-4000 Gallons Per Minute (GPM) at TDH up to 200ft. Ability to pump solids up to 7-inches in diameter. This unit is powered by a separate HPU.	**$149,924.43**

485	**EXH10000**	**10-inch Hydraulic Excavator Pump Attachment**	**Each**	10-inch Hydraulic Excavator Pump Attachment - Ideal for pumping slurry from barges, rail cars, pits, lined ponds or other bodies used for material storage. By attaching the EDDY Pump to a standard boom or of up to 75-ft and handle the most difficult applications. Designed for high solids dredging applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in the most difficult pumping applications. Operating Levels: 1200-5000 Gallons Per Minute (GPM) at TDH up to 200ft. Ability to pump solids up to 9-inches in diameter. This unit is powered by a separate HPU.	**$154,609.57**
485	**EXH12000**	**12-inch Hydraulic Excavator Pump Attachment**	**Each**	12-inch Hydraulic Excavator Pump Attachment - Ideal for pumping slurry from barges, rail cars, pits, lined ponds or other bodies used for material storage. By attaching the EDDY Pump to a standard boom or of up to 75-ft and handle the most difficult applications. Designed for high solids dredging applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in the most difficult pumping applications. Operating Levels: 1800-7000 Gallons Per Minute (GPM) at TDH up to 200ft. Ability to pump solids up to 11-inches in diameter. This unit is powered by a separate HPU.	**$210,831.23**
485	**EXE4000**	**4-inch Electric Excavator Pump Attachment**	**Each**	4-inch Electric Excavator Pump Attachment - Ideal for pumping slurry from barges, rail cars, pits, lined ponds or other bodies used for material storage. By attaching the EDDY Pump to a standard boom or long boom excavator you can get reach of up to 75-ft and handle the most difficult applications. Designed for high solids dredging applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in the most difficult pumping applications. Production: 250-1200 GPM or 75-150 cubic yards of material per hour. Ability to pump solids up to 3-inches in diameter.	**$93,702.77**

485	**EXE6000**	**6-inch Electric Excavator Pump Attachment**	**Each**	6-inch Electric Excavator Pump Attachment - Ideal for pumping slurry from barges, rail cars, pits, lined ponds or other bodies used for material storage. By attaching the EDDY Pump to a standard boom or long boom excavator you can get reach of up to of up to 75-ft and handle the most difficult applications. Designed for high solids dredging applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in the most difficult pumping applications. Production: 450-2000 GPM or 150-200 cubic yards of material per hour. Ability to pump solids up to 5-inches in diameter.	**$117,128.46**
485	**EXE8000**	**8-inch Electric Excavator Pump Attachment**	**Each**	8-inch Electric Excavator Pump Attachment - Ideal for pumping slurry from barges, rail cars, pits, lined ponds or other bodies used for material storage. By attaching the EDDY Pump to a standard boom or long boom excavator you can get reach of up to of up to 75-ft and handle the most difficult applications. Designed for high solids dredging applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in the most difficult pumping applications. Production: 800-4000 GPM or 250-300 cubic yards of material per hour. Ability to pump solids up to 7-inches in diameter.	**$163,979.85**
485	**EXE10000**	**10-inch Electric Excavator Pump Attachment**	**Each**	10-inch Electric Excavator Pump Attachment - Ideal for pumping slurry from barges, rail cars, pits, lined ponds or other bodies used for material storage. By attaching the EDDY Pump to a standard boom or long boom excavator you can get reach of up to of up to 75-ft and handle the most difficult applications. Designed for high solids dredging applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in the most difficult pumping applications. Production: 1200-5000 GPM or 350-400 cubic yards of material per hour. Ability to pump solids up to 9-inches in diameter.	**$173,350.13**

485	**EXE12000**	**12-inch Electric Excavator Pump Attachment**	**Each**	12-inch Electric Excavator Pump Attachment - Ideal for pumping slurry from barges, rail cars, pits, lined ponds or other bodies used for material storage. By attaching the EDDY Pump to a standard boom or long boom excavator you can get reach of up to of up to 75-ft and handle the most difficult applications. Designed for high solids dredging applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in the most difficult pumping applications. Production: 1800-7000 GPM. Ability to pump solids up to 11-inches in diameter.	**$229,571.79**
485	**JPH4000**	**4-inch Hydraulic Cable Deployed / Diver Operated Dredge**	**Each**	4-inch Hydraulic Cable-Deployed Crane Jetting Pump - Is ideal for projects where a crane is available. The EDDY Pump is run by hydraulics and suspended from the crane on a cable. The water-jetting system breaks up the material and feeds the EDDY Pump. Operating Levels: 250-1200 Gallons Per Minute (GPM) at TDH up to 200 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump solid objects of up to 4-inches in diameter.	**$84,332.49**

485	**JPH6000**	**6-inch Hydraulic Cable Deployed / Diver Operated Dredge**	**Each**	6-inch Hydraulic Cable-Deployed Crane Jetting Pump - Ideal for projects where a crane is available. The EDDY Pump is run by hydraulics and suspended from the crane on a cable. The water-jetting system breaks up the material and feeds the EDDY Pump. Operating Levels: 450-2000 Gallons Per Minute (GPM) at TDH up to 200 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump solid objects of up to 6-inches in diameter.	**$112,443.32**
485	**JPH8000**	**8-inch Hydraulic Crane Jetting Pump**	**Each**	8-inch Hydraulic Cable-Deployed Crane Jetting Pump - Ideal for projects where a crane is available. The EDDY Pump is run by hydraulics and suspended from the crane on a cable. The water-jetting system breaks up the material and feeds the EDDY Pump. Operating Levels: 800-4000 Gallons Per Minute (GPM) at TDH up to 200 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump solid objects of up to 8-inches in diameter.	**$149,924.43**

485	**JPH10000**	**10-inch Hydraulic Crane Jetting Pump**	**Each**	10-inch Hydraulic Cable-Deployed Crane Jetting Pump - Ideal for projects where a crane is available. The EDDY Pump is run by hydraulics and suspended from the crane on a cable. The water-jetting system breaks up the material and feeds the EDDY Pump. Operating Levels: 1200-5000 Gallons Per Minute (GPM) at TDH up to 200 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump solid objects of up to 10-inches in diameter.	**$154,609.57**
485	**JPH12000**	**12-inch Hydraulic Crane Jetting Pump**	**Each**	12-inch Hydraulic Cable-Deployed Crane Jetting Pump - Ideal for projects where a crane is available. The EDDY Pump is run by hydraulics and suspended from the crane on a cable. The water-jetting system breaks up the material and feeds the EDDY Pump. Operating Levels: 1800-7000 Gallons Per Minute (GPM) at TDH up to 200 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump solid objects of up to 12-inches in diameter.	**$210,831.23**

485	**JPE4000**	**4-inch Electric Cable Deployed / Diver Operated Dredge Pump**	**Each**	4-inch Electric Cable-Deployed Crane Jetting Pump - Ideal for projects where a crane is available. The EDDY Pump is run electrically and suspended from the crane on a cable. The water-jetting system breaks up the material and feeds the EDDY Pump. Operating Levels: 250-1200 Gallons Per Minute (GPM) at TDH up to 200 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump solid objects of up to 4-inches in diameter.	**$93,702.77**
485	**JPE6000**	**6-inch Electric Cable Deployed / Diver Operated Dredge Pump**	**Each**	6-inch Electric Cable-Deployed Crane Jetting Pump - Ideal for projects where a crane is available. The EDDY Pump is run electrically and suspended from the crane on a cable. The water-jetting system breaks up the material and feeds the EDDY Pump. Operating Levels: 450-2000 Gallons Per Minute (GPM) at TDH up to 200 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump solid objects of up to 6-inches in diameter.	**$117,128.46**

485	**JPE8000**	**8-inch Electric Crane Jetting Pump**	**Each**	8-inch Electric Cable-Deployed Crane Jetting Pump - Ideal for projects where a crane is available. The EDDY Pump is run electrically and suspended from the crane on a cable. The water-jetting system breaks up the material and feeds the EDDY Pump. Operating Levels: 800-4000 Gallons Per Minute (GPM) at TDH up to 200 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump solid objects of up to 8-inches in diameter.	**$163,979.85**
485	**JPE10000**	**10-inch Electric Crane Jetting Pump**	**Each**	10-inch Electric Cable-Deployed Crane Jetting Pump - Ideal for projects where a crane is available. The EDDY Pump is run electrically and suspended from the crane on a cable. The water-jetting system breaks up the material and feeds the EDDY Pump. Operating Levels: 1200-5000 Gallons Per Minute (GPM) at TDH up to 200 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump solid objects of up to 10-inches in diameter.	**$173,350.13**

485	**JPE12000**	**12-inch Electric Crane Jetting Pump**	**Each**	12-inch Electric Cable-Deployed Crane Jetting Pump - Ideal for projects where a crane is available. The EDDY Pump is run electrically and suspended from the crane on a cable. The water-jetting system breaks up the material and feeds the EDDY Pump. Operating Levels: 1800-7000 Gallons Per Minute (GPM) at TDH up to 200 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump solid objects of up to 12-inches in diameter.	**$229,571.79**
485	**SUBH4000**	**4-inch Hydraulic Submersible Pump**	**Each**	4-inch Hydraulic Submersible Pump - Slurry Pumps that are completely submerged in the liquid are called submersible pumps. By being submerged in the fluid to be pumped, there is no need for priming. Designed for high solids industrial pumping applications. Operating Levels: 250-2100 Gallons Per Minute (GPM) at TDH up to 160 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump solid objects of up to 4-inches in diameter.	**$56,221.66**

485	**SUBH6000**	**6-inch Hydraulic Submersible Pump**	**Each**	6-inch Hydraulic Submersible Pump - Slurry Pumps that are completely submerged in the liquid are called submersible pumps. By being submerged in the fluid to be pumped, there is no need for priming. Designed for high solids industrial pumping applications. Operating Levels: 450-2500 Gallons Per Minute (GPM) at TDH up to 200 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump solid objects of up to 6-inches in diameter.	**$84,332.49**
485	**SUBH8000**	**8-inch Hydraulic Submersible Pump**	**Each**	8-inch Hydraulic Submersible Pump - Slurry Pumps that are completely submerged in the liquid are called submersible pumps. By being submerged in the fluid to be pumped, there is no need for priming. Designed for high solids industrial pumping applications. Operating Levels: 1400-3600 Gallons Per Minute (GPM) at TDH up to 230 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump solid objects of up to 8-inches in diameter.	**$121,813.60**

485	**SUBH10000**	**10-inch Hydraulic Submersible Pump**	**Each**	10-inch Hydraulic Submersible Pump - Slurry Pumps that are completely submerged in the liquid are called submersible pumps. By being submerged in the fluid to be pumped, there is no need for priming. Designed for high solids industrial pumping applications. Operating Levels: 1600-5000 Gallons Per Minute (GPM) at TDH up to 240 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump solid objects of up to 10-inches in diameter.	**$126,498.74**
485	**SUBH12000**	**12-inch Hydraulic Submersible Pump**	**Each**	12-inch Hydraulic Submersible Pump - Slurry Pumps that are completely submerged in the liquid are called submersible pumps. By being submerged in the fluid to be pumped, there is no need for priming. Designed for high solids industrial pumping applications. Operating Levels: 2600-7300 Gallons Per Minute (GPM) at TDH up to 180 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump solid objects of up to 12-inches in diameter.	**$182,720.40**

485	**SUBE4000**	**4-inch Electric Submersible Pump**	**Each**	4-inch Electric Submersible Pump - Slurry Pumps that are completely submerged in the liquid are called submersible pumps. By being submerged in the fluid to be pumped, there is no need for priming. Designed for high solids industrial pumping applications. Operating Levels: 250-2100 Gallons Per Minute (GPM) at TDH up to 160 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump solid objects of up to 4-inches in diameter.	**$65,591.94**
485	**SUBE6000**	**6-inch Electric Submersible Pump**	**Each**	6-inch Electric Submersible Pump - Pumps that are completely submerged in the liquid are called submersible pumps. By being submerged in the fluid to be pumped, there is no need for priming. Designed for high solids industrial pumping applications. Operating Levels: 450-2000 Gallons Per Minute (GPM) at TDH up to 200 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solid. Ability to pump solid objects of up to 6-inches in diameter.	**$89,017.63**

485	**SUBE8000**	**8-inch Electric Submersible Pump**	**Each**	8-inch Electric Submersible Pump - Pumps that are completely submerged in the liquid are called submersible pumps. By being submerged in the fluid to be pumped, there is no need for priming. Designed for high solids industrial pumping applications. Operating Levels: 1400-3600 Gallons Per Minute (GPM) at TDH up to 230 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump solid objects of up to 8-inches in diameter.	**$135,869.02**
485	**SUBE10000**	**10-inch Electric Submersible Pump**	**Each**	10-inch Electric Submersible Pump - Pumps that are completely submerged in the liquid are called submersible pumps. By being submerged in the fluid to be pumped, there is no need for priming. Designed for high solids industrial pumping applications. Operating Levels: 1600-5000 Gallons Per Minute (GPM) at TDH up to 240 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump solid objects of up to 10-inches in diameter.	**$145,239.29**

485	**SUBE12000**	**12-inch Electric Submersible Pump**	**Each**	12-inch Electric Submersible Pump - Pumps that are completely submerged in the liquid are called submersible pumps. By being submerged in the fluid to be pumped, there is no need for priming. Designed for high solids industrial pumping applications. Operating Levels: 2600-7300 Gallons Per Minute (GPM) at TDH up to 180 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump solid objects of up to 12-inches in diameter.	**$201,460.96**
485	**SK4000**	**4-inch Diesel Skid Mounted Pump**	**Each**	4-inch Diesel Skid Mounted Pump - Non-clog pumps designed for high solids pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult pumping applications. Designed for high solids industrial pumping applications. Operating Levels: 250-2100 Gallons Per Minute (GPM) at TDH up to 160 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump solid objects of up to 4-inches in diameter.	**$65,591.94**

485	**SK6000**	**6-inch Diesel Skid Mounted Pump**	**Each**	6-inch Diesel Skid Mounted Pump - Non-clog pumps designed for high solids pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult pumping applications. Designed for high solids industrial pumping applications. Operating Levels: 450-2500 Gallons Per Minute (GPM) at TDH up to 200 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump solid objects of up to 6-inches in diameter.	**$95,576.83**
485	**SK8000**	**8-inch Diesel Skid Mounted Pump**	**Each**	8-inch Diesel Skid Mounted Pump - Non-clog pumps designed for high solids pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult pumping applications. Designed for high solids industrial pumping applications. Operating Levels: 1400-3600 Gallons Per Minute (GPM) at TDH up to 230 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump solid objects of up to 8-inches in diameter.	**$163,979.85**

485	**SK10000**	**10-inch Diesel Skid Mounted Pump**	**Each**	10-inch Diesel Skid Mounted Pump - Non-clog pumps designed for high solids pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult pumping applications. Designed for high solids industrial pumping applications. Operating Levels: 1600-5000 Gallons Per Minute (GPM) at TDH up to 240 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump solid objects of up to 10-inches in diameter.	**$210,831.23**
485	**SK12000**	**12-inch Diesel Skid Mounted Pump**	**Each**	12-inch Diesel Skid Mounted Pump - Non-clog pumps designed for high solids pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult pumping applications. Designed for high solids industrial pumping applications. Operating Levels: 2600-7300 Gallons Per Minute (GPM) at TDH up to 180 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump solid objects of up to 12-inches in diameter.	**$271,738.04**

485	**SKE4000**	**4-inch Electric Skid Mounted Pump**	**Each**	4-inch Electric Skid Mounted Pump - Non-clog pumps designed for high solids pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult pumping applications. Designed for high solids industrial pumping applications. Operating Levels: 250-2100 Gallons Per Minute (GPM) at TDH up to 160 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump solid objects of up to 4-inches in diameter.	**$65,591.94**
485	**SKE6000**	**6-inch Electric Skid Mounted Pump**	**Each**	6-inch Electric Skid Mounted Pump - Non-clog pumps designed for high solids pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult pumping applications. Designed for high solids industrial pumping applications. Operating Levels: 450-2000 Gallons Per Minute (GPM) at TDH up to 200 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump solid objects of up to 6-inches in diameter.	**$89,017.63**

485	**SKE8000**	**8-inch Electric Skid Mounted Pump**	**Each**	8-inch Electric Skid Mounted Pump - Non-clog pumps designed for high solids pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult pumping applications. Designed for high solids industrial pumping applications. Operating Levels: 1400-3600 Gallons Per Minute (GPM) at TDH up to 200 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump solid objects of up to 8-inches in diameter.	**$140,554.16**
485	**SKE10000**	**10-inch Electric Skid Mounted Pump**	**Each**	10-inch Electric Skid Mounted Pump - Non-clog pumps designed for high solids pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult pumping applications. Designed for high solids industrial pumping applications. Operating Levels: 1600-5000 Gallons Per Minute (GPM) at TDH up to 200 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump solid objects of up to 10-inches in diameter.	**$159,294.71**

485	**SKE12000**	**12-inch Electric Skid Mounted Pump**	**Each**	12-inch Electric Skid Mounted Pump - Non-clog pumps designed for high solids pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult pumping applications. Designed for high solids industrial pumping applications. Operating Levels: 2600-7300 Gallons Per Minute (GPM) at TDH up to 180 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solids. Ability to pump solid objects of up to 12-inches in diameter.	**$252,997.48**
485	**TE4000**	**4-inch Electric Skid Mounted Pump**	**Each**	4-inch Electric Trailer Mounted Pump - Non-clog pumps designed for high solids pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult pumping applications. Designed for high solids industrial pumping applications. Operating Levels: 250-2100 Gallons Per Minute (GPM) at TDH up to 160 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash.Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solid. Ability to pump objects of up to 9-inches in diameter.	**$60,906.80**

485	**TE6000**	**6-inch Electric Skid Mounted Pump**	**Each**	6-inch Electric Trailer Mounted Pump - Non-clog pumps designed for high solids pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult pumping applications. Designed for high solids industrial pumping applications. Operating Levels: 450-2500 Gallons Per Minute (GPM) at TDH up to 200 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design.Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solid. Ability to pump objects of up to 9-inches in diameter.	**$84,332.49**
485	**TE8000**	**8-inch Electric Skid Mounted Pump**	**Each**	8-inch Electric Trailer Mounted Pump - Non-clog pumps designed for high solids pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult pumping applications. Designed for high solids industrial pumping applications. Operating Levels: 1400-3600 Gallons Per Minute (GPM) at TDH up to 230 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solid. Ability to pump objects of up to 9-inches in diameter.	**$133,994.96**

485	**TE10000**	**10-inch Electric Skid Mounted Pump**	**Each**	10-inch Electric Trailer Mounted Pump - Non-clog pumps designed for high solids pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult pumping applications. Designed for high solids industrial pumping applications. Operating Levels: 1600-5000 Gallons Per Minute (GPM) at TDH up to 240 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solid. Ability to pump objects of up to 9-inches in diameter.	**$152,735.52**
485	**TE12000**	**12-inch Electric Skid Mounted Pump**	**Each**	12-inch Electric Trailer Mounted Pump - Non-clog pumps designed for high solids pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult pumping applications. Designed for high solids industrial pumping applications. Operating Levels: 2600-7300 Gallons Per Minute (GPM) at TDH up to 180 feet. Percentage of solids up to 40-70%. Standard Materials for Wet Ends: High Chrome 28%, Ductile Iron, Stainless Steel, Duplex Stainless. Applications: Mining, Chemical, Sand and Agg, Oil and Gas, Paper and Pulp, Fly Ash and Coal Ash. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Features and Benefits: Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design. Transport 40-70% Solid. Ability to pump objects of up to 9-inches in diameter.	**$246,438.29**

485	**HPU4000**	**Diesel Hydraulic Power Unit for 4-Inch Pump Products**	**Each**	Diesel Hydraulic Power Unit for all 4-inch pump products - The HPU powers the excavator pump attachment. This can ensure super power to the cutterhead in situations where aggressive cutterhead use is being employed. There is enough power for the hydraulic motor and the cutterhead.	**$163,979.85**
485	**HPU6000**	**Diesel Hydraulic Power Unit for 6-Inch Pump Products**	**Each**	Diesel Hydraulic Power Unit for all 6-inch pump products - The HPU powers the excavator pump attachment and other dredging equipment. This can ensure super power to the cutterhead in situations where aggressive cutterhead use is being employed. There is enough power for the hydraulic motor and the cutterhead.	**$210,831.23**
485	**HPU8000**	**Diesel Hydraulic Power Unit for 8-Inch Pump Products**	**Each**	Diesel Hydraulic Power Unit for all 8-inch pump products - The HPU powers the excavator pump attachment and other dredging equipment. This can ensure super power to the cutterhead in situations where aggressive cutterhead use is being employed. There is enough power for the hydraulic motor and the cutterhead.	**$304,534.01**
485	**HPU10000**	**Diesel Hydraulic Power Unit for 10-Inch Pump Products**	**Each**	Diesel Hydraulic Power Unit for all 10-inch pump products - The HPU powers the excavator pump attachment and other dredging equipment. This can ensure super power to the cutterhead in situations where aggressive cutterhead use is being employed. There is enough power for the hydraulic motor and the cutterhead.	**$304,534.01**
485	**HPU12000**	**Diesel Hydraulic Power Unit for 12-Inch Pump Products**	**Each**	Diesel Hydraulic Power Unit for all 12-inch pump products - The HPU powers the excavator pump attachment and other dredging equipment. This can ensure super power to the cutterhead in situations where aggressive cutterhead use is being employed. There is enough power for the hydraulic motor and the cutterhead.	**$398,236.78**
485	**EHPU4000**	**Electric Hydraulic Power Unit for 4-Inch Pump Products**	**Each**	Electric Hydraulic Power Unit for all 4-inch pump products - The HPU powers the excavator pump attachment and other dredging equipment. This can ensure super power to the cutterhead in situations where aggressive cutterhead use is being employed. There is enough power for the hydraulic motor and the cutterhead.	**$140,554.16**

485	**EHPU6000**	**Electric Hydraulic Power Unit for 6-Inch Pump Products**	**Each**	Electric Hydraulic Power Unit for all 6-inch pump products - The HPU powers the excavator pump attachment and other dredging equipment. This can ensure super power to the cutterhead in situations where aggressive cutterhead use is being employed. There is enough power for the hydraulic motor and the cutterhead.	**$187,405.54**
485	**EHPU8000**	**Electric Hydraulic Power Unit for 8-Inch Pump Products**	**Each**	Electric Hydraulic Power Unit for all 8-inch pump products - The HPU powers the excavator pump attachment and other dredging equipment. This can ensure super power to the cutterhead in situations where aggressive cutterhead use is being employed. There is enough power for the hydraulic motor and the cutterhead.	**$304,534.01**
485	**EHPU10000**	**Electric Hydraulic Power Unit for 10-Inch Pump Products**	**Each**	Electric Hydraulic Power Unit for all 10-inch pump products - The HPU powers the excavator pump attachment and other dredging equipment. This can ensure super power to the cutterhead in situations where aggressive cutterhead use is being employed. There is enough power for the hydraulic motor and the cutterhead.	**$304,534.01**
485	**EHPU12000**	**Electric Hydraulic Power Unit for 12-Inch Pump Products**	**Each**	Electric Hydraulic Power Unit for all 12-inch pump products - The HPU powers the excavator pump attachment and other dredging equipment. This can ensure super power to the cutterhead in situations where aggressive cutterhead use is being employed. There is enough power for the hydraulic motor and the cutterhead.	**$398,236.78**