



**GENERAL SERVICES ADMINISTRATION
FEDERAL SUPPLY SERVICE
AUTHORIZED FEDERAL SUPPLY SCHEDULE PRICE LIST**

MULTIPLE AWARD SCHEDULE (MAS)

**Contract Number:
47QSWA20D0022**

**Period Covered by Contract:
December 10, 2019 - December 9, 2024**

**O'KEEFFE'S, INC.
dba SAFTI FIRST
100 N HILL DR STE 12
BRISBANE, CA 94005-1010
Phone: 888-653-3333
Fax: 415-230-6757**

**Website: <https://safti.com/>
E-Mail: DianaS@safti.com**

**Business Size: Veteran Owned Small Business
DUNS Number: 009113176**

On-line access to contract ordering information, terms and conditions, up-to-date pricing, and the option to create an electronic delivery order are available through GSA Advantage!, a menu-driven database system. The Internet address for GSA Advantage! is GSAAdvantage.gov. For more information on ordering from Federal Supply Schedules click on the FSS Schedules button at fss.gsa.gov.

| |
|-----------------------------|
| ORDERING INFORMATION |
|-----------------------------|

1a. Authorized Special Item Numbers (SINs):

SINs 332321 (Doors, Windows, Skylights, Panels, and Shutters); OLM (Order-Level Materials)

1b. Lowest priced model number and lowest unit price for that model for each SIN awarded in the contract: **See attached pricing**

1c. Hourly rates, a description of all corresponding commercial job titles, experience, functional responsibility and education for those types of employees or subcontractors who will perform services: **Not Applicable**

2. Maximum order: **SINs 332321 and OLM (\$250,000)**

3. Minimum order: **\$100; and if specific minimum quantity is required**

4. Geographic coverage (delivery area): **48 contiguous states, Alaska, Hawaii, Washington, DC, Puerto Rico, US Territories and to a CONUS port or consolidation point for orders received from overseas activities.**

5. Points of production: **United States**

6. Discount from list prices or statement of net price: **Government net prices**

7. Quantity discounts: **See attached pricing.**

8. Prompt payment terms: **2% 10 days; Net 30 days. Information for Ordering Offices: Prompt payment terms cannot be negotiated out of the contractual agreement in exchange for other concessions.**

9a. Government purchase cards **are accepted** below the micropurchase threshold.

9b. Government purchase cards **are accepted** above the micropurchase threshold.

10. Foreign items (list items by country of origin): **Not Applicable**

11a. Time of delivery: **90 - 180 Days ARO**

11b. Items available for expedited delivery: **Contact Contractor**

11c. Overnight and 2-day delivery: **Contact Contractor**

11d. Urgent Requirements: **Contact Contractor**

12. F.O.B. Point: **Origin, freight prepay and add**

13a. Ordering address:

O'KEEFE'S, INC.

100 N HILL DR STE 12

BRISBANE, CA 94005-1010

13b. Ordering Procedures: **For supplies and services, the ordering procedures, and information on Blanket Purchase Agreements (BPA's) are found in Federal Acquisition Regulation (FAR) 8.405-3.**

14. Payment address: **Same as ordering address**
15. Warranty provision: **Three (3) warranties are offered (dependent on applicable products): Five year limited warranty, limited lifetime warranty, and a ten year limited warranty. Refer to the applicable warranty for complete details. Customer should contact the contractor for a copy of the applicable warranty. Return/restock policy: Not offered**
16. Export packing charges: **Not Applicable**
17. Terms and conditions of Government purchase card acceptance (any thresholds above the micropurchase level): **Contact Contractor**
18. Terms and conditions of rental, maintenance, and repair: **Not Applicable**
19. Terms and conditions of installation: **Not Applicable**
20. Terms and conditions of repair parts indicating date of parts price lists and any discounts from list prices: **Not Applicable**
- 20a. Terms and conditions for any other services: **Not Applicable**
21. List of service and distribution points: **Not Applicable**
22. List of participating dealers: **Not Applicable**
23. Preventive maintenance: **Not Applicable**
24. Environmental attributes, e.g., recycled content, energy efficiency, and/or reduced pollutants: **Not Applicable**
25. Data Universal Number System (DUNS) number: **009113176**
26. O'KEEFFE'S, INC. is registered in the System for Award Management database.

AUTHORIZED GSA SCHEDULE CONTRACT PRICING

| SIN | Part Number | Product Description | Unit of Issue | GSA Price (2-24 units) | GSA Price (25-500 units) | GSA Price (500+ units) |
|--------|------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------------------|--------------------------|------------------------|
| 332321 | SL I-20 | <ul style="list-style-type: none"> • Clear, USA-made, 1/4", 20 minute fire protective glass that meets NFPA 252/257, UL 9/10B/10C for fire and CPSC Cat. II/ANSI Z97.1 for impact safety. • IBC requires all glazing in doors, sidelites and hazardous locations to meet CPSC Cat. I or II/ANSI Z97.1 impact safety. • Used in fire protective doors and partitions up to the maximum size tested. For a list of maximum sizes, visit https://safti.com/product/superlite/ • Safe and economical alternative to wire glass and expensive ceramics. • Can be combined with standard hollow metal frames or USA-made GPX Framing by SAFTI FIRST for a complete fire protective assembly. • Custom options such as insulated, decorative, and more available by calling SAFTI FIRST (Ph: 888.653.3333) <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. Minimum order 2 sq. ft. | Square Foot | \$22.13 | \$17.02 | \$14.90 |
| 332321 | SuperClear 45-HS | <ul style="list-style-type: none"> • Clear, USA-made, 3/4", 45 minute fire protective glass that meets NFPA 252/257, UL 9/10B/10C for fire and CPSC Cat. II/ANSI Z97.1 for impact safety. • IBC requires all glazing in doors, sidelites and hazardous locations to meet CPSC Cat. I or II/ANSI Z97.1 impact safety. • Used in fire protective doors, sidelites, transoms, and openings up to the maximum size tested. For a list of maximum sizes, visit https://safti.com/superclear45-hs/ • Safe and economical alternative wire glass and expensive ceramics. • Can be combined with standard hollow metal frames or USA-made GPX Framing by SAFTI FIRST for a complete fire protective assembly. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. Minimum order 2 sq. ft. | Square Foot | \$29.02 | \$29.02 | \$29.02 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price (2-24 units) | GSA Price (25-500 units) | GSA Price (500+ units) |
|--------|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------------------|--------------------------|------------------------|
| 332321 | SuperClear 45-HS-LI | <ul style="list-style-type: none"> • Clear, USA-made, 3/4", 45 minute, low-iron, fire protective glass that meets NFPA 252/257, UL 9/10B/10C for fire and CPSC Cat. II/ANSI Z97.1 for impact safety. • IBC requires all glazing in doors, sidelites and hazardous locations to meet CPSC Cat. I or II/ANSI Z97.1 impact safety. • Used in fire protective doors, sidelites, transoms, and openings up to the maximum size tested. For a list of maximum sizes, visit https://safti.com/superclear45-hs-li/ • Safe and economical alternative wire glass and expensive ceramics. • Can be combined with standard hollow metal frames or USA-made GPX Framing by SAFTI FIRST for a complete fire protective assembly. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. Minimum order 2 sq. ft. | Square Foot | \$32.89 | \$32.89 | \$32.89 |
| 332321 | SL II-XL 45 | <ul style="list-style-type: none"> • Clear, USA-made, 1", 45 minute fire resistive glass that meets ASTM E-119, NFPA 251/252/257, UL 263/9/10B/10C for fire and CPSC Cat. II/ANSI Z97.1 for impact safety. • IBC requires all glazing in doors, sidelites and hazardous locations to meet CPSC Cat. I or II/ANSI Z97.1 impact safety. • Used in fire resistive walls, openings and doors up to the maximum size tested. For a list of maximum sizes, visit https://safti.com/product/superlite-ii-xl-45/ • Can be combined with standard hollow metal frames or USA-made GPX Framing by SAFTI FIRST for a complete fire resistive assembly. • Custom options such as insulated, hurricane, ballistic, blast, security, decorative, and more available by calling SAFTI FIRST (Ph: 888.653.3333) <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. Minimum order 2 sq. ft. | Square Foot | \$58.09 | \$44.69 | \$42.56 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price (2-24 units) | GSA Price (25-500 units) | GSA Price (500+ units) |
|--------|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------------------|--------------------------|------------------------|
| 332321 | SL II-XL 60 | <ul style="list-style-type: none"> • Clear, USA-made, 1-3/8", 60 minute fire resistive glass that meets ASTM E-119, NFPA 251/252/257, UL 263/9/10B/10C for fire and CPSC Cat. II/ANSI Z97.1 for impact safety. • IBC requires all glazing in doors, sidelites and hazardous locations to meet CPSC Cat. I or II/ANSI Z97.1 impact safety. IBC typically requires fire glass and framing assemblies 60 minute and above to meet ASTM E-119/UL 263/NFPA 251 fire resistive/temperature rise requirements. • Used in fire resistive walls, openings and doors up to the maximum size tested. For a list of maximum sizes, visit https://safti.com/product/superlite-ii-xl-60/ • Can be combined with USA-made GPX Framing by SAFTI FIRST for a complete fire resistive assembly. <ul style="list-style-type: none"> • Custom options such as insulated, hurricane, ballistic, blast, security, decorative, etc. available by calling SAFTI FIRST (Ph: 888.653.3333) <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. Minimum order 2 sq. ft. | Square Foot | \$76.07 | \$58.52 | \$55.33 |
| 332321 | SL II-XL 90 | <ul style="list-style-type: none"> • Clear, USA-made, 1-1/2", 90 minute fire resistive glass that meets ASTM E-119, NFPA 251/252/257, UL 263/9/10B/10C for fire and CPSC Cat. II/ANSI Z97.1 for impact safety. • IBC requires all glazing in doors, sidelites and hazardous locations to meet CPSC Cat. I or II/ANSI Z97.1 impact safety. IBC typically requires fire glass and framing assemblies 60 minute and above to meet ASTM E-119/UL 263/NFPA 251 fire resistive/temperature rise requirements. • Used in fire resistive walls, openings and doors up to the maximum size tested. For a list of maximum sizes, visit https://safti.com/product/superlite-ii-xl-90/ • Can be combined with USA-made GPX Framing by SAFTI FIRST for a complete fire resistive assembly. <ul style="list-style-type: none"> • Custom options such as insulated, hurricane, ballistic, blast, security, decorative, etc. available by calling SAFTI FIRST (Ph: 888.653.3333) <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. Minimum order 2 sq. ft. | Square Foot | \$124.49 | \$95.76 | \$90.44 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price (2-24 units) | GSA Price (25-500 units) | GSA Price (500+ units) |
|--------|--------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------------------|--------------------------|------------------------|
| 332321 | SL II-XL 120 | <ul style="list-style-type: none"> • Clear, USA-made, 1-3/4", 120 minute fire resistive glass that meets ASTM E-119, NFPA 251/252/257, UL 263/9/10B/10C for fire and CPSC Cat. II/ANSI Z97.1 for impact safety. • IBC requires all glazing in doors, sidelites and hazardous locations to meet CPSC Cat. I or II/ANSI Z97.1 impact safety. IBC typically requires fire glass and framing assemblies 60 minute and above to meet ASTM E-119/UL 263/NFPA 251 fire resistive/temperature rise requirements. • Used in fire resistive walls, openings and doors up to the maximum size tested. For a list of maximum sizes, visit https://safti.com/product/superlite-ii-xl-120/ • Can be combined with USA-made GPX Framing by SAFTI FIRST for a complete fire resistive assembly. <ul style="list-style-type: none"> • Custom options such as insulated, hurricane, ballistic, blast, security, decorative, etc. available by calling SAFTI FIRST (Ph: 888.653.3333) <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. Minimum order 2 sq. ft. | Square Foot | \$152.15 | \$117.04 | \$106.40 |
| 332321 | SL II-XLB 60 | <ul style="list-style-type: none"> • Clear, USA-made, 1-7/8", 60 minute fire resistive glass for oversized and butt-glazed applications that meets ASTM E-119, NFPA 251/252/257, UL 263/9/10B/10C for fire and CPSC Cat. II/ANSI Z97.1 for impact safety. • IBC requires all glazing in doors, sidelites and hazardous locations to meet CPSC Cat. I or II/ANSI Z97.1 impact safety. IBC typically requires fire glass and framing assemblies 60 minute and above to meet ASTM E-119/UL 263/NFPA 251 fire resistive/temperature rise requirements. • Used in fire resistive wall assemblies. Available in butt-glazed applications. Maximum size: 10,000 sq. in. • Can be combined with USA-made GPX Architectural Series Framing by SAFTI FIRST for a complete fire resistive assembly. <ul style="list-style-type: none"> • Custom options such as architectural, decorative, and energy-saving make-ups available by calling SAFTI FIRST (Ph: 888.653.3333) <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. Minimum order 2 sq. ft. | Square Foot | \$163.85 | \$148.96 | \$148.96 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price (2-24 units) | GSA Price (25-500 units) | GSA Price (500+ units) |
|--------|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------------------|--------------------------|------------------------|
| 332321 | SL II-XLB 90 | <ul style="list-style-type: none"> • Clear, USA-made, 2-1/2", 90 minute fire resistive glass for oversized and butt-glazed applications that meets ASTM E-119, NFPA 251/252/257, UL 263/9/10B/10C for fire and CPSC Cat. II/ANSI Z97.1 for impact safety. • IBC requires all glazing in doors, sidelites and hazardous locations to meet CPSC Cat. I or II/ANSI Z97.1 impact safety. IBC typically requires fire glass and framing assemblies 60 minute and above to meet ASTM E-119/UL 263/NFPA 251 fire resistive/temperature rise requirements. • Used in fire resistive wall assemblies. Available in butt-glazed applications. Maximum size: 7,980 sq. in. • Can be combined with USA-made GPX Architectural Series Framing by SAFTI FIRST for a complete fire resistive assembly. • Custom options such as architectural, decorative, and energy-saving make-ups available by calling SAFTI FIRST (Ph: 888.653.3333) <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. Minimum order 2 sq. ft. | Square Foot | \$163.85 | \$148.96 | \$148.96 |
| 332321 | SL II-XLB 120 | <ul style="list-style-type: none"> • Clear, USA-made, 2-1/2", 120 minute fire resistive glass for oversized and butt-glazed applications that meets ASTM E-119, NFPA 251/252/257, UL 263/9/10B/10C for fire and CPSC Cat. II/ANSI Z97.1 for impact safety. • IBC requires all glazing in doors, sidelites and hazardous locations to meet CPSC Cat. I or II/ANSI Z97.1 impact safety. IBC typically requires fire glass and framing assemblies 60 minute and above to meet ASTM E-119/UL 263/NFPA 251 fire resistive/temperature rise requirements. • Used in fire resistive wall assemblies. Available in butt-glazed applications. Maximum size: 7,980 sq. in. • Can be combined with USA-made GPX Architectural Series Framing by SAFTI FIRST for a complete fire resistive assembly. • Custom options such as architectural, decorative, and energy-saving make-ups available by calling SAFTI FIRST (Ph: 888.653.3333) <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. Minimum order 2 sq. ft. | Square Foot | \$163.85 | \$148.96 | \$148.96 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price (2-24 units) | GSA Price (25-500 units) | GSA Price (500+ units) |
|--------|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------------------|--------------------------|------------------------|
| 332321 | SL I-XL 20 | <ul style="list-style-type: none"> • Clear, USA-made, 1/4", 20 minute directional fire protective glass that meets NFPA 252/257, UL 9/10B/10C for fire and CPSC Cat. II/ANSI Z97.1 for impact safety. • IBC requires all glazing in doors, sidelites and hazardous locations to meet CPSC Cat. I or II/ANSI Z97.1 impact safety. • Tested without hose stream and may require approval for 45 minute applications. • Used in fire protective doors, sidelites, openings, and transoms up to the maximum size tested. For a list of maximum sizes, visit https://safti.com/product/superlite-xl/ • Safe and economical alternative to wire glass and expensive ceramics. • Can be combined with standard hollow metal frames or USA-made GPX Framing by SAFTI FIRST for a complete fire protective assembly. • Custom options such as insulated, decorative, and more available by calling SAFTI FIRST (Ph: 888.653.3333) • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. Minimum order 2 sq. ft. | Square Foot | \$34.58 | \$26.60 | \$21.28 |
| 332321 | SL I-XL 45 | <ul style="list-style-type: none"> • Clear, USA-made, 1/4", 45 minute directional fire protective glass that meets NFPA 252/257, UL 9/10B/10C for fire and CPSC Cat. II/ANSI Z97.1 for impact safety. • IBC requires all glazing in doors, sidelites and hazardous locations to meet CPSC Cat. I or II/ANSI Z97.1 impact safety. • Tested without hose stream and may require approval for 45 minute applications. • Used in fire protective doors, sidelites, openings, and transoms up to the maximum size tested. For a list of maximum sizes, visit https://safti.com/product/superlite-xl/ • Safe and economical alternative to wire glass and expensive ceramics. • Can be combined with standard hollow metal frames or USA-made GPX Framing by SAFTI FIRST for a complete fire protective assembly. • Custom options such as insulated, decorative, and more available by calling SAFTI FIRST (Ph: 888.653.3333) <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. Minimum order 2 sq. ft. | Square Foot | \$34.58 | \$26.60 | \$21.28 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price (2-24 units) | GSA Price (25-500 units) | GSA Price (500+ units) |
|--------|----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------------------|--------------------------|------------------------|
| 332321 | SL I-XL 20 IGU | <ul style="list-style-type: none"> • Clear, USA-made, 1", 20 minute bi-directional fire protective glass that meets NFPA 252/257, UL 9/10B/10C for fire and CPSC Cat. II/ANSI Z97.1 for impact safety. • IBC requires all glazing in doors, sidelites and hazardous locations to meet CPSC Cat. I or II/ANSI Z97.1 impact safety. • Tested without hose stream and may require approval for 45 minute applications. • Used in fire protective doors, sidelites, openings, and transoms up to the maximum size tested. For a list of maximum sizes, visit https://safti.com/product/superlite-xl-igu/ • Safe and economical alternative to wire glass and expensive ceramics. • Can be combined with standard hollow metal frames or USA-made GPX Framing by SAFTI FIRST for a complete fire protective assembly. • Custom options such as insulated, decorative, and more available by calling SAFTI FIRST (Ph: 888.653.3333) <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. Minimum order 2 sq. ft. | Square Foot | \$62.24 | \$47.88 | \$42.56 |
| 332321 | SL I-XL 45 IGU | <ul style="list-style-type: none"> • Clear, USA-made, 1", 45 minute bi-directional fire protective glass that meets NFPA 252/257, UL 9/10B/10C for fire and CPSC Cat. II/ANSI Z97.1 for impact safety. • IBC requires all glazing in doors, sidelites and hazardous locations to meet CPSC Cat. I or II/ANSI Z97.1 impact safety. • Tested without hose stream and may require approval for 45 minute applications. • Used in fire protective doors, sidelites, openings, and transoms up to the maximum size tested. For a list of maximum sizes, visit https://safti.com/product/superlite-xl-igu/ • Safe and economical alternative to wire glass and expensive ceramics. • Can be combined with standard hollow metal frames or USA-made GPX Framing by SAFTI FIRST for a complete fire protective assembly. • Custom options such as insulated, decorative, and more available by calling SAFTI FIRST (Ph: 888.653.3333) <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. Minimum order 2 sq. ft. | Square Foot | \$62.24 | \$47.88 | \$42.56 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price (2-24 units) | GSA Price (25-500 units) | GSA Price (500+ units) |
|--------|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------------------|--------------------------|------------------------|
| 332321 | SL X-45/60/90 CI | <ul style="list-style-type: none"> • Clear, USA-made, 3/4", 45-90 minute fire protective glass that meets NFPA 252, UL 10B/10C for fire and CPSC Cat. I. • IBC requires all glazing in doors, sidelites and hazardous locations to meet CPSC Cat. I or II/ANSI Z97.1 impact safety. • Used in 45-90 minute door vision lites limited to 100 sq in. <ul style="list-style-type: none"> • Safe and economical alternative to wire glass and expensive ceramics. • Can be combined with standard hollow metal frames or USA-made GPX Framing by SAFTI FIRST for a complete fire protective assembly. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. <ul style="list-style-type: none"> • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Square Foot | \$28.05 | \$28.05 | \$28.05 |
| 332321 | SL X-45/60/90 CII | <ul style="list-style-type: none"> • Clear, USA-made, 3/4", 45-90 minute fire protective glass that meets NFPA 252, UL 10B/10C for fire and CPSC Cat. II. • IBC requires all glazing in doors, sidelites and hazardous locations to meet CPSC Cat. I or II/ANSI Z97.1 impact safety. • Used in 45-90 minute door vision lites limited to 100 sq in. <ul style="list-style-type: none"> • Safe and economical alternative to wire glass and expensive ceramics. • Can be combined with standard hollow metal frames or USA-made GPX Framing by SAFTI FIRST for a complete fire protective assembly. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. <ul style="list-style-type: none"> • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Square Foot | \$90.92 | \$90.92 | \$90.92 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-----------|
| 332321 | GPXW250-45-I | <ul style="list-style-type: none"> • 45 minute, 2-1/2" profile, fire resistive aluminum framing used in window/walls with SuperLite glazing from SAFTI FIRST. <ul style="list-style-type: none"> • Meets ASTM E-119/UL 263/NFPA 251. • Standard finish include Coraflon paint and clear anodized. For a list of standard and custom finishes, visit https://safti.com/gpx-architectural-series/ • Can be customized to meet hurricane, ballistic, blast, and more Call SAFTI FIRST (Ph: 888.653.3333) for more information. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Lineal Foot | \$74.48 |
| 332321 | GPXW250-60-I | <ul style="list-style-type: none"> • 60 minute, 2-1/2" profile, fire resistive aluminum framing used in window/walls with SuperLite glazing from SAFTI FIRST. • Meets ASTM E-119/UL 263/NFPA 251. IBC typically requires fire rated glass and framing assemblies 60 minute and above to meet ASTM E-119/UL 263/NFPA 251 fire resistive/temperature rise requirements. • Standard finish include Coraflon paint and clear anodized. For a list of standard and custom finishes, visit https://safti.com/gpx-architectural-series/ • Can be customized to meet hurricane, ballistic, blast, and more Call SAFTI FIRST (Ph: 888.653.3333) for more information. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Lineal Foot | \$74.48 |
| 332321 | GPXW250-90-I | <ul style="list-style-type: none"> • 90 minute, 2-1/2" profile, fire resistive aluminum framing used in window/walls with SuperLite glazing from SAFTI FIRST. • Meets ASTM E-119/UL 263/NFPA 251. IBC typically requires fire rated glass and framing assemblies 60 minute and above to meet ASTM E-119/UL 263/NFPA 251 fire resistive/temperature rise requirements. • Standard finish include Coraflon paint and clear anodized. For a list of standard and custom finishes, visit https://safti.com/gpx-architectural-series/ • Can be customized to meet hurricane, ballistic, blast, and more Call SAFTI FIRST (Ph: 888.653.3333) for more information. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Lineal Foot | \$74.48 |
| 332321 | GPXW250-120-I | <ul style="list-style-type: none"> • 120 minute, 2-1/2" profile, fire resistive aluminum framing used in window/walls with SuperLite glazing from SAFTI FIRST. • Meets ASTM E-119/UL 263/NFPA 251. IBC typically requires fire rated glass and framing assemblies 60 minute and above to meet ASTM E-119/UL 263/NFPA 251 fire resistive/temperature rise requirements. • Standard finish include Coraflon paint and clear anodized. For a list of standard and custom finishes, visit https://safti.com/gpx-architectural-series/ • Can be customized to meet hurricane, ballistic, blast, and more Call SAFTI FIRST (Ph: 888.653.3333) for more information. • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Lineal Foot | \$74.48 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-----------|
| 332321 | GPXW250-45-E | <ul style="list-style-type: none"> • 45 minute, 2-1/2" profile, fire resistive aluminum framing used in window/walls with SuperLite glazing from SAFTI FIRST. <ul style="list-style-type: none"> • Meets ASTM E-119/UL 263/NFPA 251. • Standard finish include Coraflon paint and clear anodized. For a list of standard and custom finishes, visit https://safti.com/gpx-architectural-series/ • Can be customized to meet hurricane, ballistic, blast, and more. Call SAFTI FIRST (Ph: 888.653.3333) for more information. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Lineal Foot | \$88.99 |
| 332321 | GPXW250-60-E | <ul style="list-style-type: none"> • 60 minute, 2-1/2" profile, fire resistive aluminum framing used in window/walls with SuperLite glazing from SAFTI FIRST. • Meets ASTM E-119/UL 263/NFPA 251. IBC typically requires fire rated glass and framing assemblies 60 minute and above to meet ASTM E-119/UL 263/NFPA 251 fire resistive/temperature rise requirements. • Standard finish include Coraflon paint and clear anodized. For a list of standard and custom finishes, visit https://safti.com/gpx-architectural-series/ • Can be customized to meet hurricane, ballistic, blast, and more. Call SAFTI FIRST (Ph: 888.653.3333) for more information. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Lineal Foot | \$88.99 |
| 332321 | GPXW250-90-E | <ul style="list-style-type: none"> • 90 minute, 2-1/2" profile, fire resistive aluminum framing used in window/walls with SuperLite glazing from SAFTI FIRST. • Meets ASTM E-119/UL 263/NFPA 251. IBC typically requires fire rated glass and framing assemblies 60 minute and above to meet ASTM E-119/UL 263/NFPA 251 fire resistive/temperature rise requirements. • Standard finish include Coraflon paint and clear anodized. For a list of standard and custom finishes, visit https://safti.com/gpx-architectural-series/ • Can be customized to meet hurricane, ballistic, blast, and more. Call SAFTI FIRST (Ph: 888.653.3333) for more information. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Lineal Foot | \$88.99 |
| 332321 | GPXW250-120-E | <ul style="list-style-type: none"> • 120 minute, 2-1/2" profile, fire resistive aluminum framing used in window/walls with SuperLite glazing from SAFTI FIRST. • Meets ASTM E-119/UL 263/NFPA 251. IBC typically requires fire rated glass and framing assemblies 60 minute and above to meet ASTM E-119/UL 263/NFPA 251 fire resistive/temperature rise requirements. • Standard finish include Coraflon paint and clear anodized. For a list of standard and custom finishes, visit https://safti.com/gpx-architectural-series/ • Can be customized to meet hurricane, ballistic, blast, and more. Call SAFTI FIRST (Ph: 888.653.3333) for more information. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Lineal Foot | \$88.99 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-----------|
| 332321 | CW350-60-I | <ul style="list-style-type: none"> • 60 minute, 3" profile, fire resistive aluminum for multi-story spans of glass with SuperLite II-XL glazing from SAFTI FIRST. • Meets ASTM E-119/UL 263/NFPA 251. IBC typically requires fire rated glass and framing assemblies 60 minute and above to meet ASTM E-119/UL 263/NFPA 251 fire resistive/temperature rise requirements. • Standard finish include Corafalon paint and clear anodized. For a list of standard and custom finishes, visit https://safti.com/gpx-curtain-wall/ • Can be customized to meet hurricane, ballistic, blast, and more. Call SAFTI FIRST (Ph: 888.653.3333) for more information. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Lineal Foot | \$122.84 |
| 332321 | CW350-90-I | <ul style="list-style-type: none"> • 90 minute, 3" profile, fire resistive aluminum for multi-story spans of glass with SuperLite II-XL glazing from SAFTI FIRST. • Meets ASTM E-119/UL 263/NFPA 251. IBC typically requires fire rated glass and framing assemblies 60 minute and above to meet ASTM E-119/UL 263/NFPA 251 fire resistive/temperature rise requirements. • Standard finish include Corafalon paint and clear anodized. For a list of standard and custom finishes, visit https://safti.com/gpx-curtain-wall/ • Can be customized to meet hurricane, ballistic, blast, and more. Call SAFTI FIRST (Ph: 888.653.3333) for more information. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Lineal Foot | \$122.84 |
| 332321 | CW350-120-I | <ul style="list-style-type: none"> • 120 minute, 3" profile, fire resistive aluminum for multi-story spans of glass with SuperLite II-XL glazing from SAFTI FIRST. • Meets ASTM E-119/UL 263/NFPA 251. IBC typically requires fire rated glass and framing assemblies 60 minute and above to meet ASTM E-119/UL 263/NFPA 251 fire resistive/temperature rise requirements. • Standard finish include Corafalon paint and clear anodized. For a list of standard and custom finishes, visit https://safti.com/gpx-curtain-wall/ • Can be customized to meet hurricane, ballistic, blast, and more. Call SAFTI FIRST (Ph: 888.653.3333) for more information. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Lineal Foot | \$122.84 |
| 332321 | CW350-60-E | <ul style="list-style-type: none"> • 60 minute, 3" profile, fire resistive aluminum for multi-story spans of glass with SuperLite II-XL glazing from SAFTI FIRST. • Meets ASTM E-119/UL 263/NFPA 251. IBC typically requires fire rated glass and framing assemblies 60 minute and above to meet ASTM E-119/UL 263/NFPA 251 fire resistive/temperature rise requirements. • Standard finish include Corafalon paint and clear anodized. For a list of standard and custom finishes, visit https://safti.com/gpx-curtain-wall/ • Can be customized to meet hurricane, ballistic, blast, and more. Call SAFTI FIRST (Ph: 888.653.3333) for more information. • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Lineal Foot | \$122.84 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-----------|
| 332321 | CW350-90-E | <ul style="list-style-type: none"> • 90 minute, 3" profile, fire resistive aluminum for multi-story spans of glass with SuperLite II-XL glazing from SAFTI FIRST. • Meets ASTM E-119/UL 263/NFPA 251. IBC typically requires fire rated glass and framing assemblies 60 minute and above to meet ASTM E-119/UL 263/NFPA 251 fire resistive/temperature rise requirements. • Standard finish include Coraflon paint and clear anodized. For a list of standard and custom finishes, visit https://safti.com/gpx-curtain-wall/ • Can be customized to meet hurricane, ballistic, blast, and more. Call SAFTI FIRST (Ph: 888.653.3333) for more information. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Lineal Foot | \$122.84 |
| 332321 | CW350-120-E | <ul style="list-style-type: none"> • 120 minute, 3" profile, fire resistive aluminum for multi-story spans of glass with SuperLite II-XL glazing from SAFTI FIRST. • Meets ASTM E-119/UL 263/NFPA 251. IBC typically requires fire rated glass and framing assemblies 60 minute and above to meet ASTM E-119/UL 263/NFPA 251 fire resistive/temperature rise requirements. • Standard finish include Coraflon paint and clear anodized. For a list of standard and custom finishes, visit https://safti.com/gpx-curtain-wall/ • Can be customized to meet hurricane, ballistic, blast, and more. Call SAFTI FIRST (Ph: 888.653.3333) for more information. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Lineal Foot | \$122.84 |
| 332321 | CW350HD-60-I | <ul style="list-style-type: none"> • 60 minute, 3" profile, reinforced fire resistive aluminum for multi-story spans of glass with SuperLite II-XL glazing from SAFTI FIRST. • Meets ASTM E-119/UL 263/NFPA 251. IBC typically requires fire rated glass and framing assemblies 60 minute and above to meet ASTM E-119/UL 263/NFPA 251 fire resistive/temperature rise requirements. • Standard finish include Coraflon paint and clear anodized. For a list of standard and custom finishes, visit https://safti.com/gpx-curtain-wall/ • Can be customized to meet hurricane, ballistic, blast, and more. Call SAFTI FIRST (Ph: 888.653.3333) for more information. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Lineal Foot | \$148.96 |
| 332321 | CW350HD-90-I | <ul style="list-style-type: none"> • 90 minute, 3" profile, reinforced fire resistive aluminum for multi-story spans of glass with SuperLite II-XL glazing from SAFTI FIRST. • Meets ASTM E-119/UL 263/NFPA 251. IBC typically requires fire rated glass and framing assemblies 60 minute and above to meet ASTM E-119/UL 263/NFPA 251 fire resistive/temperature rise requirements. • Standard finish include Coraflon paint and clear anodized. For a list of standard and custom finishes, visit https://safti.com/gpx-curtain-wall/ • Can be customized to meet hurricane, ballistic, blast, and more. Call SAFTI FIRST (Ph: 888.653.3333) for more information. • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Lineal Foot | \$148.96 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-----------|
| 332321 | CW350HD-120-I | <ul style="list-style-type: none"> • 120 minute, 3" profile, reinforced fire resistive aluminum for multi-story spans of glass with SuperLite II-XL glazing from SAFTI FIRST. • Meets ASTM E-119/UL 263/NFPA 251. IBC typically requires fire rated glass and framing assemblies 60 minute and above to meet ASTM E-119/UL 263/NFPA 251 fire resistive/temperature rise requirements. • Standard finish include Coraflon paint and clear anodized. For a list of standard and custom finishes, visit https://safti.com/gpx-curtain-wall/ • Can be customized to meet hurricane, ballistic, blast, and more. Call SAFTI FIRST (Ph: 888.653.3333) for more information. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Lineal Foot | \$148.96 |
| 332321 | CW350HD-60-E | <ul style="list-style-type: none"> • 60 minute, 3" profile, reinforced fire resistive aluminum for multi-story spans of glass with SuperLite II-XL glazing from SAFTI FIRST. • Meets ASTM E-119/UL 263/NFPA 251. IBC typically requires fire rated glass and framing assemblies 60 minute and above to meet ASTM E-119/UL 263/NFPA 251 fire resistive/temperature rise requirements. • Standard finish include Coraflon paint and clear anodized. For a list of standard and custom finishes, visit https://safti.com/gpx-curtain-wall/ • Can be customized to meet hurricane, ballistic, blast, and more. Call SAFTI FIRST (Ph: 888.653.3333) for more information. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Lineal Foot | \$148.96 |
| 332321 | CW350HD-90-E | <ul style="list-style-type: none"> • 90 minute, 3" profile, reinforced fire resistive aluminum for multi-story spans of glass with SuperLite II-XL glazing from SAFTI FIRST. • Meets ASTM E-119/UL 263/NFPA 251. IBC typically requires fire rated glass and framing assemblies 60 minute and above to meet ASTM E-119/UL 263/NFPA 251 fire resistive/temperature rise requirements. • Standard finish include Coraflon paint and clear anodized. For a list of standard and custom finishes, visit https://safti.com/gpx-curtain-wall/ • Can be customized to meet hurricane, ballistic, blast, and more. Call SAFTI FIRST (Ph: 888.653.3333) for more information. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Lineal Foot | \$148.96 |
| 332321 | CW350HD-120-E | <ul style="list-style-type: none"> • 120 minute, 3" profile, reinforced fire resistive aluminum for multi-story spans of glass with SuperLite II-XL glazing from SAFTI FIRST. • Meets ASTM E-119/UL 263/NFPA 251. IBC typically requires fire rated glass and framing assemblies 60 minute and above to meet ASTM E-119/UL 263/NFPA 251 fire resistive/temperature rise requirements. • Standard finish include Coraflon paint and clear anodized. For a list of standard and custom finishes, visit https://safti.com/gpx-curtain-wall/ • Can be customized to meet hurricane, ballistic, blast, and more. Call SAFTI FIRST (Ph: 888.653.3333) for more information. • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Lineal Foot | \$148.96 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM DS010-20-137 | <ul style="list-style-type: none"> • Size: 3'-0" X 7'-0" • Full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$2,691.87 |
| 332321 | HM DS010-20-138 | <ul style="list-style-type: none"> • Size: 3'-0" X 8'-0" • Full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$2,835.99 |
| 332321 | HM DS010-20-139 | <ul style="list-style-type: none"> • Size: 3'-0" X 9'-0" • Full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph:888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$2,835.99 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM DS010-20-1310 | <ul style="list-style-type: none"> • Size: 3'-0" X 10'-0" • Full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$4,840.14 |
| 332321 | HM DS010-20-147 | <ul style="list-style-type: none"> • Size: 4'-0" X 7'-0" • Full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$3,174.53 |
| 332321 | HM DS010-20-148 | <ul style="list-style-type: none"> • Size: 4'-0" X 8'-0" • Full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph:888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$3,487.92 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM DS010-20-149 | <ul style="list-style-type: none"> • Size: 4'-0" X 9'-0" • Full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$3,623.34 |
| 332321 | HM DS010-20-1410 | <ul style="list-style-type: none"> • Size: 4'-0" X 10'-0" • Full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$5,074.22 |
| 332321 | HM DP010-20-137 | <ul style="list-style-type: none"> • Size: 6'-0" X 7'-0" • Full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph:888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$5,096.46 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-------------|
| 332321 | HM DP010-20-138 | <ul style="list-style-type: none"> • Size: 6'-0" X 8'-0" • Full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$5,355.69 |
| 332321 | HM DP010-20-139 | <ul style="list-style-type: none"> • Size: 6'-0" X 9'-0" • Full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$7,714.82 |
| 332321 | HM DP010-20-1310 | <ul style="list-style-type: none"> • Size: 6'-0" X 10'-0" • Full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph:888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$10,132.96 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM DP010-20-147 | <ul style="list-style-type: none"> • Size: 8'-0" X 7'-0" • Full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$6,287.15 |
| 332321 | HM DP010-20-148 | <ul style="list-style-type: none"> • Size: 8'-0" X 8'-0" • Full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$6,616.99 |
| 332321 | HM DP010-20-149 | <ul style="list-style-type: none"> • Size: 8'-0" X 9'-0" • Full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph:888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$8,016.60 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-------------|
| 332321 | HM DP010-20-I410 | <ul style="list-style-type: none"> • Size: 8'-0" X 10'-0" • Full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$10,434.74 |
| 332321 | HM DS010-45-I37 | <ul style="list-style-type: none"> • Size: 3'-0" X 7'-0" • Full vision, 45 minute, steel fire protective door with SuperClear 45-HS 45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$3,236.43 |
| 332321 | HM DS010-45-I38 | <ul style="list-style-type: none"> • Size: 3'-0" X 8'-0" • Full vision, 45 minute, steel fire protective door with SuperClear 45-HS 45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. • Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$3,468.57 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM DS010-45-139 | <ul style="list-style-type: none"> • Size: 3'-0" X 9'-0" • Full vision, 45 minute, steel fire protective door with SuperClear 45-HS45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. • Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$5,560.75 |
| 332321 | HM DS010-45-1310 | <ul style="list-style-type: none"> • Size: 3'-0" X 10'-0" • Full vision, 45 minute, steel fire protective door with SuperClear 45-HS45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. • Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$5,560.75 |
| 332321 | HM DS010-45-147 | <ul style="list-style-type: none"> • Size: 4'-0" X 7'-0" • Full vision, 45 minute, steel fire protective door with SuperClear 45-HS 45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. • Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$3,899.97 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM DS010-45-148 | <ul style="list-style-type: none"> • Size: 4'-0" X 8'-0" • Full vision, 45 minute, steel fire protective door with SuperClear 45-HS45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. • Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$4,332.33 |
| 332321 | HM DS010-45-149 | <ul style="list-style-type: none"> • Size: 4'-0" X 9'-0" • Full vision, 45 minute, steel fire protective door with SuperClear 45-HS 45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. • Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$4,584.79 |
| 332321 | HM DS010-45-1410 | <ul style="list-style-type: none"> • Size: 4'-0" X 10'-0" • Full vision, 45 minute, steel fire protective door with SuperClear 45-HS 45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. • Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$6,035.67 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM DP010-45-137 | <ul style="list-style-type: none"> • Size: 6'-0" X 7'-0" • Full vision, 45 minute, steel fire protective door with SuperClear 45-HS45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. • Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$6,185.59 |
| 332321 | HM DP010-45-138 | <ul style="list-style-type: none"> • Size: 6'-0" X 8'-0" • Full vision, 45 minute, steel fire protective door with SuperClear 45-HS45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. • Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$6,621.82 |
| 332321 | HM DP010-45-139 | <ul style="list-style-type: none"> • Size: 6'-0" X 9'-0" • Full vision, 45 minute, steel fire protective door with SuperClear 45-HS 45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. • Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$9,176.34 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-------------|
| 332321 | HM DP010-45- I310 | <ul style="list-style-type: none"> • Size: 6'-0" X 10'-0" • Full vision, 45 minute, steel fire protective door with SuperClear 45-HS45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$11,390.39 |
| 332321 | HM DP010-45- I47 | <ul style="list-style-type: none"> • Size: 8'-0" X 7'-0" • Full vision, 45 minute, steel fire protective door with SuperClear 45-HS45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$7,739.00 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-------------|
| 332321 | HM DP010-45-I48 | <ul style="list-style-type: none"> • Size: 8'-0" X 8'-0" • Full vision, 45 minute, steel fire protective door with SuperClear 45-HS45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. • Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$8,304.85 |
| 332321 | HM DP010-45-I49 | <ul style="list-style-type: none"> • Size: 8'-0" X 9'-0" • Full vision, 45 minute, steel fire protective door with SuperClear 45-HS45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. • Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$9,939.51 |
| 332321 | HM DP010-45-I410 | <ul style="list-style-type: none"> • Size: 8'-0" X 10'-0" • Full vision, 45 minute, steel fire protective door with SuperClear 45-HS 45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. • Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$11,575.13 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM TRDS020- 60-137 | <ul style="list-style-type: none"> • Size: 3'-0" X 7'-0" • Full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$3,616.56 |
| 332321 | HM TRDS020- 60-138 | <ul style="list-style-type: none"> • Size: 3'-0" X 8'-0" • Full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$3,897.07 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM TRDS020-60-I39 | <ul style="list-style-type: none"> • Size: 3'-0" X 9'-0" • Full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$4,319.76 |
| 332321 | HM TRDS020-60-I310 | <ul style="list-style-type: none"> • Size: 3'-0" X 10'-0" • Full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$5,770.64 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM TRDS020- 60-147 | <ul style="list-style-type: none"> • Size: 4'-0" X 7'-0" • Full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$4,483.22 |
| 332321 | HM TRDS020- 60-148 | <ul style="list-style-type: none"> • Size: 4'-0" X 8'-0" • Full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$4,787.91 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM TRDS020- 60-149 | <ul style="list-style-type: none"> • Size: 4'-0" X 9'-0" • Full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$5,415.66 |
| 332321 | HM TRDS020- 60-1410 | <ul style="list-style-type: none"> • Size: 4'-0" X 10'-0" • Full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$5,224.14 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM TRDP020-60-137 | <ul style="list-style-type: none"> • Size: 6'-0" X 7'-0" • Full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$6,984.54 |
| 332321 | HM TRDP020-60-138 | <ul style="list-style-type: none"> • Size: 6'-0" X 8'-0" • Full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$7,440.12 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-------------|
| 332321 | HM TRDP020-60-I39 | <ul style="list-style-type: none"> • Size: 6'-0" X 9'-0" • Full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$10,238.39 |
| 332321 | HM TRDP020-60-I310 | <ul style="list-style-type: none"> • Size: 6'-0" X 10'-0" • Full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$12,656.52 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM TRDP020-60-147 | <ul style="list-style-type: none"> • Size: 8'-0" X 7'-0" • Full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$8,269.06 |
| 332321 | HM TRDP020-60-148 | <ul style="list-style-type: none"> • Size: 8'-0" X 8'-0" • Full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$9,588.39 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-------------|
| 332321 | HM TRDP020-60-149 | <ul style="list-style-type: none"> • Size: 8'-0" X 9'-0" • Full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$11,275.28 |
| 332321 | HM TRDP020-60-1410 | <ul style="list-style-type: none"> • Size: 8'-0" X 10'-0" • Full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$13,693.42 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM TRDS020-90-137 | <ul style="list-style-type: none"> • Size: 3'-0" X 7'-0" • Full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$4,215.29 |
| 332321 | HM TRDS020-90-138 | <ul style="list-style-type: none"> • Size: 3'-0" X 8'-0" • Full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$4,591.56 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM TRDS020- 90-I39 | <ul style="list-style-type: none"> • Size: 3'-0" X 9'-0" • Full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$5,129.35 |
| 332321 | HM TRDS020- 90-I310 | <ul style="list-style-type: none"> • Size: 3'-0" X 10'-0" • Full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$6,580.23 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM TRDS020- 90-147 | <ul style="list-style-type: none"> • Size: 4'-0" X 7'-0" • Full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$5,281.21 |
| 332321 | HM TRDS020- 90-148 | <ul style="list-style-type: none"> • Size: 4'-0" X 8'-0" • Full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$5,714.54 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM TRDS020- 90-149 | <ul style="list-style-type: none"> • Size: 4'-0" X 9'-0" • Full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$6,280.38 |
| 332321 | HM TRDS020- 90-1410 | <ul style="list-style-type: none"> • Size: 4'-0" X 10'-0" • Full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$7,731.26 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM TRDP020- 90-137 | <ul style="list-style-type: none"> • Size: 6'-0" X 7'-0" • Full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$8,181.04 |
| 332321 | HM TRDP020- 90-138 | <ul style="list-style-type: none"> • Size: 6'-0" X 8'-0" • Full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$8,830.07 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-------------|
| 332321 | HM TRDP020-90-139 | <ul style="list-style-type: none"> • Size: 6'-0" X 9'-0" • Full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$11,822.75 |
| 332321 | HM TRDP020-90-1310 | <ul style="list-style-type: none"> • Size: 6'-0" X 10'-0" • Full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$14,240.89 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-------------|
| 332321 | HM TRDP020- 90-147 | <ul style="list-style-type: none"> • Size: 8'-0" X 7'-0" • Full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$9,864.06 |
| 332321 | HM TRDP020- 90-148 | <ul style="list-style-type: none"> • Size: 8'-0" X 8'-0" • Full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$11,442.62 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-------------|
| 332321 | HM TRDP020-90-149 | <ul style="list-style-type: none"> • Size: 8'-0" X 9'-0" • Full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$13,387.77 |
| 332321 | HM TRDP020-90-1410 | <ul style="list-style-type: none"> • Size: 8'-0" X 10'-0" • Full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinklered. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$15,806.87 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM DS010- 20-E37 | <ul style="list-style-type: none"> • Size: 3'-0" X 7'-0" • Exterior full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST(Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$3,893.20 |
| 332321 | HM DS010- 20-E38 | <ul style="list-style-type: none"> • Size: 3'-0" X 8'-0" • Exterior full vision, 20 minute steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST(Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$4,059.57 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM DS010-20-E39 | <ul style="list-style-type: none"> • Size: 3'-0" X 9'-0" • Exterior full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$4,695.05 |
| 332321 | HM DS010-20-E310 | <ul style="list-style-type: none"> • Size: 3'-0" X 10'-0" • Exterior full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$6,363.57 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM DS010-20-E47 | <ul style="list-style-type: none"> • Size: 4'-0" X 7'-0" • Exterior full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$4,448.40 |
| 332321 | HM DS010-20-E48 | <ul style="list-style-type: none"> • Size: 4'-0" X 8'-0" • Exterior full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$4,809.19 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-------------|
| 332321 | HM DS010-20-E49 | <ul style="list-style-type: none"> • Size: 4'-0" X 9'-0" • Exterior full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O’Keeffe’s, Inc. DBA SAFTI FIRST. | Each | \$ 4,964.92 |
| 332321 | HM DS010-20-E410 | <ul style="list-style-type: none"> • Size: 4'-0" X 10'-0" Exterior full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O’Keeffe’s, Inc. DBA SAFTI FIRST. | Each | \$5,872.20 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM DP010-20-E37 | <ul style="list-style-type: none"> • Size: 6'-0" X 7'-0" • Exterior full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$7,456.56 |
| 332321 | HM DP010-20-E38 | <ul style="list-style-type: none"> • Size: 6'-0" X 8'-0" • Exterior full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. • Listed and labeled by UL and/or Intertek. Price does not include freight, crate, or installation. <ul style="list-style-type: none"> • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$7,755.45 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-------------|
| 332321 | HM DP010-20-E39 | <ul style="list-style-type: none"> • Size: 6'-0" X 9'-0" • Exterior full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$10,467.63 |
| 332321 | HM DP010-20-E310 | <ul style="list-style-type: none"> • Size: 6'-0" X 10'-0" • Exterior full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$13,248.48 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM DP010-20-E47 | <ul style="list-style-type: none"> • Size: 8'-0" X 7'-0" • Exterior full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$8,826.20 |
| 332321 | HM DP010-20-E48 | <ul style="list-style-type: none"> • Size: 8'-0" X 8'-0" • Exterior full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$9,205.36 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-------------|
| 332321 | HM DP010-20-E49 | <ul style="list-style-type: none"> • Size: 8'-0" X 9'-0" • Exterior full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$10,814.87 |
| 332321 | HM DP010-20-E410 | <ul style="list-style-type: none"> • Size: 8'-0" X 10'-0" • Exterior full vision, 20 minute, steel fire protective door with SuperLite I 20 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$13,595.73 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM DS010-45-E37 | <ul style="list-style-type: none"> • Size: 3'-0" X 7'-0" • Exterior full vision, 45 minute, steel fire protective door with SuperClear 45-HS 45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$4,519.01 |
| 332321 | HM DS010-45-E38 | <ul style="list-style-type: none"> • Size: 3'-0" X 8'-0" • Exterior full vision, 45 minute, steel fire protective door with SuperClear 45-HS 45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$4,786.94 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM DS010-45-E39 | <ul style="list-style-type: none"> • Size: 3'-0" X 9'-0" • Exterior full vision, 45 minute, steel fire protective door with SuperClear 45-HS 45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O’Keeffe’s, Inc. DBA SAFTI FIRST. | Each | \$7,192.50 |
| 332321 | HM DS010-45-E310 | <ul style="list-style-type: none"> • Size: 3'-0" X 10'-0" • Exterior full vision, 45 minute, steel fire protective door with SuperClear 45-HS 45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O’Keeffe’s, Inc. DBA SAFTI FIRST. | Each | \$7,192.50 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM DS010-45-E47 | <ul style="list-style-type: none"> • Size: 4'-0" X 7'-0" • Exterior full vision, 45 minute, steel fire protective door with SuperClear 45-HS 45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$5,283.14 |
| 332321 | HM DS010-45-E48 | <ul style="list-style-type: none"> • Size: 4'-0" X 8'-0" • Exterior full vision, 45 minute, steel fire protective door with SuperClear 45-HS 45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$5,779.35 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM DS010-45-E49 | <ul style="list-style-type: none"> • Size: 4'-0" X 9'-0" • Exterior full vision, 45 minute, steel fire protective door with SuperClear 45-HS 45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$6,070.49 |
| 332321 | HM DS010-45-E410 | <ul style="list-style-type: none"> • Size: 4'-0" X 10'-0" Exterior full vision, 45 minute, steel fire protective door with SuperClear 45-HS 45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$7,739.00 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM DP010-45-E37 | <ul style="list-style-type: none"> • Size: 6'-0" X 7'-0" • Exterior full vision, 45 minute, steel fire protective door with SuperClear 45-HS 45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$8,709.16 |
| 332321 | HM DP010-45-E38 | <ul style="list-style-type: none"> • Size: 6'-0" X 8'-0" • Exterior full vision, 45 minute, steel fire protective door with SuperClear 45-HS 45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$9,211.16 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-------------|
| 332321 | HM DP010-45-E39 | <ul style="list-style-type: none"> • Size: 6'-0" X 9'-0" • Exterior full vision, 45 minute, steel fire protective door with SuperClear 45-HS 45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$12,126.47 |
| 332321 | HM DP010-45-E310 | <ul style="list-style-type: none"> • Size: 6'-0" X 10'-0" • Exterior full vision, 45 minute, steel fire protective door with SuperClear 45-HS 45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. Listed and labeled by UL and/or Intertek. <ul style="list-style-type: none"> • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$14,907.32 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-------------|
| 332321 | HM DP010-45-E47 | <ul style="list-style-type: none"> • Size: 8'-0" X 7'-0" • Exterior full vision, 45 minute, steel fire protective door with SuperClear 45-HS 45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$10,495.68 |
| 332321 | HM DP010-45-E48 | <ul style="list-style-type: none"> • Size: 8'-0" X 8'-0" • Exterior full vision, 45 minute, steel fire protective door with SuperClear 45-HS 45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$11,146.64 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-------------|
| 332321 | HM DP010-45-E49 | <ul style="list-style-type: none"> • Size: 8'-0" X 9'-0" • Exterior full vision, 45 minute, steel fire protective door with SuperClear 45-HS 45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. • Listed and labeled by UL and/or Intertek. Price does not include freight, crate, or installation. <ul style="list-style-type: none"> • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$13,026.02 |
| 332321 | HM DP010-45-E410 | <ul style="list-style-type: none"> • Size: 8'-0" X 10'-0" • Exterior full vision, 45 minute, steel fire protective door with SuperClear 45-HS 45 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. Call SAFTI FIRST (Ph: 888.653.3333) for finish options. Call SAFTI FIRST (Ph: 888.653.3333) for exterior applications. <ul style="list-style-type: none"> • Listed and labeled by UL and/or Intertek. • Price does not include freight, crate, or installation. • Made by O'Keeffe's, Inc. DBA SAFTI FIRST. | Each | \$14,694.53 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM TRDS020-60-E37 | <ul style="list-style-type: none"> • Size: 3'-0" X 7'-0" • Exterior full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$4,957.18 |
| 332321 | HM TRDS020-60-E38 | <ul style="list-style-type: none"> • Size: 3'-0" X 8'-0" • Exterior full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$5,279.27 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM TRDS020-60- E39 | <ul style="list-style-type: none"> • Size: 3'-0" X 9'-0" • Exterior full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$5,764.84 |
| 332321 | HM TRDS020-60- E310 | <ul style="list-style-type: none"> • Size: 3'-0" X 10'-0" • Exterior full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$7,433.35 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM TRDS020-60- E47 | <ul style="list-style-type: none"> • Size: 4'-0" X 7'-0" • Exterior full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$5,953.45 |
| 332321 | HM TRDS020-60- E48 | <ul style="list-style-type: none"> • Size: 4'-0" X 8'-0" • Exterior full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$6,303.60 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM TRDS020-60- E49 | <ul style="list-style-type: none"> • Size: 4'-0" X 9'-0" • Exterior full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$6,805.60 |
| 332321 | HM TRDS020-60- E410 | <ul style="list-style-type: none"> • Size: 4'-0" X 10'-0" • Exterior full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$8,474.12 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-------------|
| 332321 | HM TRDPO20-60-E37 | <ul style="list-style-type: none"> • Size: 6'-0" X 7'-0" • Exterior full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$9,628.05 |
| 332321 | HM TRDPO20-60-E38 | <ul style="list-style-type: none"> • Size: 6'-0" X 8'-0" • Exterior full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$10,151.34 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-------------|
| 332321 | HM TRDPO20-60- E39 | <ul style="list-style-type: none"> • Size: 6'-0" X 9'-0" • Exterior full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$13,370.36 |
| 332321 | HM TRDPO20-60- E310 | <ul style="list-style-type: none"> • Size: 6'-0" X 10'-0" • Exterior full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$16,151.21 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-------------|
| 332321 | HM TRDPO20-60- E47 | <ul style="list-style-type: none"> • Size: 8'-0" X 7'-0" • Exterior full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$11,105.05 |
| 332321 | HM TRDPO20-60- E48 | <ul style="list-style-type: none"> • Size: 8'-0" X 8'-0" • Exterior full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$12,622.67 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-------------|
| 332321 | HM TRDP020-60- E49 | <ul style="list-style-type: none"> Size: 8'-0" X 9'-0" Exterior full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$14,562.98 |
| 332321 | HM TRDP020-60- E410 | <ul style="list-style-type: none"> Size: 8'-0" X 10'-0" Exterior full vision, 60 minute, steel temperature rise door with SuperLite II-XL 60 minute glazing. Both made in the USA by SAFTI FIRST. Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. Meets temperature rise to 250F/450F at 60 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$17,343.84 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM TRDS020-90- E37 | <ul style="list-style-type: none"> • Size: 3'-0" X 7'-0" • Exterior full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$5,645.86 |
| 332321 | HM TRDS020-90- E38 | <ul style="list-style-type: none"> • Size: 3'-0" X 8'-0" • Exterior full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$6,079.19 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM TRDS020-90- E39 | <ul style="list-style-type: none"> • Size: 3'-0" X 9'-0" • Exterior full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$6,697.27 |
| 332321 | HM TRDS020-90- E310 | <ul style="list-style-type: none"> • Size: 3'-0" X 10'-0" • Exterior full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$8,365.78 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM TRDS020-90- E47 | <ul style="list-style-type: none"> • Size: 4'-0" X 7'-0" • Exterior full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$6,871.38 |
| 332321 | HM TRDS020-90- E48 | <ul style="list-style-type: none"> • Size: 4'-0" X 8'-0" • Exterior full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$7,369.51 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| 332321 | HM TRDS020-90- E49 | <ul style="list-style-type: none"> • Size: 4'-0" X 9'-0" • Exterior full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$8,020.47 |
| 332321 | HM TRDS020-90- E410 | <ul style="list-style-type: none"> • Size: 4'-0" X 10'-0" • Exterior full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$9,688.99 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-------------|
| 332321 | HM TRDP020-90- E37 | <ul style="list-style-type: none"> • Size: 6'-0" X 7'-0" • Exterior full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$11,004.45 |
| 332321 | HM TRDP020-90- E38 | <ul style="list-style-type: none"> • Size: 6'-0" X 8'-0" • Exterior full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$11,751.17 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-------------|
| 332321 | HM TRDP020-90- E39 | <ul style="list-style-type: none"> • Size: 6'-0" X 9'-0" • Exterior full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$15,192.66 |
| 332321 | HM TRDP020-90- E310 | <ul style="list-style-type: none"> • Size: 6'-0" X 10'-0" • Exterior full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$15,836.86 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-------------|
| 332321 | HM TRDP020-90- E47 | <ul style="list-style-type: none"> • Size: 8'-0" X 7'-0" • Exterior full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$11,105.05 |
| 332321 | HM TRDP020-90- E48 | <ul style="list-style-type: none"> • Size: 8'-0" X 8'-0" • Exterior full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$16,512.04 |

| SIN | Part Number | Product Description | Unit of Issue | GSA Price |
|--------|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-------------|
| 332321 | HM TRDPO20-90- E49 | <ul style="list-style-type: none"> • Size: 8'-0" X 9'-0" • Exterior full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$16,771.68 |
| 332321 | HM TRDPO20-90- E410 | <ul style="list-style-type: none"> • Size: 8'-0" X 10'-0" • Exterior full vision, 90 minute, steel temperature rise door with SuperLite II-XL 90 minute glazing. Both made in the USA by SAFTI FIRST. • Meets NFPA 252/UL 10B/UL 10C for fire and CPSC Cat. II/ANSI Z.971 for impact safety. IBC requires all glazing in doors to meet CPSC Cat. I or II/ANSI Z97.1 for impact safety. • Meets temperature rise to 250F/450F at 90 minutes. IBC requires fire rated glazing exceeding 100 sq. in. in the door vision panels in 60-90 minute temperature rise doors to meet ASTM E-119/UL 263/NFPA 251 regardless if the building is fully sprinkle red. • Glazing to be installed in the field by others. Doors are prepared for hardware per ANSI/SDI A250.6. Depending on hardware specified, field preparation may be required. Hardware to be installed in the field by others. Call SAFTI FIRST (Ph: 888.653.3333) for a list of hardware options. • Standard finishes include Coraflan paint or primed for field paint. Custom finishes include stainless steel and aluminum clad. | Each | \$17,931.00 |

LIMITED WARRANTY

FURNISHED TO: SAMPLE

PROJECT: SAMPLE

SALES ORDER: SAMPLE

SAFTI *FIRST* warrants that their products shall be free from defective material and comply with SAFTI *FIRST*'s published Quality Specifications and Inspection Standards for a period of five (5) years from the date of delivery provided that said products have been installed and maintained in accordance with SAFTI *FIRST*'s installation instructions and published maintenance recommendations. This warranty is limited to defects appearing in the door, window or wall framing and glazing components. This warranty is limited to the glass and framing manufacturing only and does not cover "hardware supplied by others". Should there be a defect found in operating difficulty with any hardware component, Owner should contact the respective manufacturer or consult the warranty agreement that covers the hardware component in question.

This warranty is limited to the repair or replacement of defective material or entire product and shall be determined at the discretion of the manufacturer as to what action to take.

SAFTI *FIRST* extends the SuperLite II-XL manufacturer's warranty to the immediate buyer. The conditions of this warranty for the SuperLite II-XL glazing material are as follows:

The supplier warrants its immediate buyers for a period of five (5) years from the date of delivery that under normal conditions, the free vision through the SuperLite II-XL glass will not be adversely affected.

The use of tempered glass as well as the clear, fire resistive intumescent interlayer can lead to certain optical irregularities, especially near the glass edges. These inherent irregularities do not affect the free vision through the glass. Normal conditions imply in particular that the clear, fire resistive intumescent interlayer is not allowed to reach temperatures below 32 degrees Fahrenheit or over 140 degrees Fahrenheit (0 – 60 degrees Celsius).

The warranty is subject to the following provisions:

- A liability under this warranty is limited to free repair or replacement (at the manufacturer's discretion) of defective glass and/or frames and shall not extend to any other damages in connection with defective glass. Installation of the replacement glass into GPX framing is not covered under this warranty.
- The warranty shall not apply to units which have not been handled in accordance with normal conditions of use, or units which have been subsequently processed or modified in any way, or units which have been subject to any damage affecting the bond of the SuperLite II-XL units. Normal conditions of use include but are not limited to temperatures between 32 degrees Fahrenheit and 140 degrees Fahrenheit.
- Manufacturer's warranties on component parts of materials may differ from the terms specified herein and will supersede SAFTI *FIRST*'s standard warranty.
- The manufacturer's liability will also not apply in cases where defects are not reported within 30 days after they have become recognizable by the initial buyer or by the users of the building into which SuperLite II-XL has been installed. Liability will therefore expire at the latest 30 days after the expiration of the warranty, also if the defect has not been recognizable before expiration of the 5-year warranty period. Any glass replaced or repaired under this warranty is limited by the original warranty period and shall not be extended beyond the original five years.
- Furthermore, the conditions for quality complaints according to the manufacturer's general conditions of sale for export shall apply.
- If SuperLite II-XL is exported to a country other than where the initial delivery has been made, the warranty will only be valid if the manufacturer has accepted this exportation.
- Building and safety codes vary widely throughout the world. SAFTI *FIRST* does not control nor will it be responsible for the selection of product supplied by others, configurations, or the glazing materials used in the manufacture of its door, window or wall systems. SAFTI *FIRST* makes no other warranties or representation, either expressed or implied, concerning product fitness for a particular purpose. SAFTI *FIRST* will fabricate to dimensions shown on approved drawings but will not take responsibility for failure of submitting party(s) shop drawing dimensions against job site conditions. In no event will SAFTI *FIRST* be liable for direct, indirect, special or consequential damages including but not limited to loss of profit or use.
- SAFTI *FIRST* reserves the right to inspect or have returned all products alleged to be defective excluding shipping and handling costs.
- SAFTI *FIRST* makes no other warranty, expressed or implied, regarding its products.

SAMPLE
Karen Lim, Sales Administrator

SAMPLE
Date

LIMITED WARRANTY

FURNISHED TO: SAMPLE

PROJECT: SAMPLE

SALES ORDER: SAMPLE

SAFTI *FIRST* warrants that their products shall be free from defective material and comply with SAFTI *FIRST*'s published Quality Specifications and Inspection Standards for a period of ten (10) years from the date of delivery, provided that said products have been installed and maintained in accordance with SAFTI *FIRST*'s installation instructions and published maintenance recommendations.

This warranty is limited to the replacement of defective material and shall be determined at the discretion of the manufacturer as to what action to take.

SAFTI *FIRST* extends the SuperLite I-XL IGU manufacturer's warranty to the immediate buyer. The conditions of this warranty for the SuperLite I-XL IGU glazing material are as follows:

The supplier warrants its immediate buyers for a period of ten (10) years from the date of delivery that under normal conditions, the free vision through the SuperLite I-XL IGU glass will not be adversely affected.

The warranty is subject to the following provisions:

- A liability under this warranty is limited to free replacement (at the manufacturer's discretion) of defective glass and shall not extend to any other damages in connection with defective glass. Installation of the replacement glass is not covered under this warranty.
- The warranty shall not apply to units which have not been handled in accordance with normal conditions of use, or units which have been subsequently processed or modified in any way, or units which have been subject to any damage affecting the bond of the SuperLite I-XL IGU units.
- The manufacturer's liability will also not apply in cases where defects are not reported within 30 days after they have become recognizable by the initial buyer or by a subsequent buyer or by the users of the building into which SuperLite I-XL IGU has been installed. Liability will therefore expire at the latest 30 days after the expiration of the warranty, also if the defect has not been recognizable before expiration of the 10-year warranty period. Any glass replaced or repaired under this warranty is limited by the original warranty period and shall not be extended beyond the original ten years.
- Furthermore, the conditions for quality complaints according to the manufacturer's general conditions of sale for export shall apply.
- If SuperLite I-XL IGU is exported to a country other than where the initial delivery has been made, the warranty will only be valid if the manufacturer has accepted this exportation.
- Building and safety codes vary widely throughout the world. SAFTI *FIRST* does not control nor will it be responsible for the selection of product supplied by others, configurations, or the glazing materials used in the manufacture of its door, window or wall systems. SAFTI *FIRST* makes no other warranties or representation, either expressed or implied, concerning product fitness for a particular purpose. SAFTI *FIRST* will fabricate to dimensions shown on approved drawings but will not take responsibility for failure of submitting party(s) shop drawing dimensions against job site conditions. In no event will SAFTI *FIRST* be liable for direct, indirect, special or consequential damages including but not limited to loss of profit or use.
- SAFTI *FIRST* reserves the right to inspect or have returned all products alleged to be defective excluding shipping and handling costs.
- SAFTI *FIRST* makes no other warranty, expressed or implied, regarding its products.

SAMPLE
Karen Lim, Sales Administrator

SAMPLE
Date

LIMITED WARRANTY

FURNISHED TO: SAMPLE

PROJECT: SAMPLE

SALES ORDER: SAMPLE

SAFTI *FIRST* warrants that their products shall be free from defective material and comply with SAFTI *FIRST*'s published Quality Specifications and Inspection Standards for the entire life of the product from the date of delivery, provided that said products have been installed and maintained in accordance with SAFTI *FIRST*'s installation instructions and published maintenance recommendations.

This warranty is limited to the replacement of defective material and shall be determined at the discretion of the manufacturer as to what action to take.

SAFTI *FIRST* extends the SuperClear 45-HS/SuperClear 45-HS-LI manufacturer's warranty to the immediate buyer. The conditions of this warranty for the SuperClear 45-HS/SuperClear 45-HS-LI glazing material are as follows:

The supplier warrants its immediate buyers for the entire life of the product from the date of delivery that under normal conditions, the free vision through the SuperClear 45-HS/SuperClear 45-HS-LI glass will not be adversely affected.

The warranty is subject to the following provisions:

- A liability under this warranty is limited to free replacement (at the manufacturer's discretion) of defective glass and shall not extend to any other damages in connection with defective glass. Installation of the replacement glass is not covered under this warranty.
- The warranty shall not apply to units which have not been handled in accordance with normal conditions of use, or units which have been subsequently processed or modified in any way, or units which have been subject to any damage affecting the bond of the SuperClear 45-HS/SuperClear 45-HS-LI units.
- The manufacturer's liability will also not apply in cases where defects are not reported within 30 days after they have become recognizable by the initial buyer or by a subsequent buyer or by the users of the building into which SuperClear 45-HS/SuperClear 45-HS-LI has been installed.
- Furthermore, the conditions for quality complaints according to the manufacturer's general conditions of sale for export shall apply.
- If SuperClear 45-HS/SuperClear 45-HS-LI is exported to a country other than where the initial delivery has been made, the warranty will only be valid if the manufacturer has accepted this exportation.
- Building and safety codes vary widely throughout the world. SAFTI *FIRST* does not control nor will it be responsible for the selection of product supplied by others, configurations, or the glazing materials used in the manufacture of its door, window or wall systems. SAFTI *FIRST* makes no other warranties or representation, either expressed or implied, concerning product fitness for a particular purpose. SAFTI *FIRST* will fabricate to dimensions shown on approved drawings but will not take responsibility for failure of submitting party(s) shop drawing dimensions against job site conditions. In no event will SAFTI *FIRST* be liable for direct, indirect, special or consequential damages including but not limited to loss of profit or use.
- SAFTI *FIRST* reserves the right to inspect or have returned all products alleged to be defective excluding shipping and handling costs.
- SAFTI *FIRST* makes no other warranty, expressed or implied, regarding its products.

SAMPLE
Karen Lim, Sales Administrator

SAMPLE
Date