

**GENERAL SERVICES ADMINISTRATION
FEDERAL SUPPLY SERVICE
AUTHORIZED FEDERAL SUPPLY SCHEDULE PRICELIST**

On-line access to contract ordering information, terms and conditions, up-to-date pricing, and the option to create an electronic delivery order are available through GSA *Advantage!*, a menu-driven database system. The INTERNET address GSA *Advantage!* is: www.fss.gsa.gov.

Federal Supply Schedule 084- Total Solutions for Law Enforcement, Security, Facility Management Systems, Fire, Rescue, Special Purpose Clothing, Marine Craft and Emergency/Disaster Response

**Federal Supply Group: 84-Law Enforcement and Security Equipment
FS Class: 1940**

Contract Number: **GS-07F-0613N**

For more information on ordering from Federal Supply Schedules click on the FSS Schedules button at <http://www.fss.gsa.gov>

Contract Period: June 11, 2003 – June 10, 2008

Contractor: Night Vision Technologies, Inc.
111 North Nursery Road
Irving, Texas 75017-1305
972-554-3977 (phone)
972-374-4060(fax)
www.nvti-usa.com

Business Size: Small Business

Contract Administrator: Sonia Foster

CUSTOMER INFORMATION:

1a. Awarded Special Item Number(s):

<u>Special Item Number (SIN)</u>	<u>Descriptions</u>	<u>Pricing</u>
260-99	New Items (FSC 1940)	See attached price list

1b. Identification of the lowest priced model number and lowest unit price for that model for each special item number awarded in the contract: See attached page

1c. If the Contractor is proposing hourly rates, a description of all corresponding commercial job titles with experience, functional responsibility and education for those types of employees or subcontractors who will perform services shall be provided: Not Applicable.

2. Maximum Order: \$100,000.00

3. Minimum Order: \$100.00

4. Geographic Coverage: Domestic Only

5. Point of Production: Night Vision Technologies, Inc
111 North Nursery Road
Irving, Texas 75017-1305

6. Basic Discount: 1.99% from the Night Vision Technologies, Inc. Commercial Price List

7. Quantity Discount: NONE
8. Prompt payment terms: NET 30 Days
- 9a. Government purchase cards are accepted below and above the micro-purchase threshold.
10. Foreign items: NONE
- 11a. Time of Delivery: 120 Days
- 11b. Expedited Delivery: NONE
- 11c. Overnight/2-Day Delivery: Not Applicable
- 11d. Urgent Requirements: Not Applicable
12. FOB point: FOB Origin
13. Ordering Address: Night Vision Technologies, Inc
111 North Nursery Road
Irving, Texas 75017-1305
14. Payment Address: Night Vision Technologies, Inc
111 North Nursery Road
Irving, Texas 75017-1305
15. Warranty Provision: Standard Commercial Warranty
16. Export Packing Charges: Not Applicable
17. Terms and Conditions of Government Purchase Card Acceptance: All Amounts
18. Terms and Conditions of rental, maintenance, and repair: Not Applicable
19. Terms and Conditions of installation: Not Applicable
20. Terms and Conditions of repair parts: Not Applicable
- 20a. Terms and Conditions for any other services: Not Applicable
21. List of service and distribution points: None
22. List of participating dealers: None
23. Preventive maintenance: None
- 24a. Environmental attributes, e.g. recycled content, energy efficiency, and/or reduced pollutants: Not Applicable
- 24b. Section 508 Compliance: Not applicable
25. Data Universal Number System (DUNS) number: 124380283
26. Night Vision Technologies, Inc. is currently registered in the Central Contractor Registration (CCR) Database.

<i>Mfr Part #</i>	<i>Product</i>	<i>Description</i>	<u>GSA Price + IFF</u>
1100-C	Night/Day 100mm Thermal Imager, Long Range, Remote Pan/Tilt/Zoom	Remote Pan/Tilt housing; thermal imager with 100mm lens w/ 2x digital zoom. 320x240 pixel un-cooled (BST) . Camera integrated into weatherproof, sealed, non-rusting pan/tilt head mechanism with controller. NTSC signal output.	\$46,444.84
1018i-C	Night/Day 25mm Thermal Imager, Remote Pan/Tilt	Remote Pan/Tilt housing; thermal imager with 25mm lens 160x120 pixel un-cooled (AS) . Weatherproof, sealed, non-rusting pan/tilt head mechanism with controller. 360 degree pan. NTSC signal output.	\$16,446.09
3000i-C	Night/Day 25mm Thermal Imager/Color/Ultra Low-Lux camera system	Remote Pan/Tilt housing;IR with 25mm lens 160x120 pixel un-cooled (AS), low-lux and color camera . Weatherproof, non-rusting pan/tilt head mechanism with controller. NTSC signal output (RS232-485).	\$33,864.72
3100-C	Night/Day 50mm Thermal Imager/Color/Ultra Low-Lux camera system	Remote Pan/Tilt housing;IR with 50mm lens 320x240 pixel un-cooled (BST), low-lux and color camera . Weatherproof, non-rusting pan/tilt head mechanism with controller. NTSC signal output (RS232-485).	\$42,574.04
3200-C	Night/Day 75mm Thermal Imager/Color/Ultra Low-Lux camera system	Remote Pan/Tilt housing;IR with 75mm lens 320x240 pixel un-cooled (BST), low-lux and color camera . Weatherproof, non-rusting pan/tilt head mechanism with controller. NTSC signal output (RS232-485).	\$52,251.06
125-C	Night/Day 25mm Thermal Imager Camera, stationary mount	Stationary housing/tilt thermal imager with 25mm lens. 7-14 micron range IR, 160x120 pixel un-cooled amorphous silicon microbolometer. Camera integrated into weatherproof, non-rusting stainless mounting bracket. Controller, electronics interface module and standard cables/lengths. 12Vdc input, NTSC signal output, includes operation/installation instructions.Equipment is suitable for Homeland Security and the Global War on Terror.	\$11,725.98
225-C	Night/Day 25mm Thermal Imager and Color Camera system, stationary mount	Stationary housing/tilt thermal imager with 25mm lens. 7-14 micron range IR, 160x120 pixel un-cooled amorphous silicon microbolometer and high resolution 220x zoom color camera. Both cameras integrated into weatherproof, non-rusting stainless mounting bracket. Controller, electronics interface module and standard cables/lengths. 12Vdc input, NTSC signal output, includes operation/installation instructions. Equipment is suitable for Homeland Security and the Global War on Terror.	\$15,636.28
5000-C	Night/Day 75mm Thermal Imager/Color/Ultra Low-Lux camera system	Multiple Sensor Vision System, Thermal Imager - 36° Field of View (Wide angle lens), High Resolution 312x zoom Color Camera, Ultra Low Lux Day/Night Camera (.00015 lux), 360° Continuous Pan Capability, Proportional Joystick, Backlit Controller, Pressurized Housing, Hermetically Sealed camera enclosure ,RS232 or RS485 control, CAT 5 Control Cable - 4000 feet max, Analog camera directional indicator relative to bow featured on display	\$72,078.97
5100-C	Night/Day 75mm Thermal Imager/Color/Ultra Low-Lux camera system	Multiple Sensor Vision System, Thermal Imager - 23° Field of View (Medium angle lens), High Resolution 312x zoom Color Camera, Ultra Low Lux Day/Night Camera (.00015 lux), 360° Continuous Pan Capability, Proportional Joystick, Backlit Controller, Pressurized Housing, Hermetically Sealed camera enclosure ,RS232 or RS485 control, CAT 5 Control Cable - 4000 feet max, Analog camera directional indicator relative to bow featured on display	\$73,066.42
5200-C	Night/Day 75mm Thermal Imager/Color/Ultra Low-Lux camera system	Multiple Sensor Vision System, Thermal Imager - 9° Field of View (Narrow angle lens), High Resolution 312x zoom Color Camera, Ultra Low Lux Day/Night Camera (.00015 lux), 360° Continuous Pan Capability, Proportional Joystick, Backlit Controller, Pressurized Housing, Hermetically Sealed camera enclosure ,RS232 or RS485 control, CAT 5 Control Cable - 4000 feet max, Analog camera directional indicator relative to bow featured on display	\$74,053.87

6000-C	Night/Day 75mm Thermal Imager/Color/Ultra Low-Lux camera system	Multiple Sensor Vision System, Thermal Imager - 36° Field of View (Wide angle lens), High Resolution 312x zoom Color Camera, Ultra Low Lux Day/Night Camera (.00015 lux), Gyro-stabilized Platform, Object Tracking Capability, Internet Viewing and Control, 360° Continuous Pan Capability, Enhance Safety, Security, Navigation, Proportional Joystick, Backlit Controller, Pressurized Housing, Hermetically Sealed camera enclosure, RS232 or RS485 control, CAT 5 Control Cable - 4000 feet max, Analog camera directional indicator relative to bow featured on display	\$133,300.91
6100-C	Night/Day 75mm Thermal Imager/Color/Ultra Low-Lux camera system	Multiple Sensor Vision System, Thermal Imager - 23° Field of View (Medium angle lens), High Resolution 312x zoom Color Camera, Ultra Low Lux Day/Night Camera (.00015 lux), Gyro-stabilized Platform, Object Tracking Capability, Internet Viewing and Control, 360° Continuous Pan Capability, Enhance Safety, Security, Navigation, Proportional Joystick, Backlit Controller, Pressurized Housing, Hermetically Sealed camera enclosure, RS232 or RS485 control, CAT 5 Control Cable - 4000 feet max, Analog camera directional indicator relative to bow featured on display	\$134,288.36
6200-C	Night/Day 75mm Thermal Imager/Color/Ultra Low-Lux camera system	Multiple Sensor Vision System, Thermal Imager - 9° Field of View (Narrow angle lens), High Resolution 312x zoom Color Camera, Ultra Low Lux Day/Night Camera (.00015 lux), Gyro-stabilized Platform, Object Tracking Capability, Internet Viewing and Control, 360° Continuous Pan Capability, Enhance Safety, Security, Navigation, Proportional Joystick, Backlit Controller, Pressurized Housing, Hermetically Sealed camera enclosure, RS232 or RS485 control, CAT 5 Control Cable - 4000 feet max, Analog camera directional indicator relative to bow featured on display	\$135,275.82
5000-R	Night/Day 75mm Thermal Imager/Color/Ultra Low-Lux camera system, w/ruggedized installation and interconnect plate	Multiple Sensor Vision System, Thermal Imager - 36° Field of View (Wide angle lens), High Resolution 312x zoom Color Camera, Ultra Low Lux Day/Night Camera (.00015 lux), 360° Continuous Pan Capability, Proportional Joystick, Backlit Controller, Pressurized Housing, Hermetically Sealed camera enclosure ,RS232 or RS485 control, CAT 5 Control Cable - 4000 feet max, T6 machined aluminum mounting plate with integrated sealed interconnect for quick installation and removal, Analog camera directional indicator relative to bow featured on display	\$81,953.47
5100-R	Night/Day 75mm Thermal Imager/Color/Ultra Low-Lux camera system, w/ruggedized installation and interconnect plate	Multiple Sensor Vision System, Thermal Imager - 23° Field of View (Medium angle lens), High Resolution 312x zoom Color Camera, Ultra Low Lux Day/Night Camera (.00015 lux), 360° Continuous Pan Capability, Proportional Joystick, Backlit Controller, Pressurized Housing, Hermetically Sealed camera enclosure ,RS232 or RS485 control, CAT 5 Control Cable - 4000 feet max, T6 machined aluminum mounting plate with integrated sealed interconnect for quick installation and removal, Analog camera directional indicator relative to bow featured on display	\$82,940.93
5200-R	Night/Day 75mm Thermal Imager/Color/Ultra Low-Lux camera system, w/ruggedized installation and interconnect plate	Multiple Sensor Vision System, Thermal Imager - 9° Field of View (Narrow angle lens), High Resolution 312x zoom Color Camera, Ultra Low Lux Day/Night Camera (.00015 lux), 360° Continuous Pan Capability, Proportional Joystick, Backlit Controller, Pressurized Housing, Hermetically Sealed camera enclosure ,RS232 or RS485 control, CAT 5 Control Cable - 4000 feet max, T6 machined aluminum mounting plate with integrated sealed interconnect for quick installation and removal, Analog camera directional indicator relative to bow featured on display	\$83,928.38

6000-R	Night/Day 75mm Thermal Imager/Color/Ultra Low-Lux camera system, w/ruggedized installation and interconnect plate	Multiple Sensor Vision System, Thermal Imager - 36° Field of View (Wide angle lens), High Resolution 312x zoom Color Camera, Ultra Low Lux Day/Night Camera (.00015 lux), Gyro-stabilized Platform, Object Tracking Capability, Internet Viewing and Control, 360° Continuous Pan Capability, Enhance Safety, Security, Navigation, Proportional Joystick, Backlit Controller, Pressurized Housing, Hermetically Sealed camera enclosure, RS232 or RS485 control, CAT 5 Control Cable - 4000 feet max, T6 machined aluminum mounting plate with integrated sealed interconnect for quick installation and removal. Analog camera directional indicator relative to bow featured on display	\$143,175.42
6100-R	Night/Day 75mm Thermal Imager/Color/Ultra Low-Lux camera system, w/ruggedized installation and interconnect plate	Multiple Sensor Vision System, Thermal Imager - 23° Field of View (Medium angle lens), High Resolution 312x zoom Color Camera, Ultra Low Lux Day/Night Camera (.00015 lux), Gyro-stabilized Platform, Object Tracking Capability, Internet Viewing and Control, 360° Continuous Pan Capability, Enhance Safety, Security, Navigation, Proportional Joystick, Backlit Controller, Pressurized Housing, Hermetically Sealed camera enclosure, RS232 or RS485 control, CAT 5 Control Cable - 4000 feet max, T6 machined aluminum mounting plate with integrated sealed interconnect for quick installation and removal, Analog camera directional indicator relative to bow featured on display	\$144,162.87
6200-R	Night/Day 75mm Thermal Imager/Color/Ultra Low-Lux camera system, w/ruggedized installation and interconnect plate	Multiple Sensor Vision System, Thermal Imager - 9° Field of View (Narrow angle lens), High Resolution 312x zoom Color Camera, Ultra Low Lux Day/Night Camera (.00015 lux), Gyro-stabilized Platform, Object Tracking Capability, Internet Viewing and Control, 360° Continuous Pan Capability, Enhance Safety, Security, Navigation, Proportional Joystick, Backlit Controller, Pressurized Housing, Hermetically Sealed camera enclosure, RS232 or RS485 control, CAT 5 Control Cable - 4000 feet max, T6 machined aluminum mounting plate with integrated sealed interconnect for quick installation and removal, Analog camera directional indicator relative to bow featured on display	\$145,150.32
<u>OPTIONS</u>			
NTSC-CONV	NTSC to PAL video converter		\$1,070.40
DIR-IND	Analog camera directional indicator relative to bow featured on display *option not available on model 1018i		\$1,608.56
LI-CAM	Litght Intensified Camera for 5000 & 6000 series		\$14,658.76
ADD-CONT1018I	Additional Controller for 1018i		\$305.98
ADD-CONT3000	Additional Controller for 3000 series		\$1,759.64
ADD-CONT-5000-6000	Additional Controller for 5000 & 6000 series		\$2,927.84
IP-CONT-3000-5000	IP Control for 3000 & 5000 series		\$4,882.99
POW-COND	Power Conditioner (not required for 5000 & 6000 series)		\$879.82
VID-POW-ISOL	Video and Power Isolator (not required for 5000 & 6000 series)		\$1,221.97
HDBASE-3000	Heavy Duty base for 3000 series		\$6,109.85