



GENERAL SERVICES ADMINISTRATION  
FEDERAL SUPPLY SERVICE  
AUTHORIZED FEDERAL SUPPLY SERVICE PRICE LIST AND CATALOG  
September 1, 2005

FSC, Group 56, Part IV, Section A  
FSC CLASS: 5670

CONTRACT NUMBER: GS-07F-7558C

CONTRACT PERIOD: 4/1/1995 – 3/31/2009

CONTRACTORS NAME:

Total Door® an Openings Company  
40 W. Howard  
Pontiac, MI 48342  
(248) 335-7380

DISTRIBUTOR

Note: all sales are to be through  
Openings Distributors  
\* (See attached list)

BUSINESS SIZE: Small, woman owned

## January 2007 - Current GSA Distributor Listing

- 1 Door Specialties of Alaska, Inc.  
4011 Arctic Blvd., Suite 206  
Anchorage, **AK** 99503  
Phone: 907-563-5550 Fax: 907-562-0351
  
- 2 Norcon Industries, Inc.  
5412 E. Calle Cerrito  
Guadalupe, **AZ** 85082-2202  
Phone: 480-839-2324 Fax: 480-839-2281
  
- 3 Automatic Door Sales & Service, Inc.  
820-822 West Pratt Road  
Little Rock, **AR** 72206  
Phone: 501-888-2443 Fax: 501-888-4914
  
- 4 Select Source Building Products, Inc.  
465 Corporate Drive  
Escondido, **CA** 92029  
Phone: 760-743-8100 Fax: 760-743-8111
  
- 5 Automatic Entrances of Colorado  
2746 W. 13th Avenue  
Denver, **CO** 80204  
Phone: 303-623-5539 Fax: 303-623-6125
  
- 6 Willco Sales & Service  
P.O. Box 320003/38 Duka Avenue  
Fairfield, **CT** 06430  
Phone: 203-366-3895 Fax: 203-366-6344
  
- 7 Brandywine Access Solutions Inc  
1330 East 12th Street  
Wilmington, **DE** 19802  
Phone: 302-622-9900 Fax: 302-652-7426
  
- 8 Acoustical Products Co  
9000 West Sheridan St. Suite #166  
Pembroke Pines, **FL** 33024  
Phone: 954-431-3899 Fax: 954-431-9408

- 10 Automatic Doors, Inc  
111 Railroad Avenue  
Bartlett, **IL** 60103  
Phone: 630-837-4496 Fax: 630-837-4681
  
- 11 Doors, Inc.  
300 SW 6th Street  
Des Moines, **IA** 50309  
Phone: 515-288-8951 Fax: 515-288-6212
  
- 12 Automatic Doors of Kansas, Inc.  
6813 West 45th North  
Wichita, **KS** 67205  
Phone: 316-722-1724 Fax: 316-722-5646
  
- 13 Door Systems Corp  
66 Westminster Street  
Lewiston, **ME** 04240  
Phone: 207-783-7185 Fax: 207-786-3667
  
- 14 Superior Engineered Products  
2227 Hollins Ferry Road  
Baltimore, **MD** 21230  
Phone: 410-625-8989 Fax: 410-625-8838
  
- 15 Allied Products Group Inc.  
90 Reservoir Park Drive  
Rockland, **MA** 02370  
Phone: 781-792-0505 Fax: 781-871-8222
  
- 16 Egress Inc.  
21 Elm  
Pepperell, **MA** 01463-1603  
Phone: 978-433-6575 Fax: 978-433-6056
  
- 17 Northeast Security Solutions  
74 Doty Circle  
W. Springfield, **MA** 01089-1308  
Phone: 413-733-7303 Fax: 413-739-5476

- 18 Crawford Door Sales  
18095 Sherwood Ave  
Detroit, **MI** 48234  
Phone: 313-366-5400 Fax: 313-366-2356
  
- 19 W.L. Hall Company  
14800 Martin Drive  
Eden Prairie, **MN** 55344  
Phone: 952-937-8400 Fax: 952-937-9126
  
- 20 Ravensburg, Incorporated  
1338 Hanley Industrial Court  
St. Louis, **MO** 63144  
Phone: 314-968-4020 Fax: 314-968-2678
  
- 21 Mid-State Door, Inc.  
602 Cambridge Avenue  
Syracuse, **NY** 13208  
Phone: 315-455-5736 Fax: 315-455-8712
  
- 22 McCormick Equipment Co-All Branches  
112 Northeast Drive  
Loveland, OH 45140  
PHONE: 513-677-8888 FAX: 513-677-9322
  
- 23 Best Companies, Inc.  
7301 North Classen Blvd.  
Oklahoma City, **OK** 73116  
Phone: 405-840-1077 Fax: 405-840-5277
  
- 24 AB Specialties, Inc.  
534 Braddock Ave  
Turtle Creek, **PA** 15145  
Phone: 412-825-0220 Fax: 412-825-0387
  
- 25 Mesko Glass & Mirror Company, Inc.  
100 Glendale Road  
Avoca, **PA** 18641  
Phone: 570-457-1700 Fax: 570-457-1714

- 26 William S. Trimble Company  
2200 Atchley SE  
Knoxville, TN 37920  
Phone: 865-573-1911 Fax: 865-573-5239
  
- 27 Coastal ADS  
1834 N. Padre Island Drive  
Corpus Christi, TX 78469  
Phone: 361-289-0864 Fax: 361-289-5540
  
- 28 Trinity Builders Supply  
408 S. Bonham  
Amarillo, TX 79106  
Phone: 806-342-0556 Fax: 806-342-0557
  
- 29 Alder Sales Corporation  
6676 South 400 West  
Murray, UT 84107  
Phone: 801-262-9700 Fax: 801-261-8242
  
- 30 arc one - Newport News  
700 Flagstone Way, Suite D  
Newport News, VA 23608  
Phone: 757-989-0500 Fax: 757-989-5900
  
- 31 Precision Doors & Hardware, Inc.  
6295-80 Edsall Road  
Alexandria, VA 22312  
Phone: 703-461-8282 Fax: 703-461-3431
  
- 32 Yadon Construction Specialties, Inc.  
N 202 Napa - Box 2672 TA  
Spokane, WA 99220  
Phone 509-535-0301 Fax: 509-534-1787



INFORMATION FOR ORDERING

- 1a. ITEM NUMBER SIN 563 23  
LOWEST PRICE FOR ONE UNIT
- 1b. Single Hollow Metal Fire Rated Door Sys F. O. B. DESTINATION: \$ 575.04 net.
- 1c. Pair Hollow Metal Fire Rated Door Sys F. O. B. DESTINATION: \$1,303.22 net.
- 1d. Double Egress Hollow Metal Fire Door Sys F. O. B. DESTINATION: \$1,402.76 net.
- 1e. Single Wood Core Fire Rated Door Sys F. O. B. DESTINATION: \$ 558.96 net.
- 1f. Pair Wood Core Fire Rated Door Sys F. O. B. DESTINATION: \$1,271.06 net.
- 1g. Double Egress Wood Core Fire Door Sys F. O. B. DESTINATION: \$1,370.60 net.
- 1h. Single Metal Low Range Blast Door (VLR) F. O. B. DESTINATION: \$1,059.73 net.
- 2. MAXIMUM ORDER LIMITATION \$75,000.00 net
- 3. MINIMUM ORDER: \$ 50.00
- 4. GEOGRAPHIC COVERAGE: 48 Contiguous States in addition to Washington, DC, and Alaska, Hawaii, Puerto Rico, and all other US Territories.
- 5. POINT OF PRODUCTION: Pontiac, MI
- 6. DISCOUNT FROM LIST PRICES:
  - 24% on orders under \$ 5,000 list
  - 28% on orders from \$ 5,000 to \$ 9,999 list
  - 32% on orders from \$10,000 to \$ 24,999 list
  - 35% on orders from \$25,000 to \$ 49,999 list
  - 39% on orders from \$50,000 to \$75,000 list
- 7. QUANTITY DISCOUNTS: As shown above
- 8. PROMPT PAYMENT TERMS Net 30 Days
- 9a. GOVERNMENT COMMERCIAL CREDIT CARD:
- 9b. DISCOUNT FOR PAYMENT BY GOVERNMENT COMMERCIAL CREDIT CARD: N/A
- 10. FOREIGN ITEMS: None
- 11. TIME OF DELIVERY 45 days ARO
- 12. F. O. B. POINT: Destination – Freight allowed for continental US; Origin-Prepay/Add for Alaska, Hawaii, Puerto Rico, and all US Territories.
- \*13. ORDERING ADDRESS: See Attached Distributor List
- \*14. PAYMENT ADDRESS: See Attached Distributor List
- 15. WARRANTY PROVISIONS:
 

All material fabricated by Total Door® an Openings Company is guaranteed as to material and workmanship (including freight charges for shipping defective items back to manufacturer) for a period of two (2) years from the date of completed installation, provided that defects are not the result of abuse, unreasonable usage or other causes beyond the sellers control. Total Door® an Openings Company's liability shall not exceed the cost of material furnished. There are no warranties of merchantability for fitness of such goods or services for any particular purpose, except that all goods shall conform to their description, subject to commercial tolerances and variations.
- 16. EXPORT PACKING CHANGES: N/A
- 17. TERMS AND CONDITIONS OF RENTAL MAINTENANCE AND REPAIR: N/A
- 18. TERMS AND CONDITIONS OF INSTALLATION: Available from Distributor
- 19. TERMS AND CONDITIONS OF REPAIR PARTS: Available from Distributor
- 20. LIST OF SERVICE AND DISTRIBUTION POINTS: See Distributor List
- 21. LIST OF PARTICIPATING DISTRIBUTORS See Distributor List
- 22. PREVENTATIVE MAINTENANCE: N/A



PRICES TO THE GSA

AND OTHER PARTICIPATING FEDERAL SUPPLY SERVICES

September 1, 2005

FSC Group 56, Part IV, Section A:

UNDISCOUNTED PRICE: \$ 751.00 / DOOR

ITEM DESCRIPTION: A door & hardware system with a 20-gauge steel door body, 3' 0" x 7' 0", 1-1/2 hour (B) label, with positive pressure and smoke & draft, complete with continuous lock and levers, in any hand, function and finish listed below.

This system includes the following factory installed components:

Continuous hinges

Continuous lock mechanism

Steel door body, electro galvanized & prime painted

1-1/2 hour fire label

All door and hardware components are equal to or superior to  
ANSI A156.1, grade 1 hinges  
ANSI A156.13, grade 1 lock mechanisms  
ANSI A250.4, all grades, steel doors  
ANSI A156.3, grade 1 panics

PRODUCT DETAILS AND NOTES:

Item # 563 23 is a system which meets all performance characteristics of a Class I product. It will fit any existing 3' 0" x 7' 0" frame, whether wood, aluminum or steel, single rabbeted, double rabbeted or case with or without reinforcements, hinge or strike cutouts. Door can swing right or left on any frame. The door is automatically reinforced for any surface closer or holder. It is built with a polystyrene core for strength and insulating value.

Doors are shipped with hinges and locks already installed. The hinge is a continuous element 7' 0" high with no projecting knuckles. The locking channel is also 7' 0" high and engages the jamb for its full height offering greater security against unauthorized entry especially kicking, "loiding", and jamb spreading.

Any standard mortise cylinder with a standard cam will operate the locking mechanism. Levers are part of the package.

FINISHES AVAILABLE:

625 = Mirror Chrome  
630 = Satin Stainless Steel  
605 = Mirror Brass  
606 = Bright Brass  
611 = Bright Bronze  
612 = Satin Bronze

FUNCTIONS AVAILABLE:

Federal Function Nos.  
F01, F02, F04, F05,  
F07, F09, F13, F14,  
F17, F18

HANDS AVAILABLE:

Right hand = R  
Left hand = L  
Right hand reverse = RR  
Left hand reverse = LR



September 1, 2005

Prices to the GSA and other Participating Supply Services

FSC Group 56, Part IV, Section A:

Item: Single Hollow Metal Fire Rated Door Sys

List Price: \$751.00

Discounted Price: \$575.04

Item Description:

A complete, integrated door & hardware system with 20-gauge steel door body, 3'0" x 7'0", complete with continuous lock and levers, in any hand, function & finish listed. Factory installed continuous hinges & lock mechanism. Steel door body, electro galvanized & prime painted. 1-1/2 hour fire label - positive pressure – with smoke and draft, (other labels and sizes available, including 3 hour, 250 degree temperature rise). Components meet or exceed ANSI A156.1, grade 1 hinges. ANSI A156.13, grade 1 lock mechanisms. ANSI A250.4, all grades, steel doors. ANSI A156.3, grade 1 panics.

Product Details and Notes:

Product Details and Notes: Item #563 23 is a system, which meets all performance characteristics of a Class I product. It will fit any existing 3'0" x 7'0" frame, whether wood, aluminum or steel, single rabbet, double rabbet or cased with or without reinforcements, hinge or strike cutouts. Door can swing right or left on any frame - specify which. The door is automatically reinforced for any surface closer or holder. It is built with a polystyrene core for strength and insulating value. Doors are shipped with hinges and locks already installed. Any standard mortise cylinder with a standard cam will operate the locking mechanism. Standard mortise and cam cylinders must be provided by the owner to match existing master key system. The hinge is a continuous element 7'0" high with no projecting knuckles. The locking channel is also 7'0" high and engages the jamb for its full height offering greater security against unauthorized entry, especially kicking, "loiding" and jamb spreading. Levers are part of the package. A full range of products and sizes are available as part of the package: i.e. panic devices, closers, frames, kick plates, lite kits, glazing.

Finishes: 625-Mirror Chrome, 630-Satin Stainless Steel, 605-Mirror Brass, 606-Bright Brass,  
611-Bright Bronze, 612-Satin Bronze.

Functions: Federal Function Nos.: F01, F02, F04, F05, F07, F09, F13, F14, F17, F18.

Hands: Right Hand-R, Left Hand-L, Right Hand Reverse-RR, Left Hand Reverse-LR.



September 1, 2005

Prices to the GSA and other Participating Supply Services

FSC Group 56, Part IV, Section A:

Item: Pair Hollow Metal Fire Rated Door Sys

List Price: \$1,702.00

Discounted Price: \$1,303.22

Item Description:

A complete, integrated door & hardware system with 20-gauge steel door body, 6'0" x 7'0", complete with continuous lock and levers, in any hand, function & finish listed. Factory installed continuous hinges & lock mechanism. Steel door body, electro galvanized & prime painted. 1-1/2 hour fire label, - positive pressure – with smoke and draft (other labels and sizes available, including 3 hour, 250 degree temperature rise). Components meet or exceed ANSI A156.1, grade 1 hinges. ANSI A156.13, grade 1 lock mechanisms. ANSI A250.4, all grades, steel doors. ANSI A156.3, grade 1 panics. Hardware supplied eliminates need for flush bolts, astragals, coordinators and floor strikes, available with panic exit devices.

Product Details and Notes:

Product Details and Notes: Item #563 23 is a system, which meets all performance characteristics of a Class I product. It will fit any existing 6'0" x 7'0" frame, whether wood, aluminum or steel, single rabbet, double rabbet or cased with or without reinforcements, hinge or strike cutouts. Door can swing right or left on any frame - specify which. The door is automatically reinforced for any surface closer or holder. It is built with a polystyrene core for strength and insulating value. Doors are shipped with hinges and locks already installed. Any standard mortise cylinder with a standard cam will operate the locking mechanism. Standard mortise and cam cylinders must be provided by the owner to match existing master key system. The hinge is a continuous element 7'0" high with no projecting knuckles. The locking channel is also 7'0" high and engages the opposing locking channel for its full height offering greater security against unauthorized entry, especially kicking, "loiding" and jamb spreading. Levers are part of the package. A full range of products and sizes are available as part of the package: i.e. panic devices, closers, frames, kick plates, lite kits, glazing. Door system eliminates need for flush bolts, astragals, coordinators and floor strikes.

Finishes: 625-Mirror Chrome, 630-Satin Stainless Steel, 605-Mirror Brass, 606-Bright Brass,  
611-Bright Bronze, 612-Satin Bronze.

Functions: Federal Function Nos.: F01, F02, F04, F05, F07, F09, F13, F14, F17, F18.

Hands: Right Hand-R, Left Hand-L, Right Hand Reverse-RR, Left Hand Reverse-LR.



September 1, 2005

Prices to the GSA and other Participating Supply Services

FSC Group 56, Part IV, Section A:

Item: Double Egress Hollow Metal Fire Door Sys

List Price: \$1,832.00

Discounted Price: \$1,402.76

Item Description:

A complete, integrated door & hardware system with 20-gauge steel door body, 6'0" x 7'0", complete with continuous lock and levers, in any hand, function & finish listed. Factory installed continuous hinges & lock mechanism. Steel door body, electro galvanized & prime painted. 1-1/2 hour fire label - positive pressure - with smoke and draft, (other labels and sizes available, including 3 hour, 250 degree temperature rise). Components meet or exceed ANSI A156.1, grade 1 hinges. ANSI A156.13, grade 1 lock mechanisms. ANSI A250.4, all grades, steel doors. ANSI A156.3, grade 1 panics. Hardware supplied eliminates need for flush bolts, astragals, and floor strikes, available with panic exit devices.

Product Details and Notes:

Product Details and Notes: Item #563 23 is a system, which meets all performance characteristics of a Class I product. It will fit any existing 6'0" x 7'0" double egress frame, whether wood, aluminum or steel, single rabbet, double rabbet or cased with or without reinforcements, hinge or strike cutouts. Door can swing right or left on any frame - specify which. The door is automatically reinforced for any surface closer or holder. It is built with a polystyrene core for strength and insulating value. Doors are shipped with hinges and locks already installed. Any standard mortise cylinder with a standard cam will operate the locking mechanism. Standard mortise and cam cylinders must be provided by the owner to match existing master key system. The hinge is a continuous element 7'0" high with no projecting knuckles. The locking channel is also 7'0" high and engages the opposing locking channel for its full height offering greater security against unauthorized entry especially kicking, "loiding" and jamb spreading. Levers are part of the package. A full range of products and sizes are available as part of the package: i.e. panic devices, closers, frames, kick plates, lite kits, glazing. Door system eliminates need for flush bolts, astragals and floor strikes. Can be retrofitted to a standard rabbet pair frame by order sizes to 5'-10/3/4" x 6'-11/3/8".

Finishes: 625-Mirror Chrome, 630-Satin Stainless Steel, 605-Mirror Brass, 606-Bright Brass,  
611-Bright Bronze, 612-Satin Bronze.

Functions: Federal Function Nos.: F01, F02, F04, F05, F07, F09, F13, F14, F17, F18.

Hands: Right Hand-R, Left Hand-L, Right Hand Reverse-RR, Left Hand Reverse-LR.



September 1, 2005

Prices to the GSA and other Participating Supply Services

FSC Group 56, Part IV, Section A:

Item: Single Wood Core Fire Rated Door Sys

List Price: \$730.00

Discounted Price: \$558.96

Item Description:

A complete, integrated door & hardware system with flat cut red oak, clear finish, solid wood core door body, 3'0" x 7'0", 20 minute fire label - positive pressure - with smoke and draft, (or non label) complete with continuous lock and levers, in any hand, function & finish listed. Factory installed continuous hinges & lock mechanism. Components meet or exceed ANSI A156.1, grade 1 hinges. ANSI A156.13, grade 1 lock mechanisms. ANSI A250.4, all grades, ANSI A156.3, grade 1 panics.

Product Details and Notes:

Product Details and Notes: Item #563 23 is a system, which meets all performance characteristics of a Class I product. It will fit any existing 3'0" x 7'0" frame, whether wood, aluminum or steel, single rabbet, double rabbet or cased with or without reinforcements, hinge or strike cutouts. Door can swing right or left on any frame - specify which. The door is automatically reinforced for any surface closer or holder. It is built with a wood core for strength and insulating value. Doors are shipped with hinges and locks already installed. Any standard mortise cylinder with a standard cam will operate the locking mechanism. Standard mortise and cam cylinders must be provided by the owner to match existing master key system. The hinge is a continuous element 7'0" high with no projecting knuckles. The locking channel is also 7'0" high and engages the jamb for its full height offering greater security against unauthorized entry especially kicking, "loiding" and jamb spreading. Levers are part of the package. A full range of products and sizes are available as part of the package: i.e. panic devices, closers, frames, kick plates, lite kits, glazing.

Finishes: 625-Mirror Chrome, 630-Satin Stainless Steel, 605-Mirror Brass, 606-Bright Brass,  
611-Bright Bronze, 612-Satin Bronze.

Functions: Federal Function Nos.: F01, F02, F04, F05, F07, F09, F13, F14, F17, F18.

Hands: Right Hand-R, Left Hand-L, Right Hand Reverse-RR, Left Hand Reverse-LR.



September 1, 2005

Prices to the GSA and other Participating Supply Services

FSC Group 56, Part IV, Section A:

Item: Pair Wood Core Fire Rated Door Sys

List Price: \$1,660.00

Discounted Price: \$1,271.06

Item Description:

A complete, integrated door & hardware system with flat cut red oak, clear finish, solid wood core door body, 6'0" x 7'0", 20 minute fire label - positive pressure - with smoke and draft, (or non label) complete with continuous lock and levers, in any hand, function & finish listed. Factory installed continuous hinges & lock mechanism. Components meet or exceed ANSI A156.1, grade 1 hinges. ANSI A156.13, grade 1 lock mechanisms. ANSI A250.4, all grades, ANSI A156.3, grade 1 panics. Hardware supplied eliminates need for flush bolts, astragals and floor strikes, available with panic exit devices.

Product Details and Notes:

Product Details and Notes: Item #563 23 is a system, which meets all performance characteristics of a Class I product. It will fit any existing 6'0" x 7'0" frame, whether wood, aluminum or steel, single rabbet, double rabbet or cased with or without reinforcements, hinge or strike cutouts. Door can swing right or left on any frame - specify which. The door is automatically reinforced for any surface closer or holder. It is built with a wood core for strength and insulating value. Doors are shipped with hinges and locks already installed. Any standard mortise cylinder with a standard cam will operate the locking mechanism. Standard mortise and cam cylinders must be provided by the owner to match existing master key system. The hinge is a continuous element 7'0" high with no projecting knuckles. The locking channel is also 7'0" high and engages the opposing locking channel for its full height offering greater security against unauthorized entry, especially kicking, "loiding" and jamb spreading. Levers are part of the package. A full range of products and sizes are available as part of the package: i.e. panic devices, closers, frames, kick plates, lite kits, glazing. Door system eliminates need for flush bolts, astragals, coordinators and floor strikes.

Finishes: 625-Mirror Chrome, 630-Satin Stainless Steel, 605-Mirror Brass, 606-Bright Brass,  
611-Bright Bronze, 612-Satin Bronze.

Functions: Federal Function Nos.: F01, F02, F04, F05, F07, F09, F13, F14, F17, F18.

Hands: Right Hand-R, Left Hand-L, Right Hand Reverse-RR, Left Hand Reverse-LR.



September 1, 2005

Prices to the GSA and other Participating Supply Services

FSC Group 56, Part IV, Section A:

Item: Double Egress Wood Core Fire Door Sys

List Price: \$1,790.00

Discounted Price: \$1,370.60

Item Description:

A complete, integrated door & hardware system with flat cut red oak, clear finish, solid wood core door body, 6'0" x 7'0", 20 minute fire label, - positive pressure - with smoke and draft, (or non label) complete with continuous lock and levers, in any hand, function & finish listed. Factory installed continuous hinges & lock mechanism. Components meet or exceed ANSI A156.1, grade 1 hinges. ANSI A156.13, grade 1 lock mechanisms. ANSI A250.4, all grades, ANSI A156.3, grade 1 panics hardware supplied eliminates need for flush bolts, astragals, coordinators and floor strikes, available with panic exit devices.

Product Details and Notes:

Product Details and Notes: Item #563 23 is a system, which meets all performance characteristics of a Class I product. It will fit any existing 6'0" x 7'0" double egress frame, whether wood, aluminum or steel, single rabbet, double rabbet or cased with or without reinforcements, hinge or strike cutouts. Door can swing right or left on any frame - specify which. The door is automatically reinforced for any surface closer or holder. It is built with a wood core for strength and insulating value. Doors are shipped with hinges and locks already installed. Any standard mortise cylinder with a standard cam will operate the locking mechanism. Standard mortise and cam cylinders must be provided by the owner to match existing master key system. The hinge is a continuous element 7'0" high with no projecting knuckles. The locking channel is also 7'0" high and engages the opposing locking channel for its full height offering greater security against unauthorized entry especially kicking, "loiding" and jamb spreading. Levers are part of the package. A full range of products and sizes are available as part of the package: i.e. panic devices, closers, frames, kick plates, lite kits, glazing. Door system eliminates need for flush bolts, astragals and floor strikes. Can be retrofitted to a standard rabbet pair frame by order sizes to 5'-10/3/4" x 6'-11/3/8".

Finishes: 625-Mirror Chrome, 630-Satin Stainless Steel, 605-Mirror Brass, 606-Bright Brass,  
611-Bright Bronze, 612-Satin Bronze.

Functions: Federal Function Nos.: F01, F02, F04, F05, F07, F09, F13, F14, F17, F18.

Hands: Right Hand-R, Left Hand-L, Right Hand Reverse-RR, Left Hand Reverse-LR.



September 1, 2005

Prices to the GSA and other Participating Supply Services

FSC Group 56, Part IV, Section A:

Item: Single Metal Low Range Blast Door (VLR)

List Price: \$1,384.00

Discounted Price: \$1,059.73

Item Description:

A complete low range blast door (VLR) 144# / sq. ft. integrated door & hardware system with 18-gauge steel door body for superior security protection. 3'0" x 7'0", complete with continuous lock and levers, in any hand, function & finish listed. Factory installed continuous hinges & lock mechanism. Steel door body, electro galvanized & prime painted. 1-1/2 hour fire label, - positive pressure - with smoke and draft (other labels and sizes available, including 3 hour, 250 degree temperature rise). Components meet or exceed ANSI A156.1, grade 1 hinges. ANSI A156.13, grade 1 lock mechanisms. ANSI A250.4, all grades, steel doors. ANSI A156.3, grade 1 panics.

Product Details and Notes:

Product Details and Notes: Item #563 23 is a system, which meets all performance characteristics of a Class I product. The VLR blast door will fit any existing & structurally sound 3'0" x 7'0" frame, whether wood, aluminum or steel, single rabbet, double rabbet or cased with or without reinforcements, hinge or strike cutouts. Door can swing right or left on any frame - specify which. The door is automatically reinforced for any surface closer or holder. It is built with a polystyrene core for strength and insulating value. Doors are shipped with hinges and locks already installed. Any standard mortise cylinder with a standard cam will operate the locking mechanism. Standard mortise and cam cylinders must be provided by the owner to match existing master key system. The hinge is a continuous element 7'0" high with no projecting knuckles. The locking channel is also 7'0" high and engages the jamb for its full height providing blast resistance and offering greater security against unauthorized entry, especially kicking, "loiding" and jamb spreading. Levers are part of the package. A full range of products and sizes are available as part of the package: i.e. panic devices, closers, frames, kick plates, lite kits, glazing.

Finishes: 625-Mirror Chrome, 630-Satin Stainless Steel, 605-Mirror Brass, 606-Bright Brass,  
611-Bright Bronze, 612-Satin Bronze.

Functions: Federal Function Nos.: F01, F02, F04, F05, F07, F09, F13, F14, F17, F18.

Hands: Right Hand-R, Left Hand-L, Right Hand Reverse-RR, Left Hand Reverse-LR.