



GENERAL

TRUCK BODY MFG. COMPANY



7110 Jensen Drive ★ Houston, Texas 77093
phone (713) 692-5177 fax (713)692-0700
www.generalbody.com

GENERAL SERVICES ADMINISTRATION
Federal Supply Service
Authorized Federal Supply Schedule Price List

On-line access to contract ordering information, terms and conditions, up-to-date pricing, and the option to create an electronic delivery order are available through GSA Advantage!, a menu-driven database system.
The INTERNET address GSA *Advantage!* is: GSAAdvantage.gov.

VEHICULAR MULTIPLE AWARD SCHEDULE (VMAS)
FSC Group 23V

Contract Number
GS-30F-0006T

For more information on ordering from Federal Supply Schedules click on the FSS Schedules button at fss.gsa.gov

Period Covered by Contract
2006-2011

General Services Administration

Business Size: Small

Business Status: Woman-Owned HUBZONE

DUNS Number: 05-514-4414

Updated: December 21, 2008

CUSTOMER INFORMATION

- 1a. Table of awarded special item number(s) with appropriate cross-reference to item descriptions and awarded price(s).

618-01 Fire Fighting Vehicles and Accessories
272-105 New Technologies

- 1b. Identification of the lowest priced model number and lowest unit price for that model for each special item number awarded in the contract. This price is the Government price based on a unit of one, exclusive of any quantity/dollar volume, prompt payment, or any other concession affecting price. Those contracts that have unit prices based on the geographic location of the customer, should show the range of the lowest price, and cite the areas to which the prices apply.

SIN: 618-01

MCU1200 = \$141,557.62 (Chassis - Ford F550 WB 189 in, CA 108 in, GVWR 17,950 lb & PL 10,450 lb, Engine Triton 6.8L V10, Transmission Ford Torque Shift™ 5-Speed Automatic)

MCU2000 = \$220,200.75 (Chassis - Ford F650 WB 242 in, CA 168 in, GVWR 29,000 lb & PL 20,350 lb, Engine Cummins 5.9L 1-6 OHV w/ Diesel Injection @ 200 hp, Transmission Allison 2500 5-Speed Automatic)

MCU2600 = \$277,872.37 (Chassis - Ford F750 WB 260 in, After Cab (CA) 186 in, GVWR 33,000 lb & Payload (PL) 22,740 lb, Engine CAT 7.2L 1-6 OHV w/ Diesel Injection @ 210 hp, Transmission Allison 3000 6-Speed Automatic)

MCU4000 = \$408,944.25 (Chassis - Peterbilt 379 WB 255 in, Engine Diesel Cummins @ 260 hp, Transmission Manual min 9-speed, Air suspension, Tandem axle.)

PEV3000 = (Chassis – Freightliner Columbia CL112) w/ 30' body

SIN: 272-105

EGU1600 = \$173,014.87 (Chassis - Ford F550 WB 201 in, CA 120 in, GVWR 17,950 lb & PL 12,260 lb, Engine Triton 6.8L V10, Transmission Ford Torque Shift™ 5-Speed Automatic)

- 1c. If the Contractor is proposing hourly rates, a description of all corresponding commercial job titles, experience, functional responsibility and education for those types of employees or subcontractors who will perform services shall be provided. If hourly rates are not applicable, indicate "Not applicable" for this item.
Not Applicable

2. Maximum order.
618-01: 25 Units
272-105: 25 Units
3. Minimum order
618-01: \$100.00
272-105: \$100.00

4. Geographic coverage (delivery area)
CONUS
5. Point(s) of production (city, county, and State or foreign country)
Houston, Harris County, Texas
6. Statement of net price (base models excluding options).
Net Price with IFF

Model:	= Net Price
MCU1200	\$141,557.62
MCU2000	\$220,200.75
MCU2600	\$277,872.37
MCU4000	\$408,944.25
EGU1600	\$173,014.87
PEV3000	\$493,224.00

Net Price without IFF (base models excluding options)

Model:	= Net Price
MCU1200	\$140,616.00
MCU2000	\$218,736.00
MCU2600	\$276,024.00
MCU4000	\$406,224.00
EGU1600	\$171,864.00
PEV3000	\$489,552.00

Note: All Trucks Offered Meet Applicable EPA Standards

7. Quantity discounts.
Included in Net Price
8. Prompt payment terms.
0% Net 30
- 9a. Notification that Government purchase cards are accepted at or below the micro-purchase threshold.
General Body Manufacturing Co., Inc. will accept Government purchase cards for orders below the micro-purchase threshold.
- 9b. Notification whether Government purchase cards are accepted or not accepted above the micro-purchase threshold.
General Body Manufacturing Co., Inc. will accept Government purchase cards for above the micro-purchase threshold.

10. Foreign items (list items by country of origin).
Not Applicable
- 11a. Time of delivery. (Contractor insert number of days.)
MCU1200 = 90 days
MCU2000 = 90 days
MCU2600 = 120 days
MCU4000 = 150 days
EGU1600 = 90 days
- 11b. Expedited Delivery.
As Negotiated Between Contractor and Ordering Agency
- 11c. Overnight and 2-day delivery.
Not Available
- 11d. Urgent Requirements.
As Negotiated
12. F.O.B. point(s).
Origin for 618-1 and Destination for 272-105
13. Ordering address(es).
Bryant S. Banes, Director Government Operations
General Body Manufacturing Co., Inc. d/b/a General Truck Body
6901 Avenue V
Houston, Harris County, Texas 77011
[**bbanes@neelhooper.com**](mailto:bbanes@neelhooper.com)
- 13b. Ordering procedures: For supplies and services, the ordering procedures, information on Blanket Purchase Agreements (BPA's) are found in Federal Acquisition Regulation (FAR) 8.405-3.
14. Payment address(es).
General Body Manufacturing Co., Inc. d/b/a General Truck Body
6901 Avenue V
Houston, Harris County, Texas 77011
15. Warranty provision.
General Body Manufacturing Co., Inc. d/b/a General Truck Body warrants that the items delivered hereunder are merchantable and fit for use for the particular purpose described in this contract
16. Export packing charges, if applicable.
Not Applicable

17. Terms and conditions of Government purchase card acceptance (any thresholds above the micro-purchase level).
Government Purchase Cards will be accepted for all orders.
18. Terms and conditions of rental, maintenance, and repair (if applicable).
Not Applicable
19. Terms and conditions of installation (if applicable).
Not Applicable
20. Terms and conditions of repair parts indicating date of parts price lists and any discounts from list prices (if applicable).
Not Applicable
- 20a. Terms and conditions for any other services (if applicable).
Not Applicable
21. List of service and distribution points (if applicable).
Not Applicable
22. List of participating dealers (if applicable).
Not Applicable
23. Preventive maintenance (if applicable).
Not Applicable
- 24a. Special attributes such as environmental attributes (e.g., recycled content, energy efficiency, and/or reduced pollutants).
Not Applicable
- 24b. If applicable, indicate that Section 508 compliance information is available on Electronic and Information Technology (EIT) supplies and services and show where full details can be found (e.g. contractor's website or other location.) The EIT standards can be found at: www.Section508.gov/.
Not Applicable
25. Data Universal Number System (DUNS) number.
05-514-4414
26. Notification regarding registration in Central Contractor Registration (CCR) database.
Contractor is registered with the Central Contractor Registration Database
Cage Code: 8H011

MCU 1200

DETAIL SPECIFICATIONS

MOBILE COMMAND UNIT 12 ft
GTB# MCU1200

- Up to 17,500 GVWR
- 5.5 Kw Generator with shore power access
- Welded Aluminum frame construction
- 2-3 door cabinets
- 1- Large storage cabinet with rod and hook
- Large First Aid Kit and Fire Extinguisher ABC 5 lb
- Overhead storage with Dry Erase board on door at each station
- 2 Work station w/ Motorola radio and Telecom access
- Sink area w/ faucet and pump
- Water Tank 12 gal, 20 gal waste tank under sink
- Internal 120V lighting and 12V lighting to specification
- All Electrical to required specification and NEC code
- Flip Down Table w/ large Dry Erase on wall
- Lower cabinet/drawer storage
- External storage 35 cu ft for extension cords and misc.
- External storage for aux. batteries
- External lighting to specification and NEC code
- 1 Rooftop A/C at 13500BTU/hr each
- Ford 550 Chassis (detail specs enclosed) - All options can be discussed for variation of vehicle layout.

Scope of any unit will be total dictated by contract specification and service schedule. General Truck Body Mfg is able to configure as well as assist with design requirements to best fit the needs of the customer.

2008 Ford F-550 Chassis
4x2 SD Regular Cab 189 in. WB DRW XL T

Major Standard Equipment

- . Triton 6.8L V-10 SOHC w/SMPI 362hp
- . 4-wheel ABS
- . Firm suspension
- . AM/FM stereo single CD
- . Variable intermittent wipers
- . Dual front airbags w/passenger cancel
- . Reclining front 40-20-40 split-bench seats
- . 17,950lbs. GVWR
- . 13,660lbs. rear GAWR
- . 13,660lbs. rear axle capacity
- . 13,660lbs. rear spring rating
- . 36,000 frame yield strength (psi)
- . 108.0" cab to axle
- . 273.6" overall length
- . 5 speed automatic trans w/OD
- . LT225/70SR19.5F BSW AS tires
- . Air conditioning
- . Dual power remote heated mirrors
- . 19.5" x 6" wheels
- . Tachometer
- . Cloth seats
- . 6,500lbs. front GAWR
- . 7,000lbs. front axle capacity
- . 6,500lbs. front spring rating
- . 17.20cu.in. frame section modulus
- . 189.0" wheelbase
- . 47.5" axle to end of frame
- . Left mounted muffler, left mounted tailpipe

Selected Optional Equipment

- Order Code 667 A
- Engine: 6.0L V8 Power Stroke Diesel
- Transmission: TorqShift 5-Speed Auto w/OD (Diesel)
- Cloth Luxury Captain's Chairs
- Dual Alternators
- TowCommand Integrated Trailer Brake Controller TowCommand System
- Ambulance Prep Package
- Carpet Delete
- Passenger Air Bag Delete
- 50 State Emissions System

MCU 1600

DETAIL SPECIFICATIONS

MOBILE COMMAND UNIT 16 ft
GTB# MCU1600

- Up to 19,000 GVWR
- 5.5 Kw Generator * with shore power access
- Welded Aluminum frame construction
- 2-3 door cabinets
- 1- Large storage cabinet with rod and hook
- Large First Aid Kit and Fire Extinguisher ABC 5 lb
- Overhead storage with Dry Erase board on door at each station
- 3-4 Work station w/ Motorola radio and Telecom access
- Sink area w/ faucet and pump
- Water Tank 12 gal, 20 gal waste tank under sink
- Internal 120V lighting and 12V lighting to specification
- All Electrical to required specification and NEC code
- Flip Down Table w/ large Dry Erase on wall
- Lower cabinet/drawer storage
- External storage 35 cu ft for extension cords and misc.
- External storage for aux. batteries
- External lighting to specification and NEC code
- 2 Rooftop A/C at 13500BTU/hr each
- Ford 550 Chassis (detail specs enclosed) - All options can be discussed for variation of vehicle layout.

Scope of any unit will be total dictated by contract specification and service schedule. General Truck Body Mfg is able to configure as well as assist with design requirements to best fit the needs of the customer.

* Optional 7.5 KW generator \$1000.00 for diesel version.

2008 Ford F-550 Chassis

4x2 SD Regular Cab 201 in. WB DRW XL T

Major Standard Equipment

- . Triton 6.8L V-10 SOHC w/SMP1362hp
- . 4-wheel ASS
- . Firm suspension
- . AM/FM stereo single CD
- . Variable intermittent wipers
- . Dual front airbags w/passenger cancel
- . Reclining front 40-20-40 split-bench seats
- . 17,950 lbs. GVWR
- . 13,660 lbs. rear GAWR
- . 13,660 lbs. rear axle capacity
- . 13,660 lbs. rear spring rating
- . 36,000 frame yield strength (psi)
- . 120.0" cab to axle
- . 285.6" overall length
- . 5 speed automatic trans w/OD
- . L T225/70SR 19.5F SSW AS tires
- . Air conditioning
- . Dual power remote heated mirrors
- . 19.5" x 6" wheels
- . Tachometer
- . Cloth seats
- . 6,000lbs. front GAWR
- . 7,000lbs. front axle capacity
- . 6,000lbs. front spring rating
- . 17.20cu.in. frame section modulus
- . 201.0" wheelbase
- . 47.5" axle to end of frame
- . Left mounted muffler, left mounted tailpipe

Selected Optional Equipment

Order Code 667 A
Engine: 6.0L V8 Power Stroke Diesel Transmission: TorqShift 5-Speed Auto w/OD (Diesel)
GVWR: 19,000 lbs
Cloth Luxury Captain's Chairs
Payload Upgrade Package
Ambulance Prep Package Not Included
50 State Emissions System

MCU 2000

DETAIL SPECIFICATIONS

MOBILE COMMAND UNIT 20 ft
GTB# MCU2000

- Up to 29,000 GVWR
- 10 Kw Generator * with shore power access
- Welded Aluminum frame construction
- 2-3 door cabinets
- 1- Large storage cabinet with rod and hook
- Large First Aid Kit and Fire Extinguisher ABC 5 lb
- Overhead storage with Dry Erase board on door at each station
- Work station w/ Motorola radio and Telecom access
- Sink area w/ faucet and pump
- Water Tank 12 gal, 20 gal waste tank under sink
- Internal 120V lighting and 12V lighting to specification
- All Electrical to required specification and NEC code
- Flip Down Table w/ large Dry Erase on wall
- Lower cabinet/drawer storage
- External storage 35 cu ft for extension cords and misc.
- External storage for aux. batteries
- External lighting to specification and NEC code
- 2 Rooftop A/C at 15000BTU/hr each
- Ford 650 Chassis (detail specs enclosed) - All options can be discussed for variation of vehicle layout.

Scope of any unit will be total dictated by contract specification and service schedule. General Truck Body Mfg is able to configure as well as assist with design requirements to best fit the needs of the customer.

* Optional 15 KW generator \$1250.00 for diesel version.

2008 Ford F-650

Regular Cab XLT

Major Standard Equipment

- . Cummins 5.9L 1-6 OHV w/diesel injection 200hp
- . 4-wheel ABS, hydraulic disc brakes
- . M+S rear tires
- . Tinted glass
- . Variable intermittent wipers
- . Tachometer
- . Cloth seats
- . 130 Amp alternator
- . 45gal. right front fuel tank
- . 8,500lbs. front axle capacity
- . 8,500lbs. front spring rating
- . 12.64cu.in. frame section modulus
- . 158.0" wheelbase
- . 39.0" axle to end of frame
- . Heated fuel/water separator
- . Right mounted horizontal muffler, right mounted horizontal tailpipe
- . 5 speed automatic trans w/OD
- . 10.0R22.5 highway tires
- . Air conditioning
- . AM/FM stereo single CD
- . 22.5" x 7.5" white steel disc wheels
- . High back 40-20-40 bench seats
- . 1,250 Amp dual batteries
- . Side steps
- . Multi-leaf rear springs
- . Transmission PTO provision
- . 17,500 lbs. rear axle capacity
- . 18,500 lbs. rear spring rating
- . 50,000 frame yield strength (psi)
- . 84.0" cab to axle
- . 236.0" overall length
- . Dual electric horn

Selected Optional Equipment

- 242" Wheelbase/168" CA/100" AF/381" OAL
- I-Beam Type - 10,000 lb. Cap. 1-100SG
- Taper-Leaf Springs, Parabolic - 10,000 lb. Cap
- 19,000 lb. Single-Speed - Spicer 19060S
- Air Suspension - 20,000 lb. Cap
- Air Brakes - Straight Truck w/15.0x8.63 Rear Brakes
- Caterpillar (7.2L) C7 210 HP @ 2200 RPM,
- Governed @ 2500 RPM
- Single, Horizontal Muffler & Short Tail Pipe, Left Side 10 Gal.
- Single Tank Fuel Fill. Mandatory Charge Applied,
- Based On Tank Selection
- Driver Captains Chair, 40%, Reclining, Mortar Cloth w/
- Brick Cloth Insert
- Passenger Captains Chair, 40%, Reclining, Mortar Cloth w/
- Brick Cloth Insert
- XL T Trim Package
- Wheels, Front 19.5 x 7.5 Painted Steel Disc, 10-Hole Tires,
- Front Two 245/70R19.5F Goodyear G647 RSS (626 rev/mile)
- Wheels, Rear 19.5 x 7.5 Painted Steel Disc, 10-Hole
- Tires, Rear Four 245/70R19.5F Goodyear G647 RSS

MCU 2600

DETAIL SPECIFICATIONS

MOBILE COMMAND UNIT 26 ft
GTB# MCU2600

- Up to 33,000 GVWR
- 15 Kw Generator * with shore power access
- Welded Aluminum frame construction
- 2-3 door cabinets
- 1- Large storage cabinet with rod and hook
- Large First Aid Kit and Fire Extinguisher ABC 5 lb
- Overhead storage with Dry Erase board on door at each station
- 6 Work station w/ Motorola radio and Telecom access
- Sink area w/ faucet and pump
- Water Tank 12 gal, 20 gal waste tank under sink
- Internal 120V lighting and 12V lighting to specification
- All Electrical to required specification and NEC code
- Flip Down Table w/ large Dry Erase on wall
- Lower cabinet/drawer storage
- External storage 35 cu ft for extension cords and misc.
- External storage for aux. batteries
- External lighting to specification and NEC code
- 3 Rooftop A/C at 15000BTU/hr each
- Ford 750 Chassis (detail specs enclosed) - All options can be discussed for variation of vehicle layout.

Scope of any unit will be total dictated by contract specification and service schedule. General Truck Body Mfg is able to configure as well as assist with design requirements to best fit the needs of the customer.

* Optional 20 KW generator \$2000.00 for diesel version.

2008 Ford F-750

S Regular Cab XLT

Major Standard Equipment

- . Caterpillar 7.2L 1-6 OHV w/diesel injection 210 hp
- . 4-wheel ABS, air brakes
- . M+S rear tires
- . Tinted glass
- . Variable intermittent wipers
- . Tachometer
- . Cloth seats
- . 130 Amp alternator
- . 45gal. right front fuel tank
- . 10,000lbs. front axle capacity
- . 10,000lbs. front spring rating
- . 16.98cu.in. frame section modulus
- . 158.0" wheelbase
- . 49.0" axle to end of frame
- . Fuel/water separator
- . Right mounted horizontal muffler, right mounted horizontal tailpipe
- . 13.2cu.ft. air compressor, manual moisture ejector
- . 6 speed automatic trans w/OD
- . 11.0R22.5 highway tires
- . Air conditioning
- . AM/FM stereo single CD
- . 22.5" x 7.5" white steel disc wheels
- . High back 40-20-40 bench seats
- . 1,250 Amp dual batteries
- . Side steps
- . Multi-leaf rear springs
- . 21,000lbs. rear axle capacity
- . 23,500lbs. rear spring rating
- . 120,000 frame yield strength (psi)
- . 84.0" cab to axle
- . 246.0" overall length
- . Transmission PTO provision
- . Dual electric horn
- . Crankshaft-mounted engine PTO provision

Selected Optional Equipment

260" Wheelbase/186" CA/120" AF/419" OAL
Single Channel- Straight 'C' 14.18 SM, 120,000 PSI
Outer "C" Channel Reinforcement - 29.84 SM, 120,000 PSI
I-Beam Type - 13,200 lb. Cap. 1-132SG
Taper-Leaf Springs, Parabolic - 13,200 lb. Cap
Air Suspension - 23,000 lb. Cap
Air Brakes - Straight Truck
Allison Programming I/O Rugged Duty Series-
General Purpose/Construction
Single, Horizontal Muffler; Vertical Non-Bright Finish
Tail Pipe, Right Side
Rain Cap, Non-Bright Finish - For Single Vertical Exhaust
Roof Marker/Clearance Lights Delete
Tail Light Delete
Jump Start Single Stud - Remote Mounted On Battery Box
Tank - Steel (Deep) 50 U.S. gal. (189 L.) - Single
10 Gal. Single Tank Fuel Fill. Mandatory Charge Applied,
Based On Tank Selection
Driver Captains Chair, 40%, Reclining, G-Grain Vinyl with
G-Grain Vinyl Insert
Passenger Seat - Delete
XL T Trim Package

MCU 4000

DETAIL SPECIFICATIONS

MOBILE COMMAND UNIT 40 ft
GTB# MCU4000

- Up to 50,000 GVWR
- 25 Kw Generator with shore power access (Possible to place up to 60 KW)
- Welded Aluminum frame construction
- 4-3 door cabinets
- 3- Large storage cabinet with rod and hook
- Large First Aid Kit and 2 Fire Extinguisher ABC 5 lb
- Overhead storage with Dry Erase board on door at each station
- 6-8 Work station w/ Motorola radio and Telecom access
- Sink area w/ faucet and pump
- Water Tank 12 gal, 20 gal waste tank under sink
- Internal 120V lighting and 12V lighting to specification
- All Electrical to required specification and NEC code
- Flip Down Table w/ large Dry Erase on wall
- Lower cabinet/drawer storage
- External storage 35 cu ft for extension cords and misc.
- External storage for aux. batteries
- External lighting to specification and NEC code
- 6 Rooftop A/C at 15000BTU/hr each
- All options can be discussed for variation of vehicle layout.

Scope of any unit will be total dictated by contract specification and service schedule required. General Truck Body Mfg is able to configure as well as assist with design requirements to best fit the needs of the customer.

Semi-tractor will be specified DOT standard over the road requirements for total load up to 50,000 GVWR.

2008 Peterbilt 335
Std ConventionalCab

Major Standard Equipment

- Cummins 260hp diesel injection
- ABS, air brakes
- Tinted glass
- Variable intermittent wipers
- Tachometer
- Cloth seats
- 130 Amp alternator
- 70 gal. right front fuel tank
- 10,000 lbs. front axle capacity
- 10,000 lbs. front spring rating
- Fuel/water separator
- Right mounted vertical muffler
- 13.2cu.ft. air compressor, manual moisture ejector
- Transmission mounted engine PTO provision
- 9 speed Eaton-Fuller trans
- 11.0R22.5 highway tires
- Air conditioning
- AM/FM stereo single CD
- 22.5" x 7.5" aluminum disc wheels
- 1,250 Amp dual batteries
- 21,000 lbs. rear axle capacity
- 23,500 lbs. rear spring rating
- 120,000 frame yield strength (psi)
- Transmission PTO provision
- Peterbilt air ride suspension

EGU 1600

DETAIL SPECIFICATIONS

EVIDENCE GATHERING UNIT

GTB# EGU1600

- Up to 19,000 GVWR
- 5.5 kw Generator * w/ shore power access
- Welded Aluminum frame construction
- 2-3 door cabinets one with SS sink
- 1- Large storage cabinet w/ rod and hook
- Large First Aid Kit and Fire Extinguisher ABC 5 lb
- Overhead storage with Dry Erase board on door at each station
- Large Refrigeration w/ expanded metal partitions
- 3-4 Work station
- Sink area w/ faucet and pump
- Water Tank 12 gal/ 20 gal waste tank under sink
- Internal 120V lighting and 12V lighting to specification
- All Electrical to required specification and NEC code
- Flip Down Table w/ large Dry Erase on wall
- Lower cabinet/drawer storage
- External storage 35 cu ft for extension cords and misc.
- External storage for aux. batteries
- External lighting to specification and NEC code
- 1 Roof top A/C at 13500BTU/hr each
- Re-enforced rear roof for observation w/ ladder access (folding safety railing included).
- Ford 550 Chassis (detail specs enclosed) - All options can be discussed for variation of vehicle layout.

Scope of any unit will be total dictated by contract specification and service schedule required. General Truck Body Mfg is able to configure as well as assist with design requirements to best fit the needs of the customer.

* Optional 7.5 KW generator \$1000.00 for diesel version.

2008 Ford F-550 Chassis

4x2 SD Regular Cab 201 in. WB DRW XL T

Major Standard Equipment

- . Triton 6.8L V-10 SOHC w/SMP1362hp
- . 4-wheel ASS
- . Firm suspension
- . AM/FM stereo single CD
- . Variable intermittent wipers
- . Dual front airbags w/passenger cancel
- . Reclining front 40-20-40 split-bench seats
- . 17,950 lbs. GVWR
- . 13,660 lbs. rear GAWR
- . 13,660 lbs. rear axle capacity
- . 13,660 lbs. rear spring rating
- . 36,000 frame yield strength (psi)
- . 120.0" cab to axle
- . 285.6" overall length
- . 5 speed automatic trans w/OD
- . L T225/70SR 19.5F SSW AS tires
- . Air conditioning
- . Dual power remote heated mirrors
- . 19.5" x 6" wheels
- . Tachometer
- . Cloth seats
- . 6,000lbs. front GAWR
- . 7,000lbs. front axle capacity
- . 6,000lbs. front spring rating
- . 17.20cu.in. frame section modulus
- . 201.0" wheelbase
- . 47.5" axle to end of frame
- . Left mounted muffler, left mounted tailpipe

Selected Optional Equipment

Order Code 667 A
Engine: 6.0L V8 Power Stroke Diesel Transmission: TorqShift 5-Speed Auto w/OD (Diesel)
GVWR: 19,000 lbs
Cloth Luxury Captain's Chairs
Payload Upgrade Package
Ambulance Prep Package Not Included
50 State Emissions System

PEV 3000

DETAIL SPECIFICATIONS

30-Foot Patient Evacuation Vehicle - PEV3000



Base Model Price: \$493,225

Base Model Includes: 30' aluminum body with Freightliner Chassis or equivalent

Options Pricing

20 KW DIESEL GENERATOR or equivalent	\$ 9,969
45,000 BTU diesel fired heater	\$ 3,479
Hydraulic Leveling System	\$ 3,623
Litter Stanchions (1 pair / max cap. 4 litters) or equivalent*	\$87,463
Wheelchair Sure Lock (1 wheelchair cap.) Each	\$ 877
Single BV foldaway seat	\$ 687
Double BV foldaway seat	\$ 1,035
Electric Ramp Assist	\$ 2,047
Side door w/ entry door	\$ 2,624
Skylight Ventilator w/ safety glass or equivalent Each	\$ 365
8' Rear Awning	\$ 2,681
18ft side awning	\$ 903
2nd Oxygen Supply	\$18,190
Medical Air Throughout	\$18,190
Suction/Aspiration Throughout	\$18,190
HandiWash System	\$ 671
Auto Transfer System	\$ 3,778
Pwr Converter & Battery Conditioner	\$ 1,685
GPS Navigation System	\$ 497
LED Interior Lighting	\$ 342
EMS Digital Spectra radio	\$ 8,605
Intercom System	\$ 1,601
Back Up Camera w/ Sonar Prox Sys	\$ 1,192
Custom Graphics	\$ 3,934