



36 NE Hwy 156
P.O. Box 1988
Great Bend, KS 67530
Phone (620) 792-6222
Fax: (620) 792-3308
www.doonan.com

GENERAL SERVICES ADMINISTRATION

Federal Supply Service Authorized Federal Supply Schedule Price List

On-line access to contract ordering information, terms and conditions, up-to-date pricing, and the option to create an electronic delivery order are available through GSA Advantage!, a menu-driven database system.

The INTERNET address for GSA *Advantage!* is: GSAAvantage.gov.

For more information on ordering from Federal Supply Schedules click on the FSS Schedules button at fss.gsa.gov.

SOLICITATION NO. FFAH-C2-99-C-0325-B, REFRESH #6
WORLDWIDE FEDERAL SUPPLY SCHEDULE CONTRACT FOR
FSC GROUP 23, PART V, - VEHICULAR MULTIPLE AWARD SCHEDULE (VMAS)
FSC CLASS (ES)/PRODUCT CODE (S): 23

Schedule Title:

Multiple Award Schedule: 23V
Special Item Number (SIN): 023-101
Federal Stock Code: 2330
Contract Number: GS-30F-0011W
Contract Period: December 4, 2009 – December 3, 2014
DUNS Number: 063575245
CAGE Code: 0MPJ4

Address: Doonan Specialized Trailer, LLC
36 NE Hwy 156
P.O. Box 1988
Great Bend, KS 67530

Point of Contact: Elgen L. Reynolds
Co-Manager
Phone: (636) 614-2820
Fax: (620) 792-3308
Email: ereynolds@doonan.com
Website: www.doonan.com

- 1a. Table of awarded special item number(s) with appropriate cross-reference to item descriptions and awarded price(s). **See Attached Price List**
- 1b. Identification of the lowest priced model number and lowest unit price for that model for each special item number awarded in the contract. This price is the Government price based on a unit of one, exclusive of any quantity/dollar volume, prompt payment, or any other concession affecting price. Those contracts that have unit prices based on the geographic location of the customer, should show the range of the lowest price, and cite the areas to which the prices apply. **See Attached Price List**
- 1c. If the Contractor is proposing hourly rates, a description of all corresponding commercial job titles, experience, functional responsibility and education for those types of employees or subcontractors who will perform services shall be provided. If hourly rates are not applicable, indicate "Not applicable" for this item. **Not Applicable**
2. Maximum order. **\$2,500,000.00**
3. Minimum order. **\$100.00**
4. Geographic coverage (delivery area). **48 Contiguous States & District of Columbia, Alaska, Hawaii, Puerto Rico**
5. Point(s) of production (city, county, and State or foreign country). **Great Bend, KS Barton County**
6. Discount from list prices or statement of net price. **5%**
Doonan Specialized Trailer, LLC will provide a 5% basic discount to all GSA customers from its standard commercial price list. Additional discounts may be granted to Doonan's most favored customers without being granted to all GSA customers. However, in no instance will a discount be granted to a most favored customer that is greater than the 5% basic discount given to all GSA customers.
7. Quantity discounts. **None**
8. Prompt payment terms. **Net 30 days**
- 9a. Notification that Government purchase cards are accepted at or below the micro-purchase threshold. **Government purchase cards are accepted**
- 9b. Notification whether Government purchase cards are accepted or not accepted above the micro-purchase threshold. **Government purchase cards are accepted**
10. Foreign items (list items by country of origin). **Not Applicable**
- 11a. Time of delivery. (Contractor insert number of days.) **120 days**
- 11b. Expedited Delivery. The Contractor will insert the sentence "Items available for expedited delivery are noted in this price list." under this heading. The Contractor may use a symbol of its choosing to highlight items in its price lists that have expedited delivery. **60 days for 1 unit**
- 11c. Overnight and 2-day delivery. The Contractor will indicate whether overnight and 2-day delivery are available. Also, the Contractor will indicate that the schedule customer may contact the Contractor for rates for overnight and 2-day delivery. **Not Applicable**

- 11d. Urgent Requirements. The Contractor will note in its price list the "Urgent Requirements" clause of its contract and advise agencies that they can also contact the Contractor's representative to effect a faster delivery. **Not Applicable**
12. F.O.B. point(s). **Domestic**
- 13a. Ordering address(es). **36 NE Highway 156 Great Bend, KS 67530-8827**
- 13b. Ordering procedures: For supplies and services, the ordering procedures, information on Blanket Purchase Agreements (BPA's) are found in Federal Acquisition Regulation (FAR) 8.405-3.
14. Payment address(es). **PO BOX 1988 Great Bend, KS 67530-1988**
15. Warranty provision. **Standard manufacturer warranty**
16. Export packing charges, if applicable. **Not Applicable**
17. Terms and conditions of Government purchase card acceptance (any thresholds above the micro-purchase level). **Not Applicable**
18. Terms and conditions of rental, maintenance, and repair (if applicable). **Not Applicable**
19. Terms and conditions of installation (if applicable). **Not Applicable**
20. Terms and conditions of repair parts indicating date of parts price lists and any discounts from list prices (if applicable). **Not Applicable**
- 20a. Terms and conditions for any other services (if applicable). **Not Applicable**
21. List of service and distribution points (if applicable). **Not Applicable**
22. List of participating dealers (if applicable). **Not Applicable**
23. Preventive maintenance (if applicable). **Not Applicable**
- 24a. Special attributes such as environmental attributes (e.g., recycled content, energy efficiency, and/or reduced pollutants). **Not Applicable**
- 24b. If applicable, indicate that Section 508 compliance information is available on Electronic and Information Technology (EIT) supplies and services and show where full details can be found (e.g. contractor's website or other location.) The EIT standards can be found at: www.Section508.gov/.
25. Data Universal Number System (DUNS) number. **063575245**
26. Notification regarding registration in Central Contractor Registration (CCR) database **Doonan Specialized Trailer, LLC is registered with CCR.**

Doonan Dropdeck Specifications

Specifications		CHAPARRAL	Platinum	Diamond	Black Gold
Pricing	GSA Price	\$37,771.76	\$34,011.04	\$30,135.62	\$28,581.16
	Model Number	482ABNICEAKB	482MBOICCDKB	482MBCICCDKB	482DBCICCDKB
S T R U C T U R E	Beam Rating	50,000 lbs in 10 feet	50,000 lbs in 10 feet	50,000 lbs in 10 feet	50,000 lbs in 10 feet
	Overall Length	48' 0"	48' 0"	48' 0"	48' 0"
	Top Deck Length	10' 0"	10' 0"	10' 0"	10' 0"
	Rear Deck Length	38' 0"	38' 0"	38' 0"	38' 0"
	Width	102"	102"	102"	102"
	Rear Deck Height	41"	41"	40"	40"
	Fifth Wheel Height	49"	49"	49"	49"
	King Pin Setting	18"	18"	18"	18"
	Top Flange Thickness	1" x 5" extruded aluminum top rail	3/8" x 5" minimum 130k grade material	3/8" x 5" minimum 130k grade material	3/8" x 5" minimum 130k grade material
	Bottom Flange Thickness	1" x 5" extruded aluminum bottom rail	3/8" x 5" minimum 130k grade material	3/8" x 5" minimum 130k grade material	3/8" x 5" minimum 130k grade material
	Web Thickness	0.300" web aluminum	7 gauge web (minumum 80k grade web material)	7 gauge web (minumum 80k grade web material)	7 gauge web (minumum 80k grade web material)
	Beams	Two (2) 25" deep manufactured beams	Two (2) 24" deep manufactured beams	Two (2) 24" deep manufactured beams	Two (2) 24" deep manufactured beams
	Fifth Wheel & Gooseneck	Steel	Steel	Steel	Steel
	Cross Sill Height	5" alum. crossmembers on 15" centers	5" alum. crossmembers on 16" centers	4" steel crossmembers on 14" centers	4" steel crossmembers on 14" centers
	Side Rail	7.4" alum side rail with stake pockets on 24" centers, and dbl pipe spools, and integrated "J" hook track and integrated winch track	7.4" alum side rail with stake pockets on 24" centers, and dbl pipe spools, and integrated "J" hook track and integrated winch track	6" alum side rail with stake pockets on 24" centers, and dbl pipe spools, and integrated "J" hook track	6" steel side rail with stake pockets on 24" centers and double pipe spools
	Flooring	Aluminum Floor W/ 3 Apitong Nailers	Aluminum Floor W/ 3 Apitong Nailers	1 1/8" Apitong Wood Floor	1 1/8" Apitong Wood Floor
Paint	Silver - Sherwin Williams 2 part epoxy primer and top coat applied after shot blasting	Black - Sherwin Williams 2 part epoxy primer and top coat applied after shot blasting	Black - Sherwin Williams 2 part epoxy primer and top coat applied after shot blasting	Black - Sherwin Williams 2 part epoxy primer and top coat applied after shot blasting	
A X L E S & S U S P E N S I O N S	Suspension Type	Hendrickson AA230	Hendrickson AA230	Hendickson HT250	Hendickson HT250
	Number of Axles	2 axles - 23,000 lb nominal with 77.5 tracking	2 axles - 23,000 lb nominal with 77.5 tracking	2 axles - 25,000 lb nominal with 77.5 tracking	2 axles - 25,000 lb nominal with 77.5 tracking
	Axle Spacing	122" - set to the rear	122" - set to the rear	122" - set to the rear	122" - set to the rear
	Sliding Axles	No Sliding Axles	No Sliding Axles	No Sliding Axles	No Sliding Axles
	Axle Spindle	Tapered Spindle	Tapered Spindle	Tapered Spindle	Tapered Spindle
	Lift Axle Kits	None Standard	None Standard	None Standard	None Standard
	Hub & Drums	Duralite hub and fused drums	Duralite hub and fused drums	Cast hub and cast drums	Cast hub and cast drums
	Bearing Lubricant	Oil in hubs	Oil in hubs	Oil in hubs	Oil in hubs
	Outer Wheels	22.5" x 8.25" Aluminum - Milled	22.5" x 8.25" Aluminum - Milled	22.5" x 8.25" Steel - Prepainted White	22.5" x 8.25" Steel - Prepainted White
	Inner Wheels	22.5" x 8.25" Aluminum - Milled	22.5" x 8.25" Aluminum - Milled	22.5" x 8.25" Steel - Prepainted White	22.5" x 8.25" Steel - Prepainted White
	Tires	General ST250 255/70R22.5	General ST250 255/70R22.5	General ST250 255/70R22.5	General ST250 255/70R22.5
	Spare Wheel & Tire	None Standard	None Standard	None Standard	None Standard
Tire Carrier	None Standard	None Standard	None Standard	None Standard	
Tire Inflation System	None Standard	None Standard	None Standard	None Standard	
Mudflaps	One Pair Per Axle	One Pair Per Axle	One Pair Per Axle	One Pair Per Axle	
A I R & L I G H T S	ABS	Wabco 4S/2M	Wabco 4S/2M	Wabco 4S/2M	Wabco 4S/2M
	Brakes	Spring brakes with auto slack adjusters	Spring brakes with auto slack adjusters	Spring brakes with auto slack adjusters	Spring brakes with auto slack adjusters
	Brake Dust Covers	None Standard	None Standard	None Standard	None Standard
	Light Kit	Standard Grote LED	Standard Grote LED	Standard Grote LED	Standard Grote LED
	Clearance Lights	5 Clearance Lights Per Side	5 Clearance Lights Per Side	3 Clearance Lights Per Side	3 Clearance Lights Per Side
	Rear Lights	3-3-3 Standard LED Rear Lights	3-3-3 Standard LED Rear Lights	4-3-4 Standard LED Rear Lights	4-3-4 Standard LED Rear Lights
	Conspicuity Tape	Per NHTSA spec	Per NHTSA spec	Per NHTSA spec	Per NHTSA spec
	Flag Holders	Not Included	Not Included	Not Included	Not Included
M I S C .	Certificate Holder	Not Included	Not Included	Not Included	Not Included
	FHWA Inspection	Not Included	Not Included	Not Included	Not Included
		Omit Front Stake Pockets	Omit Front Stake Pockets	Omit Front Stake Pockets	Omit Front Stake Pockets
		Omit Rear Stake Pockets & Rubrail	Omit Rear Stake Pockets & Rubrail	Omit Rear Stake Pockets & Rubrail	Omit Rear Stake Pockets & Rubrail
		Manual Dock Dump Valve	Beam Holes	Alum. Tail Light Panels	
	Winch Track - Both Sides	Winch Track - Both Sides	Aluminum Drop Plate		
	Rubber Dock Bumpers	Rubber Dock Bumpers			
Weight		8,759 lbs	9,019 lbs	10,441 lbs	10,791 lbs

Doonan Flatbed Specifications

	Specifications	CHAPARRAL	Platinum	Diamond	Black Gold
Pricing	GSA Price	\$33,880.25	\$30,419.71	\$26,329.87	\$24,989.82
S T R U C T U R E	Model Number	482BBNLTAKB	482OBOLTTDKB	482OBCLTTDKB	482FBCLTTDKB
	Beam Rating	60,000 lbs in 10 feet	50,000 lbs in 10 feet	50,000 lbs in 10 feet	50,000 lbs in 10 feet
	Overall Length	48' 0"	48' 0"	48' 0"	48' 0"
	Top Deck Length	0' 0"	0' 0"	0' 0"	0' 0"
	Rear Deck Length	48' 0"	48' 0"	48' 0"	48' 0"
	Width	102"	102"	102"	102"
	Rear Deck Height	54"	54"	54"	54"
	Fifth Wheel Height	49"	49"	49"	49"
	King Pin Setting	18"	18"	18"	18"
	Top Flange Thickness	1" x 5" extruded aluminum top rail	3/8" x 5" minimum 130k grade material	3/8" x 5" minimum 130k grade material	3/8" x 5" minimum 130k grade material
	Bottom Flange Thickness	1" x 5" extruded aluminum bottom rail	3/8" x 5" minimum 130k grade material	3/8" x 5" minimum 130k grade material	3/8" x 5" minimum 130k grade material
	Web Thickness	0.300" web aluminum	7 gauge web (minumum 80k grade web material)	7 gauge web (minumum 80k grade web material)	7 gauge web (minumum 80k grade web material)
	Beams	Two (2) 25" deep manufactured beams	Two (2) 24" deep manufactured beams	Two (2) 24" deep manufactured beams	Two (2) 24" deep manufactured beams
	Cross Sill Height	5" alum. crossmembers on 15" centers	5" alum. crossmembers on 16" centers	4" steel crossmembers on 14" centers	4" steel crossmembers on 14" centers
	Side Rail	7.4" alum side rail with stake pockets on 24" centers, and dbl pipe spools, and integrated "J" hook track and integrated winch track	7.4" alum side rail with stake pockets on 24" centers, and dbl pipe spools, and integrated "J" hook track and integrated winch track	6" alum side rail with stake pockets on 24" centers, and dbl pipe spools, and integrated "J" hook track	6" steel side rail with stake pockets on 24" centers and double pipe spools
	Flooring	Aluminum Floor W/ 3 Apitong Nailers	Aluminum Floor W/ 3 Apitong Nailers	1 1/8" Apitong Wood Floor	1 1/8" Apitong Wood Floor
Paint	Silver - Sherwin Williams 2 part epoxy primer and top coat applied after shot blasting	Black - Sherwin Williams 2 part epoxy primer and top coat applied after shot blasting	Black - Sherwin Williams 2 part epoxy primer and top coat applied after shot blasting	Black - Sherwin Williams 2 part epoxy primer and top coat applied after shot blasting	
A X L E S & S U S P E N S I O N S	Suspension Type	Hendrickson AA230	Hendrickson AA230	Hendrickson AA230	Hendrickson AA230
	Number of Axles	2 axles - 23,000 lb nominal with 77.5 tracking	2 axles - 23,000 lb nominal with 77.5 tracking	2 axles - 25,000 lb nominal with 77.5 tracking	2 axles - 25,000 lb nominal with 77.5 tracking
	Axle Spacing	122" - set to the rear	122" - set to the rear	122" - set to the rear	122" - set to the rear
	Sliding Axles	No Sliding Axles	No Sliding Axles	No Sliding Axles	No Sliding Axles
	Axle Spindle	Tapered Spindle	Tapered Spindle	Tapered Spindle	Tapered Spindle
	Lift Axle Kits	None Standard	None Standard	None Standard	None Standard
	Hub & Drums	Duralite hub and fused drums	Duralite hub and fused drums	Cast hub and cast drums	Cast hub and cast drums
	Bearing Lubricant	Oil in hubs	Oil in hubs	Oil in hubs	Oil in hubs
	Outer Wheels	22.5" x 8.25" Aluminum - Milled	22.5" x 8.25" Aluminum - Milled	22.5" x 8.25" Steel - Prepainted White	22.5" x 8.25" Steel - Prepainted White
	Inner Wheels	22.5" x 8.25" Aluminum - Milled	22.5" x 8.25" Aluminum - Milled	22.5" x 8.25" Steel - Prepainted White	22.5" x 8.25" Steel - Prepainted White
	Tires	General ST250 295/75R22.5	General ST250 295/75R22.5	General ST250 295/75R22.5	General ST250 295/75R22.5
	Spare Wheel & Tire	None Standard	None Standard	None Standard	None Standard
	Tire Carrier	None Standard	None Standard	None Standard	None Standard
Tire Inflation System	None Standard	None Standard	None Standard	None Standard	
Mudflaps	One Pair Per Axle	One Pair Per Axle	One Pair Per Axle	One Pair Per Axle	
A I R & L I G H T S	ABS	Wabco 4S/2M	Wabco 4S/2M	Wabco 4S/2M	Wabco 4S/2M
	Brakes	Spring brakes with auto slack adjusters	Spring brakes with auto slack adjusters	Spring brakes with auto slack adjusters	Spring brakes with auto slack adjusters
	Brake Dust Covers	None Standard	None Standard	None Standard	None Standard
	Light Kit	Standard Grote LED	Standard Grote LED	Standard Grote LED	Standard Grote LED
	Clearance Lights	5 Clearance Lights Per Side	5 Clearance Lights Per Side	3 Clearance Lights Per Side	3 Clearance Lights Per Side
	Rear Lights	3-3-3 Standard LED Rear Lights	3-3-3 Standard LED Rear Lights	4-3-4 Standard LED Rear Lights	4-3-4 Standard LED Rear Lights
	Conspicuity Tape	Per NHTSA spec	Per NHTSA spec	Per NHTSA spec	Per NHTSA spec
	Flag Holders	Not Included	Not Included	Not Included	Not Included
M I S C	Certificate Holder	Not Included	Not Included	Not Included	Not Included
	FHWA Inspection	Not Included	Not Included	Not Included	Not Included
		Omit Front Stake Pockets	Omit Front Stake Pockets	Omit Front Stake Pockets	Omit Front Stake Pockets
		Omit Rear Stake Pockets & Rubrail	Omit Rear Stake Pockets & Rubrail	Omit Rear Stake Pockets & Rubrail	Omit Rear Stake Pockets & Rubrail
		Auto Dump When Set Park Brakes	Auto Dump When Set Park Brakes	Auto Dump When Set Park Brakes	Auto Dump When Set Park Brakes
	Winch Track - Both Sides	Winch Track - Both Sides	Alum. Tail Light Panels		
	Rubber Dock Bumpers	Rubber Dock Bumpers			
		Beam Holes			
Weight		8,262 lbs	8,834 lbs	10,276 lbs	10,606 lbs

Doonan Mechanical Detachable (RGN) Double Drop Specifications

Specifications		60,000	70,000	80,000	90,000	100,000
Pricing	GSA Price	\$39,087.15	\$41,231.23	\$43,107.30	\$47,181.06	\$49,057.13
S T R U C T U R E	Model Number	482QBBIQFCB	482QBBIQGCB	482QBBIQNCB	482QBBIQNCB	482QBBIQNCB
	Beam Rating	60,000 lbs in 16 feet	70,000 lbs in 16 feet	80,000 lbs in 16 feet	90,000 lbs in 16 feet	100,000 lbs in 16 feet
	Overall Length	48' 0"	48' 0"	48' 0"	48' 0"	48' 0"
	Top Deck Length	10' 0"	10' 0"	10' 0"	10' 0"	10' 0"
	Main Deck Length	29' 0"	29' 0"	29' 0"	29' 0"	29' 0"
	Rear Deck Length	9' 0"	9' 0"	9' 0"	9' 0"	9' 0"
	Width	102 inches	102 inches	102 inches	102 inches	102 inches
	Flange - Inner Beam	5/8" x 7" minimum 130k grade material	3/4" x 7" minimum 130k grade material	3/4" x 7" minimum 130k grade material	1" x 7" minimum 130k grade material	1" x 7" minimum 130k grade material
	Flange - Outer Beam	1/2" x 6" minimum 130k grade material	1/2" x 6" minimum 130k grade material			
	Inner Beams	Two (2) 12" deep manufactured beams with 1/4" web (minimum 50k grade web material)	Two (2) 12" deep manufactured beams with 1/4" web (minimum 50k grade web material)	Two (2) 14" deep manufactured beams with 1/4" web (minimum 50k grade web material)	Two (2) 14" deep manufactured beams with 1/4" web (minimum 50k grade web material)	Two (2) 16 deep manufactured beams with 1/4" web (minimum 50k grade web material)
	Outer Beams	Two (2) 12" deep manufactured beams with 1/4" web (minimum 50k grade web material)	Two (2) 12" deep manufactured beams with 1/4" web (minimum 50k grade web material)	Two (2) 14" deep manufactured beams with 1/4" web (minimum 50k grade web material)	Two (2) 14" deep manufactured beams with 1/4" web (minimum 50k grade web material)	Two (2) 16 deep manufactured beams with 1/4" web (minimum 50k grade web material)
	Cross Sill Height	6" & 4" alternating crossmembers on 12" centers	6" & 4" alternating crossmembers on 12" centers	8" & 4" alternating crossmembers on 12" centers	8" & 4" alternating crossmembers on 12" centers	10" & 4" alternating crossmembers on 12" centers
	Side Rail	Outer perimeter beam with 4 D-rings on each side of the main deck	Outer perimeter beam with 4 D-rings on each side of the main deck	Outer perimeter beam with 4 D-rings on each side of the main deck	Outer perimeter beam with 4 D-rings on each side of the main deck	Outer perimeter beam with 4 D-rings on each side of the main deck
	Neck	Full width top deck with outer perimeter beams and 2 D-rings on each side	Full width top deck with outer perimeter beams and 2 D-rings on each side	Full width top deck with outer perimeter beams and 2 D-rings on each side	Full width top deck with outer perimeter beams and 2 D-rings on each side	Full width top deck with outer perimeter beams and 2 D-rings on each side
	Rear Deck Height	40 inches	40 inches	40 inches	40 inches	40 inches
	Main Deck Height	18 inches	18 inches	20 inches	20 inches	24 inches
	Fifth Wheel Height	49 inches	49 inches	49 inches	49 inches	49 inches
	King Pin Setting	16 inches	16 inches	16 inches	16 inches	16 inches
	Outriggers	None Standard	None Standard	None Standard	None Standard	None Standard
	Flooring	1 5/16 Inch Apitong Wood	1 3/8 Inch Apitong Wood	1 3/8 Inch Apitong Wood	1 1/2 Inch Apitong Wood	1 1/2 Inch Apitong Wood
Paint	Black - Sherwin Williams	Black - Sherwin Williams	Black - Sherwin Williams	Black - Sherwin Williams	Black - Sherwin Williams	
A X L E S & S U S P E N S I O N S	Suspension Type	Hendrickson HT250 Air-ride Suspension	Hendrickson HT250 Air-ride Suspension			
	Number of Axles	2 axles - 25,000 lb nominal with 77.5 tracking	2 axles - 25,000 lb nominal with 77.5 tracking	2 axles - 25,000 lb nominal with 77.5 tracking	2 axles - 25,000 lb nominal with 77.5 tracking	2 axles - 25,000 lb nominal with 77.5 tracking
	Axle Spacing	54 inches - set to the rear	54 inches - set to the rear			
	Sliding Axles	No Sliding Axles	No Sliding Axles	No Sliding Axles	No Sliding Axles	No Sliding Axles
	Axle Spindle	Tapered Spindle	Tapered Spindle	Tapered Spindle	Tapered Spindle	Tapered Spindle
	Lift Axle Kits	None Standard	None Standard	None Standard	None Standard	None Standard
	Hub & Drums	Cast hub with outboard cast drums	Cast hub with outboard cast drums	Cast hub with outboard cast drums	Cast hub with outboard cast drums	Cast hub with outboard cast drums
	Bearing Lubricant	Oil in hubs	Oil in hubs	Oil in hubs	Oil in hubs	Oil in hubs
	Outer Wheels	22.5" x 8.25" Steel - Prepainted White	22.5" x 8.25" Steel - Prepainted White			
	Inner Wheels	22.5" x 8.25" Steel - Prepainted White	22.5" x 8.25" Steel - Prepainted White			
	Tires	General ST250 255/70R22.5	General ST250 255/70R22.5	General ST250 255/70R22.5	General ST250 255/70R22.5	General ST250 255/70R22.5
	Spare Wheel & Tire	None Standard	None Standard	None Standard	None Standard	None Standard
	Tire Carrier	None Standard	None Standard	None Standard	None Standard	None Standard
Tire Inflation System	None Standard	None Standard	None Standard	None Standard	None Standard	
Mudflaps	Single Pair At Rear	Single Pair At Rear	Single Pair At Rear	Single Pair At Rear	Single Pair At Rear	
A I R & L I G H T S	ABS	Wabco 4S/2M	Wabco 4S/2M	Wabco 4S/2M	Wabco 4S/2M	Wabco 4S/2M
	Brakes	Spring brakes with auto slack adjusters	Spring brakes with auto slack adjusters			
	Brake Dust Covers	None Standard	None Standard	None Standard	None Standard	None Standard
	Light Kit	Standard Grote LED	Standard Grote LED	Standard Grote LED	Standard Grote LED	Standard Grote LED
	Clearance Lights	3 Clearance Lights Per Side	3 Clearance Lights Per Side			
	Rear Lights	4-3-4 Standard LED Lights	4-3-4 Standard LED Lights	4-3-4 Standard LED Lights	4-3-4 Standard LED Lights	4-3-4 Standard LED Lights
	Conspicuity Tape	Per NHTSA spec	Per NHTSA spec	Per NHTSA spec	Per NHTSA spec	Per NHTSA spec
	Flag Holders	Included Standard	Included Standard	Included Standard	Included Standard	Included Standard
	Certificate Holder	Included Standard	Included Standard	Included Standard	Included Standard	Included Standard
FHWA Inspection	Included Standard	Included Standard	Included Standard	Included Standard	Included Standard	
Weight		14,787 lbs	15,387 lbs	15,637 lbs	16,837 lbs	17,087 lbs

Doonan Fixed Neck Double Drop Specifications

Specifications		60,000	70,000	80,000	90,000	100,000
Pricing	GSA Price	\$38,015.11	\$40,159.19	\$42,035.26	\$46,109.02	\$47,985.09
	Model Number	482SBBICOFGB	482SBBICOGCB	482SBCICNGCB	482SBCICNHCB	482SBEICMHCB
S T R U C T U R E	Beam Rating	60,000 lbs in 16 feet	70,000 lbs in 16 feet	80,000 lbs in 16 feet	90,000 lbs in 16 feet	100,000 lbs in 16 feet
	Overall Length	48' 0"	48' 0"	48' 0"	48' 0"	48' 0"
	Top Deck Length	10' 0"	10' 0"	10' 0"	10' 0"	10' 0"
	Main Deck Length	29' 0"	29' 0"	29' 0"	29' 0"	29' 0"
	Rear Deck Length	9' 0"	9' 0"	9' 0"	9' 0"	9' 0"
	Width	102 inches	102 inches	102 inches	102 inches	102 inches
	Flange - Inner Beam	5/8" x 7" minimum 130k grade material	3/4" x 7" minimum 130k grade material	3/4" x 7" minimum 130k grade material	1" x 7" minimum 130k grade material	1" x 7" minimum 130k grade material
	Flange - Outer Beam	1/2" x 6" minimum 130k grade material	1/2" x 6" minimum 130k grade material			
	Inner Beams	Two (2) 12" deep manufactured beams with 1/4" web (minimum 50k grade web material)	Two (2) 12" deep manufactured beams with 1/4" web (minimum 50k grade web material)	Two (2) 14" deep manufactured beams with 1/4" web (minimum 50k grade web material)	Two (2) 14" deep manufactured beams with 1/4" web (minimum 50k grade web material)	Two (2) 16 deep manufactured beams with 1/4" web (minimum 50k grade web material)
	Outer Beams	Two (2) 12" deep manufactured beams with 1/4" web (minimum 50k grade web material)	Two (2) 12" deep manufactured beams with 1/4" web (minimum 50k grade web material)	Two (2) 14" deep manufactured beams with 1/4" web (minimum 50k grade web material)	Two (2) 14" deep manufactured beams with 1/4" web (minimum 50k grade web material)	Two (2) 16 deep manufactured beams with 1/4" web (minimum 50k grade web material)
	Cross Sill Height	6" & 4" alternating crossmembers on 12" centers	6" & 4" alternating crossmembers on 12" centers	8" & 4" alternating crossmembers on 12" centers	8" & 4" alternating crossmembers on 12" centers	10" & 4" alternating crossmembers on 12" centers
	Side Rail	Outer perimeter beam with 4 D-rings on each side of the main deck	Outer perimeter beam with 4 D-rings on each side of the main deck	Outer perimeter beam with 4 D-rings on each side of the main deck	Outer perimeter beam with 4 D-rings on each side of the main deck	Outer perimeter beam with 4 D-rings on each side of the main deck
	Neck	Full width top deck with outer perimeter beams and 2 D-rings on each side	Full width top deck with outer perimeter beams and 2 D-rings on each side	Full width top deck with outer perimeter beams and 2 D-rings on each side	Full width top deck with outer perimeter beams and 2 D-rings on each side	Full width top deck with outer perimeter beams and 2 D-rings on each side
	Rear Deck Height	40 inches	40 inches	40 inches	40 inches	40 inches
	Main Deck Height	18 inches	18 inches	20 inches	20 inches	24 inches
	Fifth Wheel Height	49 inches	49 inches	49 inches	49 inches	49 inches
	King Pin Setting	16 inches	16 inches	16 inches	16 inches	16 inches
	Outriggers	None Standard	None Standard	None Standard	None Standard	None Standard
	Flooring	1 5/16 Inch Apitong Wood	1 3/8 Inch Apitong Wood	1 3/8 Inch Apitong Wood	1 1/2 Inch Apitong Wood	1 1/2 Inch Apitong Wood
	Paint	Black - Sherwin Williams	Black - Sherwin Williams			
A X L E S & S U S P E N S I O N S	Suspension Type	Hendrickson HT250 Air-ride Suspension	Hendrickson HT250 Air-ride Suspension			
	Number of Axles	2 axles - 25,000 lb nominal with 77.5 tracking	2 axles - 25,000 lb nominal with 77.5 tracking	2 axles - 25,000 lb nominal with 77.5 tracking	2 axles - 25,000 lb nominal with 77.5 tracking	2 axles - 25,000 lb nominal with 77.5 tracking
	Axle Spacing	54 inches - set to the rear	54 inches - set to the rear			
	Sliding Axles	No Sliding Axles	No Sliding Axles	No Sliding Axles	No Sliding Axles	No Sliding Axles
	Axle Spindle	Tapered Spindle	Tapered Spindle	Tapered Spindle	Tapered Spindle	Tapered Spindle
	Lift Axle Kits	None Standard	None Standard	None Standard	None Standard	None Standard
	Hub & Drums	Cast hub with outboard cast drums	Cast hub with outboard cast drums	Cast hub with outboard cast drums	Cast hub with outboard cast drums	Cast hub with outboard cast drums
	Bearing Lubricant	Oil in hubs	Oil in hubs	Oil in hubs	Oil in hubs	Oil in hubs
	Outer Wheels	22.5" x 8.25" Steel - Prepainted White	22.5" x 8.25" Steel - Prepainted White			
	Inner Wheels	22.5" x 8.25" Steel - Prepainted White	22.5" x 8.25" Steel - Prepainted White			
	Tires	General ST250 255/70R22.5	General ST250 255/70R22.5	General ST250 255/70R22.5	General ST250 255/70R22.5	General ST250 255/70R22.5
	Spare Wheel & Tire	None Standard	None Standard	None Standard	None Standard	None Standard
	Tire Carrier	None Standard	None Standard	None Standard	None Standard	None Standard
Tire Inflation System	None Standard	None Standard	None Standard	None Standard	None Standard	
Mudflaps	Single Pair At Rear	Single Pair At Rear	Single Pair At Rear	Single Pair At Rear	Single Pair At Rear	
A I R & L I G H T S	ABS	Wabco 4S/2M	Wabco 4S/2M	Wabco 4S/2M	Wabco 4S/2M	Wabco 4S/2M
	Brakes	Spring brakes with auto slack adjusters	Spring brakes with auto slack adjusters			
	Brake Dust Covers	None Standard	None Standard	None Standard	None Standard	None Standard
	Light Kit	Standard Grote LED	Standard Grote LED	Standard Grote LED	Standard Grote LED	Standard Grote LED
	Clearance Lights	3 Clearance Lights Per Side	3 Clearance Lights Per Side			
	Rear Lights	4-3-4 Standard LED Lights	4-3-4 Standard LED Lights	4-3-4 Standard LED Lights	4-3-4 Standard LED Lights	4-3-4 Standard LED Lights
	Conspicuity Tape	Per NHTSA spec	Per NHTSA spec	Per NHTSA spec	Per NHTSA spec	Per NHTSA spec
	Flag Holders	Included Standard	Included Standard	Included Standard	Included Standard	Included Standard
	Certificate Holder	Included Standard	Included Standard	Included Standard	Included Standard	Included Standard
FHWA Inspection	Included Standard	Included Standard	Included Standard	Included Standard	Included Standard	
Weight	14,787 lbs	15,387 lbs	15,637 lbs	16,837 lbs	17,087 lbs	

Doonan Extendibles Specifications

Specifications		Dropdeck Black Gold	Flatbed Black Gold	RGN 60,000	Fixed Neck 60,000
Pricing	GSA Price	\$46,591.44	\$43,000.10	\$57,311.84	\$56,239.80
	Model Number	482DBCICJABX	482FBLTJTJABX	482QBBIcofCBX	482SBBICofCBX
S T R U C T U R E	Beam Rating	70,000 lbs in 10 feet in the closed position	70,000 lbs in 10 feet in the closed position	50,000 lbs in 16 feet in the closed well position	50,000 lbs in 16 feet in the closed well position
	Overall Length	48' 0" to 68' 9"	48' 0" to 80' 9"	48' 0" to 69' 0"	48' 0" to 69' 0"
	Top Deck Length	10' 0"	0' 0"	10' 0"	10' 0"
	Main Deck Length	N/A	N/A	29' 0" to 50' 0"	29' 0" to 50' 0"
	Rear Deck Length	38' 0"	48' 0"	9' 0"	9' 0"
	Width	102 inches	102 inches	102 inches	102 inches
	Flange - Inner Beam	5/8" x 6" minimum 130k grade material	5/8" x 6" minimum 130k grade material	5/8" x 15" minimum 100k grade material	5/8" x 15" minimum 100k grade material
	Flange - Outer Beam	1/2" x 6" minimum 130k grade material	1/2" x 6" minimum 130k grade material	1/2" x 17" minimum 130k grade material	1/2" x 17" minimum 130k grade material
	Inner Beams	Two (2) 24 inch deep manufactured beams with 7 gauge web (minumum 80k grade web material)	Two (2) 24 inch deep manufactured beams with 7 gauge web (minumum 80k grade web material)	Two (2) 12" deep manufactured beams with 1/4" web (minumum 50k grade web material)	Two (2) 12" deep manufactured beams with 1/4" web (minumum 50k grade web material)
	Outer Beams	N/A	N/A	8 inch steel structural "C" channel	8 inch steel structural "C" channel
	Cross Sill Height	4 inch steel crossmembers on 14 inch centers	4 inch steel crossmembers on 14 inch centers	6" & 4" alternating crossmembers on 12" centers	6" & 4" alternating crossmembers on 12" centers
	Side Rail	6" steel side rail with stake pockets on 24" centers and double pipe spools	6" steel side rail with stake pockets on 24" centers and double pipe spools	Outer perimeter beam with 4 D-rings on each side of the main deck	Outer perimeter beam with 4 D-rings on each side of the main deck
	Neck			Full width top deck with 6 inch steel structural "C" channel with 2 D-rings per side	Full width top deck with 6 inch steel structural "C" channel with 2 D-rings per side
	Rear Deck Height	40 inches	58 inches	40 inches	40 inches
	Main Deck Height	N/A	N/A	20 inches	20 inches
	Fifth Wheel Height	49 inches	49 inches	49 inches	49 inches
	King Pin Setting	18 inches	18 inches	16 inches	16 inches
	Outriggers	N/A	N/A	None Standard	None Standard
	Flooring	1 1/8 Inch Apitong Wood Floor	1 1/8 Inch Apitong Wood Floor	1 5/16 Inch Apitong Wood Floor	1 5/16 Inch Apitong Wood Floor
	Paint	Black - Sherwin Williams 2 part epoxy primer and top coat applied after shot blasting	Black - Sherwin Williams 2 part epoxy primer and top coat applied after shot blasting	Black - Sherwin Williams 2 part epoxy primer and top coat applied after shot blasting	Black - Sherwin Williams 2 part epoxy primer and top coat applied after shot blasting
S U S P E N S I & O N S	Suspension Type	Hendrickson HT - 25,000 lb	Hendrickson AA230	Hendrickson HT250 Air-ride Suspension	Hendrickson HT250 Air-ride Suspension
	Number of Axles	2 axles - 25,000 lb nominal with 77.5 tracking	2 axles - 25,000 lb nominal with 77.5 tracking	2 axles - 25,000 lb nominal with 77.5 tracking	2 axles - 25,000 lb nominal with 77.5 tracking
	Axle Spacing	49 inches - set to the rear	49 inches - set to the rear	54 inches - set to the rear	54 inches - set to the rear
	Sliding Axles	No Sliding Axles	No Sliding Axles		
	Axle Spindle	Tapered Spindle	Tapered Spindle	Tapered Spindle	Tapered Spindle
	Lift Axle Kits	None Standard	None Standard	None Standard	None Standard
	Hub & Drums	Cast hub and cast drums	Cast hub and cast drums	Cast hub and cast drums	Cast hub and cast drums
	Bearing Lubricant	Oil in hubs	Oil in hubs	Oil in hubs	Oil in hubs
	Outer Wheels	22.5" x 8.25" Steel - Prepainted White	22.5" x 8.25" Steel - Prepainted White	22.5" x 8.25" Steel - Prepainted White	22.5" x 8.25" Steel - Prepainted White
	Inner Wheels	22.5" x 8.25" Steel - Prepainted White	22.5" x 8.25" Steel - Prepainted White	22.5" x 8.25" Steel - Prepainted White	22.5" x 8.25" Steel - Prepainted White
	Tires	General ST250 255/70R22.5 - Drop	General ST250 295/75R22.5 - Flat	General ST250 255/70R22.5	General ST250 255/70R22.5
	Spare Wheel & Tire	None Standard	None Standard	None Standard	None Standard
	Tire Carrier	None Standard	None Standard	None Standard	None Standard
Tire Inflation System	None Standard	None Standard	None Standard	None Standard	
Mudflaps	Single Pair At Rear	Single Pair At Rear	Single Pair At Rear	Single Pair At Rear	
A I R H T & S	ABS	Wabco 4S/2M	Wabco 4S/2M	Wabco 4S/2M	Wabco 4S/2M
	Brakes	Spring brakes with auto slack adjusters	Spring brakes with auto slack adjusters	Spring brakes with auto slack adjusters	Spring brakes with auto slack adjusters
	Brake Dust Covers	None Standard	None Standard	None Standard	None Standard
	Light Kit	Standard Grote LED	Standard Grote LED	Standard Grote LED	Standard Grote LED
	Clearance Lights	3 Clearance Lights Per Side	3 Clearance Lights Per Side	3 Clearance Lights Per Side	3 Clearance Lights Per Side
	Rear Lights	4-3-4 Standard LED Rear Lights	4-3-4 Standard LED Rear Lights	4-3-4 Standard LED Lights	4-3-4 Standard LED Lights
	Conspicuity Tape	Per NHTSA spec	Per NHTSA spec	Per NHTSA spec	Per NHTSA spec
	Flag Holders	Not Included	Not Included	Included Standard	Included Standard
	Certificate Holder	Not Included	Not Included	Included Standard	Included Standard
FHWA Inspection	Not Included	Not Included	Included Standard	Included Standard	
M I S C		Omit Front Stake Pockets	Omit Front Stake Pockets		
		Omit Rear Stake Pockets & Rubrail	Omit Rear Stake Pockets & Rubrail		
Weight					
		14,686 lbs	14,501 lbs	17,787 lbs	17,787 lbs

Doonan Available Options

Available Options		CHAPARRAL		Platinum		Diamond		Black Gold	
		Flatbed	Dropdeck	Flatbed	Dropdeck	Flatbed	Dropdeck	Flatbed	Dropdeck
S T R U C T U R E	Extendibles: lengths 80'+			♦	♦	♦	♦	♦	♦
	96" & 102" widths	♦	♦	♦	♦	♦	♦	♦	♦
	3/8", 1/2", 5/8" or 3/4" steel top & bottom flanges			♦	♦	♦	♦	♦	♦
	7 Gauge, 1/4", or 3/8" steel web material			♦	♦	♦	♦	♦	♦
	Normal duty, heavy duty or super duty aluminum beams	♦	♦						
	Beam holes			♦	♦	♦	♦	♦	♦
	12", 14" or 16" sill spacings			♦	♦	♦	♦	♦	♦
	12" or 15" sill spacings	♦	♦						
	Steel sills					♦	♦	♦	♦
	Aluminum sills	♦	♦	♦	♦				
	Steel side rails							♦	♦
	Aluminum side rails	♦	♦	♦	♦	♦	♦		
	Single pipe spool or double pipe spools on side rail	♦	♦	♦	♦	♦	♦	♦	♦
	Front stake pockets	♦	♦	♦	♦	♦	♦	♦	♦
	Rear stake pockets & rub rail	♦	♦	♦	♦	♦	♦	♦	♦
	Apitong or aluminum flooring	♦	♦	♦	♦	♦	♦	♦	♦
13.5", 18", 24", 30", or 36" king pin setting	♦	♦	♦	♦	♦	♦	♦	♦	
S U S P E N S I O N S & A X L E S	HT, AA or spring suspension types	♦	♦	♦	♦	♦	♦	♦	♦
	23k, 25k, or 30k suspensions & axle ratings	♦	♦	♦	♦	♦	♦	♦	♦
	Front or rear axle slides	♦	♦	♦	♦	♦	♦	♦	♦
	Tandem axle slides	♦	♦			♦	♦	♦	♦
	Multi axles	♦	♦	♦	♦	♦	♦	♦	♦
	Lift kits	♦	♦			♦	♦	♦	♦
	California legal axle settings	♦	♦	♦	♦	♦	♦	♦	♦
	Axle spacing from 49" to 122"	♦	♦	♦	♦	♦	♦	♦	♦
	Cast or light weight hubs	♦	♦	♦	♦	♦	♦	♦	♦
	Cast or fused drums	♦	♦	♦	♦	♦	♦	♦	♦
	Drum or disc brakes	♦	♦	♦	♦	♦	♦	♦	♦
	P.S.I. air inflation systems	♦	♦	♦	♦	♦	♦	♦	♦
	Brake dust covers	♦	♦	♦	♦	♦	♦	♦	♦
	ABS - 4S/2M or 2S/1M	♦	♦	♦	♦	♦	♦	♦	♦
	Steel, aluminum-milled or aluminum-polished wheels	♦	♦	♦	♦	♦	♦	♦	♦
	Axle straps	♦	♦	♦	♦	♦	♦	♦	♦
17.5", 19.5", or 22.5" tires		♦		♦		♦		♦	
22.5" or 24.5" tires	♦	♦			♦	♦	♦	♦	
L I G H T S	3-3-3 or 3-5-3 LED rear lights	♦	♦	♦	♦				
	4-3-4 or 2-3-2 LED rear lights					♦	♦	♦	♦
	Full pattern multi-diode lights	♦	♦	♦	♦	♦	♦	♦	♦
	Unlimited side marker lights	♦	♦	♦	♦	♦	♦	♦	♦
	Wide turn light on beam	♦	♦	♦	♦	♦	♦	♦	♦
	Over dimension lights	♦	♦	♦	♦	♦	♦	♦	♦
	Backup lights	♦	♦	♦	♦	♦	♦	♦	♦
	Strobe lights in center light panel	♦	♦	♦	♦	♦	♦	♦	♦
E L E C T R I C & A I R	Manual dock dump, auto dump, or electric dump valves	♦	♦	♦	♦	♦	♦	♦	♦
	Air raise and lower valves with or without plastic or aluminum box	♦	♦	♦	♦	♦	♦	♦	♦
	Pull lanyards on air tanks	♦	♦	♦	♦	♦	♦	♦	♦
	Air & electrical in two locations	♦	♦	♦	♦	♦	♦	♦	♦
	7 way in front bumper or rear panel	♦	♦	♦	♦	♦	♦	♦	♦
	4 way in front bumper or rear panel	♦	♦	♦	♦	♦	♦	♦	♦
	Liquid filled air gauge, digital electric air way, or smart scale	♦	♦	♦	♦	♦	♦	♦	♦
Hub-o-meter	♦	♦	♦	♦	♦	♦	♦	♦	
S E C U R E M E N T	Winch track - roadside, curbside, or both	♦	♦	♦	♦	♦	♦	♦	♦
	Sliding winches or fixed winches	♦	♦	♦	♦	♦	♦	♦	♦
	Sliding winches without winch track							♦	♦
	Tie bars	♦	♦	♦	♦	♦	♦	♦	♦
	J-hook track on siderail	♦	♦	♦	♦	♦	♦	♦	♦
	J-hook track on floor boards	♦	♦	♦	♦	♦	♦	♦	♦
	Recessed D-rings	♦	♦	♦	♦	♦	♦	♦	♦
	Recessed Chain ties	♦	♦	♦	♦	♦	♦	♦	♦
	Rope hooks	♦	♦	♦	♦	♦	♦	♦	♦
Container locks	♦	♦	♦	♦	♦	♦	♦	♦	
D & O V E R R A M P S	Fixed dovetails with and without ramps	♦	♦	♦	♦	♦	♦	♦	♦
	Detachable dovetails with and without ramps					♦	♦	♦	♦
	Top deck ramps	♦	♦	♦	♦	♦	♦	♦	♦
	16' Sturdi-lite ramps	♦	♦	♦	♦	♦	♦	♦	♦
	Bridge adapter for 2 ramps	♦	♦	♦	♦	♦	♦	♦	♦
	Ramp carriers	♦	♦	♦	♦	♦	♦	♦	♦
Load bunks with and without ramps	♦	♦	♦	♦	♦	♦	♦	♦	
S T O R I A G E &	Aluminum boxes, any size	♦	♦	♦	♦	♦	♦	♦	♦
	Steel boxes, any size	♦	♦	♦	♦	♦	♦	♦	♦
	Belly boxes, 96", 120", or 132"	♦	♦	♦	♦	♦	♦	♦	♦
	Dunnage boxes or dunnage racks	♦	♦	♦	♦	♦	♦	♦	♦
	Pull-out rear bumper or pull-out top deck					♦	♦	♦	♦
	Certificate Holder	♦	♦	♦	♦	♦	♦	♦	♦
	FHWA inspections	♦	♦	♦	♦	♦	♦	♦	♦
	Rubber dock bumpers	♦	♦	♦	♦	♦	♦	♦	♦
Crossfires	♦	♦	♦	♦	♦	♦	♦	♦	

Not all options are listed on the GSA website, please contact Doonan Specialized Trailer, LLC directly for specific GSA approved option pricing.

Not all options are compatible with other option combinations

Custom options are available upon request.